No.JXCX-OMU0022



# **Operation Manual**

**Product Name** 

## Controller setting software, (For 3 or 4-axis Step Motor Controller) Installation Manual

**Model/Series** 

# **JXC-MA1**

**SMC** Corporation

#### 1. Preparation

Prepare the following items before using this setting software (JXC Controller).

#### **1.1 Applicable Computer**

Prepare the PC according to the following operating environment.

Compatible OS*1	Windows ®7 (32bit / 64bit) Microsoft .NET Framework 2.0 is necessary. Windows® 8.1 (32bit / 64bit) Microsoft .NET Framework 3.5 is necessary.
Hard disk space	50MB or more
Interface	USB port (USB1.1 or USB 2.0)

\*1 If Microsoft.NET Framework is not installed during installation of the device, install Microsoft.NET Framework.

#### 1.2 USB Cable

Prepare USB cable (A-B type) (Product No.: JXC-MA1-2)

#### 2. Software Installation

Before starting the installation, please implement the following points:

- Login by a user account with authority of Administrator
- Terminate all other applications

#### 2.1 Installation of the software

Insert the CD-ROM into the CD/DVD drive.

Open the application folder (JXC\*2: \3-axis\Application\English, JXC\*3: \4-axis\Application\English). Right-click on "setup.exe" displayed in "Run as administrator".

Installation process starts. Install the software according to the instructions displayed on the screen.

岃 JXC Controller		
Select Installation Folder		
The installer will install JXC Controller to the following folder.		
To install in this folder, click "Next". To install to a different folder, enter it below	or click "Browse".	
Eolder: C:¥Program Files¥SMC CORPORATION¥JXC Controller¥	Browse	
Install JXC Controller for yourself, or for anyone who uses this compu	Disk Cost	Only when the setting software for JXC*3 is installed, the user sellection will be displayed. Select "Everyone".
Everyone		
⊚ Just <u>m</u> e		
Cancel < <u>B</u> ack	Next >	

The following "JXC" icon is displayed on the desktop when the installation is completed.

Setting software for JXC\*2:

Setting software for JXC\*3:





#### 2.2 Installation of the driver

- 1) Open the USB-Driver folder (JXC\*2: \3-axis\USB\_Driver, JXC\*3: \4-axis\USB\_Driver) in the CD-ROM. Select 32 bit or 64 bit depending on your PC. Right-click on "Install.bat" displayed in "Run as administrator".
- 2) The following screen will be displayed depending on the setup of the PC. Click Yes.



- 3) Command prompt is displayed.
- 4) The following screen will be displayed. Click the "Next".

Dev	vice Driver Installation Wizard
	Welcome to the Device Driver Installation Wizard! This wizard helps you install the software drivers that some computers devices need in order to work.
	< Back Next > Cancel
l	

5) The following screen will be displayed. Select "Always trust software from SMC K.K." and click the Install button. Select "Next".





6) The following display appears when installation is completed. Click the Finish button.

De	vice Driver Installation W	/izard
	Completing the De Installation Wizar	evice Driver d
	The drivers were successfully in	nstalled on this computer.
	You can now connect your dev came with instructions, please r	rice to this computer. If your device ead them first.
	Driver Name ✓ SMC CORPORATION (	Status Ready to use
		- 10 8.80 4 40.000 A
	< Back	Finish Cancel

7) Connect the USB cable as shown in the figure below, and supply power to the controller. The PC will recognize the connected controller automatically.





#### 3. Connection Check

Connect the USB cable, and supply power to the controller.

Double-click the JXC Controller icon on the PC desktop, and then confirmation of the communication between the PC and the controller will start. The screen below will be displayed when the communication is established correctly.



By selecting "Yes (Y)", the parameters and step data are uploaded automatically, after displaying the title screen. When selecting "No (N)", the software will start without uploading.

When the PC is not able to communicate with the controller, the following screen will be displayed.

JXC Controller	<b>×</b>
USB cable is not connected. This application starts in	offline state.
	ОК

When "OK" is selected, the title window will be displayed. And the title window will disappear in a few seconds, but it can be skipped by clicking on the title window.

	CA SMC
	Controller Setting Software
/	For Multi-axis Controller
/	
Application version Controller version	SMC Corporation Copyright (C) 2015

(The above title window of the setting software for JXC\*3 is the same as it for JXC\*2.)



#### The main window as shown below is then displayed.

🛃 JXC Controller Ver 0.73 Y4		
$File(\underline{F})$ $View(\underline{V})$ $Window(\underline{W})$ $Help(\underline{H})$		
Status Teaching Parameter	Step Data Alarm Test drive	OVON     O Normal mode       OFF     OR       ON     Maintenance
	Communication sta	atus
🛃 St 🗗 🗉 🔀 🖬 Te 🗗 🗉 🔀		a Ala 🎯 🖻 🔀 Te 🗗 🖲 🖾
Axis 1:01- Axis 2:01- Axis 3:01- Axis 4:01- Current S	itep data No. : Offline	

(The above main window of the setting software for JXC\*3 is the same as it for JXC\*2.)

The communication status is displayed at the bottom of the main window.

Display	Details
Offline	Off-line state
Online	On-line state

When the PC is able to communicate with the controller, "On-line" status is established automatically. If the communication is in the off-line state, the PC is not able to communicate with the controller. Please check the following.

- Check that power is supplied to the connected controller.
- Check that the controller and the computer are connected to each other via the USB cable.
- Check that the USB driver is installed correctly.

### **A** Caution

Do not turn off the controller for communication while the setting software (JXC Controller) is running.

Do not connect or disconnect the cable while the setting software is running.

The communication is being established continuously while the setting software is running. Disconnecting the cable during communication may cause the software to become corrupt.



#### 4. Software Removal

The following is the procedure to uninstall both the controller setting software and the driver.

#### 4.1 Uninstallation of the controller setting software

- 1) Open the "Start menu" -> "Control Panel", then double-click on "Programs and Features" or click "Uninstall a program" (this varies according to the control panel).
- 2) Select "JXC Controller" from the list of "Add or Remove Programs". And then, select the "Uninstall".
- 3) Click "Yes (Y)".
- 4) When uninstallation of the controller setting software is completed, the uninstallation program will end automatically.

#### 4.2 Uninstallation of the USB driver

If the controller is connected, the uninstallation of the driver might fail. Uninstall the driver with the controller disconnected, as follows:

- Turn off the power supply to the controller. Open the "Start menu" -> "Control Panel", double-click "Programs and Features" or click "Uninstall a program" (this varies according to the control panel).
- Select "Windows Driver Package- SMC CORPORATION (JXCUSBDRIVER)..." from the list of "Add or Remove Programs". Click on the "Uninstall".
- 3) The following screen is displayed. Select "Yes".



4) Program removal will be executed. When the removal is completed, "Windows Driver Package-SMC CORPORATION (JXCUSBDRIVER)." should have been removed from the list of "Add or Remove Programs".





Revision history First edition: February 2017

### **SMC** Corporation

4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021 JAPAN Tel: + 81 3 5207 8249 Fax: +81 3 5298 5362 URL <u>http://www.smcworld.com</u>

Note: Specifications are subject to change without prior notice and any obligation on the part of the manufacturer. @ 2017 SMC Corporation All Rights Reserved

