

Rotary Actuator

Ø 30, Ø 50, Ø 63, Ø 80, Ø 100

New

RoHS

Compact auto switches are mountable.
(D-M9□)

Width reduced by
up to 14 mm

Space saving by
changing the auto
switch rail mounting to
groove mounting.




Current model




Mountable on
2 surfaces.

Compact
auto switch



Auto switch can be mounted from the front.

- Auto switch can be mounted from the front at any position on the mounting groove.
- Auto switch can be mounted after installation or when installation condition is changed.





Weight is reduced by up to 14 %.

- Lightweight body by changing the body and the cover shape.

Size	CRA1 [kg]	Current model [kg]	Reduction rate [%]
30	0.27	0.3	10
50	1.3	1.5	13
63	2.2	2.5	12
80	3.9	4.3	10
100	7.3	8.5	14

Mounting interchangeable with the current model


Series **CRA1**



Standard type

Size: 30, 50, 63, 80, 100


Rotating angle	30	90°, 180°
	50 to 100	90°, 180°, 100°, 190°



Angle adjustable type

Size: 50, 63, 80, 100

Rotating angle	50 to 100	90°, 180°, 100°, 190°
----------------	-----------	-----------------------



CAT.EUS20-232C-UK

Standard type

Cushion seal is replaceable.




Cushion seal has been made replaceable.
(Not possible for current model. Cushion seal only)

Replacement parts	• Slider	• Tube gasket
	• Piston seal	• Spring pin
	• Cushion seal (New)	

Interchangeable with current model

Exterior dimension, shaft diameter, and mounting dimension are interchangeable with current model.

Rotating angle



Compact auto switches are mountable.

Solid state auto switch

- D-M9□
- D-M9□W

Reed auto switch

- D-A9□



Easy adjustment of cushion valve


- Cushion valve shape is changed so it can be adjusted using a hexagon wrench only.
- No protrusion from the body.
- Retaining ring is used to prevent drop-out.

Port, cushion valve and auto switch are on the same surface.

Easy to handle.


* Cushion valve cannot be mounted on the air-hydro type.

With cushion valve retaining ring




Mountable on 2 surfaces.

Auto switches can be mounted in two rows.



Auto switches can be mounted in two rows.

Auto switches can be mounted in two rows.



Many variations of shaft type

Current model


Standard : 2 types
Semi-standard : 6 types




Series **CRA1**
Standard: 8 types

- Shaft type can be selected to suit the specification.
- Part number is assigned for shaft types <single round shaft, double shaft (round shaft, with four chamfers), double round shaft>.


Single shaft with four chamfers:
CRA1BX




Double shaft with key:
CRA1BY




Double shaft with four chamfers:
CRA1BZ




Single round shaft:
CRA1BT



Double shaft (round shaft, with four chamfers):
CRA1BJ



Double round shaft:
CRA1BK




* Single round shaft, double shaft (round shaft, with four chamfers), double round shaft are made to order.


Mounting suitable for operating conditions is possible.

Foot bracket can be mounted at a desired position. (Foot bracket is included in the rotary actuator at shipment.)


Bottom side




Shaft side



Port side





Back side



Angle adjustable type

Angle can be adjusted to a desired level in a range of up to 90°.



Angle can be adjusted to an appropriate level suitable for applications.

Angle adjusting screw

Rotary Actuator Series **CRA1** Ø 30, Ø 50, Ø 63, Ø 80, Ø 100



Standard type



Angle adjustable type

Series Variations

Type			Pneumatic					Air-hydro			
Size			30	50	63	80	100	50	63	80	100
Standard	Rotating angle	90°	●	●	●	●	●	●	●	●	●
		100°		●	●	●	●	●	●	●	●
		180°	●	●	●	●	●	●	●	●	●
		190°		●	●	●	●	●	●	●	●
	Shaft type	Single shaft	S	●	●	●	●	●	●	●	●
		Double shaft	W	●	●	●	●	●	●	●	●
		Single shaft with four chamfers	X	●	●	●	●	●	●	●	●
		Double shaft with key	Y	●	●	●	●	●	●	●	●
		Double shaft with four chamfers	Z	●	●	●	●	●	●	●	●
		Single round shaft	T	●	●	●	●	●	●	●	●
		Double shaft (round shaft, with four chamfers)	J	●	●	●	●	●	●	●	●
		Double round shaft	K	●	●	●	●	●	●	●	●
	Cushion	None		●	●	●	●	●	●	●	●
		Air cushion		●	●	●	●	●	●	●	●
	Variations	With auto switch		●	●	●	●	●	●	●	●
		Angle adjustable type		●	●	●	●				
		Clean series <small>Note)</small>	11-	●	●						
	Mounting bracket	Flange	F		●	●	●	●	●	●	●
		Foot	L	●	●	●	●	●	●	●	●
Made to Order	Pattern	Shaft type pattern		●	●	●	●	●	●	●	●
		Rotation range		●	●	●	●	●	●	●	●
		Port location		●	●	●	●	●	●	●	●
	Stainless steel shaft/bolt/parallel key		-X 6	●	●	●	●	●			
	Operating temperature	Heat resistant 100 °C	-X 7	●	●	●	●	●			
	Both sides angle adjustable		-X10		●	●	●	●			
	One side angle adjustable, One side with cushion		-X11		●	●	●	●			
	Fluororubber seal		-X16	●	●	●	●	●			

Поворотный привод

CDRA1BW

Типоразмер: 30~100

- Реечно-шестеренчатый тип
- Высокое отношение крутящего момента к габаритам
- Угол поворота 90°/100°/180°/190°
- Возможность установки универсальных датчиков положения D-A9(V)L, D-M9(V)L
- Непосредственный или фланцевый монтаж, исполнения с одно- и двусторонним валом, с пневматическим демпфером (по запросу)

Технические характеристики

Среда		Сжатый воздух, с содержанием или без содержания масла				
Рабочее давление (МПа)		0.1~1				
Температура окружающей среды (°C)		0~60				
Монтажное положение		произвольное				
Угол поворота		90° и 180° 90°,100°,180°,190°				
Исполнение вала		С одной стороны – призматическая шпонка, с другой стороны – четырехгранник				
Типоразмер		30	50	63	80	100
Присоединительная резьба – цилиндрическая трубная резьба		M5	G1/8	G1/8	G1/4	G3/8
Внутренний объем (см³)	90°	7.4	32	60	111	259
	180°	14	65	120	221	518
Вес (кг)	90°	0.3	1.3	2.2	3.9	7.3
	180°	0.4	1.5	2.6	4.4	8.3
Макс. кинет. энергия (Нм)		0.01	0.05	0.12	0.16	0.55
Допустимое время поворота * (с/90°)		0.2~1	0.2~2	0.2~3	0.2~4	0.2~5

* Время поворота зависит от начального момента инерции масс, см. стр. 2-127

Типоразмер 30




Типоразмер 50 ~ 100





Крутящий момент

Типоразмеры 30-50



Типоразмеры 63-100



Номер для заказа (без датчиков положения)

Типоразмер	Угол поворота 90°	Угол поворота 180°	Угол поворота 100°	Угол поворота 190°
30	ECDRA1BW30-90	ECDRA1BW30-180	-	-
50	CDRA1BW50TF-90Z	CDRA1BW50TF-180Z	CDRA1BW50TF-100Z	CDRA1BW50TF-190Z
63	CDRA1BW63TF-90Z	CDRA1BW63TF-180Z	CDRA1BW63TF-100Z	CDRA1BW63TF-190Z
80	CDRA1BW80TF-90Z	CDRA1BW80TF-180Z	CDRA1BW80TF-100Z	CDRA1BW80TF-190Z
100	CDRA1BW100TF-90Z	CDRA1BW100TF-180Z	CDRA1BW100TF-100Z	CDRA1BW100TF-190Z

Исполнения с односторонним валом и (или) пневматическим демпфером - по запросу


Технические характеристики

Допуски по углу поворота


Типоразмер	Угол поворота
30	±3°
50-100	+4°~0°

Давление на входе "А"
вызывает поворот по часовой стрелке
Давление на входе "В"
вызывает поворот против часовой стрелки

ECDRA1BW30




CDRA1BW 50-100




Нагрузки на вал в Н
(статическая нагрузка)

Типоразмер	Направление усилия		
	Fsa	Fsb	Fr
30	30		
50	500	200	200
63	600	200	300
80	900	200	400
100	1000	200	600

Вышеприведенная таблица относится только к статической нагрузке. При динамической нагрузке грузы не должны устанавливаться непосредственно на поворотном валу. При этом могут использоваться следующие конструктивные варианты.




Конструктивные предложения при динамической нагрузке на вал




Поворотный привод CDRA1BW

Конструкция

Типоразмер 30



Типоразмеры 50-100



Спецификация. Типоразмер 30

Поз	Обозначение	Материал
1	Корпус цилиндра	Алюминий
2	Крышка	Алюминий
3	Крышка	Алюминий
4	Поршень	Алюминий
5	Вал	Хромистая сталь
6	Рама/зубчатая рейка	Сталь
7	Упор	Сталь
8	Стопорный винт	Сталь
9	Ползунок	Дельрин
10	Крепежный винт	Сталь
11	Опора подшипника	Алюминий
12	Винт с крестовым шлицем	Сталь
13	Шарикоподшипник	
14	Крепежный винт	Сталь
15	Винт с крестовым шлицем	Сталь
16	Гайка	Сталь
17	Пружинное кольцо	Сталь
18	Подпружиненный палец	Сталь
19	Шпонка	Сталь
20	Кольцевая прокладка круглого профиля	NBR
21	Уплотнительное кольцо С-образного профиля	NBR

Спецификация. Типоразмеры 50 - 100

Поз	Наименование	Материал
1	Корпус цилиндра	Алюминий
2	Крышка	Алюминий
3	Крышка	Алюминий
4	Поршень	Алюминий
5	Вал	Сталь
6	Рама/зубчатая рейка	Сталь
7	Ползунок	Полимер
8	Опора подшипника	Алюминий
9	Уплотнение гильзы	NBR
10	Уплотнение поршня	NBR
11	Подшипник	Подшипниковая сталь
12	Винт с шайбой	Сталь
13	Подпружиненный палец	Сталь
14	Шпонка	Сталь
15	Винт	Сталь
16	Винт	Сталь
17	Компенсационное кольцо	Полимер
18	Датчик положения	-
19	Магнит	-
20	Крепление датчика	Полимер

Ремкомплект


Типоразмер	Код для заказа
30	КТ-CRA1B30 ¹⁾
50	P694020-20 ²⁾
63	P694030-20 ²⁾
80	P694040-20 ²⁾
100	P694050-20 ²⁾

1) Комплект уплотнений, включающий поз. 9/20/21

2) Комплект уплотнений, включающий поз. 7/9/10 (по 2 шт.), поз. 13 (4 шт.) и 10 г смазки


Размеры

Типоразмер 30



Типоразмер	Присоед. резьба G	A	B	C	D (g6)	DD (h9)	F	H	J	K	S	U	W	BA	BB	CA	CB	SA	SB	SC	SD	SE
CDRA1BS50	1/8	62	48	46	15	25	2.5	36	M8x8	5	156(189)	98	17	17	8.5	8.5	13	33	13.5	12	14	34
CDRA1BS63	1/8	76	60	57	17	30	2.5	41	M10x12	5	175(213.5)	117	19.5	20	10	10	14	33	14.5	12	21	34
CDRA1BS80	1/4	92	72	70	20	35	3	50	M12x13	5	199(243)	142	22.5	23.5	12	12	18	33	15.5	12	29	34
CDRA1BS100	3/8	112	85	85	25	40	4	60	M12x14	5	259(325)	172	28	25	12.5	12.5	18	33	16	12	39	34

Типоразмеры 50-100



Типоразмер	Присоед. резьба G	A	B	C	D (g6)	DD (h9)	F	H	J	K	С датчиком					U	W	BA	BB	BC	CA*	CB*	Размеры шпонки	
											S	SB	SC	SD	SE								b	L1
CDRA1BS50	1/8	62	48	46	15	25	2.5	36	M8x8	5	156(189)	1.5	5	14.5	33	98	17	17	8.5	6	9.5	7.5	5 _{h9}	25
CDRA1BS63	1/8	76	60	57	17	30	2.5	41	M10x12	5	175(213.5)	1.5	5	21.5	33	117	19.5	20	10	7	11	8	6 _{h9}	30
CDRA1BS80	1/4	92	72	70	20	35	3	50	M12x13	5	199(243)	1.5	5	29.5	33	142	22.5	23.5	12	8	13	9	6 _{h9}	40
CDRA1BS100	3/8	112	85	85	25	40	4	60	M12x14	5	259(325)	1.5	5	39.5	33	172	28	25	12.5	8	14	10	8 _{h9}	45

Поворотный привод


CDRA1BW

Время поворота


Типоразмер 30




Типоразмер 50



Типоразмер 63



Типоразмер 80



Типоразмер 100



Примеры расчета момента инерции см. на стр. 2-127

Герконовые датчики и электронные датчики

Технические характеристики

D-A73L, D-F7PL (с индикатором рабочего состояния), D-A80L (без индикатора рабочего состояния) + длина кабеля 3м								
Номер для заказа	D-A73L		D-A80L			D-F7PL		
Рабочее напряжение	24VDC	110VAC	24VDC	48VDC	110VAC	PNP 24VDC		
Макс. ток (мА)	5~40	5~18	50	40	18	100мА		
Внутреннее падение напряжения	<2.4 V		—			при 50 мА < 0.4V при 100 мА < 0.8V		
Схема защиты	—							
Ток утечки	—							
Индикатор рабочего состояния	ВКЛ = красный светодиод		—			ВКЛ = красный светодиод		

- Время срабатывания – 1,2 мс
- Исполнение кабеля – маслостойкий винил, наружн. Ø3,4мм, 0,2мм², 2 жилы (красная, черная)
- Устойчивость к ударным нагрузкам – 30 G, D-F5PL: 100 G
- Сопротивление изоляции – не менее 50 МОм при измерении с напряжением 500 VDC
- Испытательное напряжение – 1500 VAC, D-F5PL: 1000 VAC (в течение 1 мин)
- Температура окружающей среды от – 10 до + 60 °C
- Степень защиты – IEC IP67, а также водонепроницаемость по JISCO920, маслостойкость

Герконовые датчики и электронные датчики


Выбор датчика положения

Типоразмер	Датчики положения				
	D-M9(V)L	D-A9(V)L	D-A73L	D-A80L	D-F7PL
30			●	●	●
50	●	●			
63	●	●			
80	●	●			
100	●	●			


Характеристики универсальных датчиков положения D-A9(V)L, D-M9(V)L приведены на стр. 2-219

Схемы подключения


D-A73L




D-A80L



D-F7PL




Монтажное положение
универсальных датчиков положения D-A9(V)L, D-M9(V)L




Типоразмер	Угол поворота	Герконовые датчики D-A9		Электронные датчики D-M9	
		A	Зона переключений θ	A	Зона переключений θ
50	90°	18.5	44°	22.5	30°
	180°	35		39	
63	90°	21	49°	25	28°
	180°	40.5		44.5	
80	90°	23.5	41°	27.5	23°
	180°	45.5		49.5	
100	90°	38.5	29°	42.5	15°
	180°	71.5		75.5	

Размеры


D-A73L / D-A80L



D-F7PL



Установка универсальных датчиков положения D-A9(V)L, D-M9(V)L
в профильных пазах корпуса привода



CONTENTS

Rotary Actuator Series **CRA1**


CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order



● Rotary Actuator Series CRA1

How to Order	Page 5
Specifications	Page 6
Dimensions	Page 7
Construction	Page 13

● Rotary Actuator: Angle Adjustable Type Series CRA1□□U

How to Order	Page 15
Specifications	Page 16
Dimensions	Page 17
Construction	Page 18

● Auto Switch Mounting

Page 19

● Simple Specials/Made to Order

Simple specials


Shaft pattern sequencing I	-XA1 to -XA24	Page 23
Shaft pattern sequencing II	-XA33 to -XA59	Page 27

Made to Order

How to Order	Page 32
① Reversed shaft -XC7	Page 33
② Change of rotation range -XC8 to -XC11	Page 33
③ Changed to fluorine grease -XC30	Page 33
④ Change of rotation range and shaft rotation direction -XC31 to XC36	Page 34
⑤ Change of rotation range and angle adjusting direction -XC37 to XC42	Page 35
⑥ Change of rotation range and angle adjusting direction -XC43 to XC46	Page 36
⑦ Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.) -XC47 to XC52	Page 37
⑧ Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.) -XC53 to XC58	Page 38
⑨ Change of port location (Mounting location of the cover is changed.) -XC59 to XC61	Page 39
⑩ One side air-hydro, One side air -XC63, -XC64	Page 39
⑪ Stainless steel shaft/Bolt/Parallel key -X6	Page 40
⑫ Heat resistant -X7	Page 40
⑬ Both sides angle adjustable -X10	Page 40
⑭ One side angle adjustable, One side with cushion -X11	Page 41
⑮ Fluororubber seal -X16	Page 41
Made to Order/-X6 to -X16	Page 42

Specific Product Precautions

Page 43




Rotary Actuator

Series CRA1

RoHS

Rack & Pinion Type/Size: 30, 50, 63, 80, 100



How to Order

CRA1 B S 50 - 90 Z

With auto switch CDRA1 B S 50 - 90 Z - M9BW

Built-in magnet

Mounting

B	Basic type
L Note 1, 2)	Foot type
F Note 3)	Flange type

Note 1) For foot bracket and part number, refer to page 6.
 Note 2) Foot bracket is included in the same package, (but not assembled).
 Note 3) Except size 30.

Size

30
50
63
80
100

Rotating angle

90	90°
180	180°
100 Note)	100°
190 Note)	190°

Note) Except size 30

Number of auto switches

—	2 pcs.
S	1 pc.

Note) Up to two auto switches are mountable.

Auto switch

—	Without auto switch (Built-in magnet)
----------	---------------------------------------

Note) For applicable auto switch model, refer to the table below.

Air cushion

—	None
C Note)	With air cushion

Note) Except air-hydro type.

Port type

Size	30	50	63	80	100
—	M thread	M5	—	—	—
—	Rc	—	—	—	—
TF	G	—	1/8	1/8	1/4
TN	NPT	—	1/8	1/8	1/4
TT	NPTF	—	1/8	1/8	1/4

Shaft type

S	Single shaft
W	Double shaft
X	Single shaft with four chamfers
Y	Double shaft with key
Z	Double shaft with four chamfers
T	Single round shaft
J	Double shaft (round shaft, with four chamfers)
K	Double round shaft

Note 1) Flange type is not available for T, J, K.
 Note 2) T, J, K are made to order.

Type

—	Pneumatic
H Note)	Air-hydro

Note) Except size 30. Refer to page 43 for handling precautions.

Made to Order
 Refer to page 6.

Applicable Auto Switches/Refer to the **WEB catalogue** or the Auto Switch Guide for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load	
					DC	AC	Perpendicular	In-line	0.5 (—)	1 (M)	3 (L)	5 (Z)			
Solid state auto switch	Diagnosis indication (2-color indication)	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	M9NV	M9N	●	●	●	○	○	IC circuit	Relay, PLC
				3-wire (PNP)		12 V	M9PV	M9P	●	●	●	○	○	—	
				2-wire		5 V, 12 V	M9BV	M9B	●	●	●	○	○	—	
				3-wire (NPN)		5 V, 12 V	M9NWV	M9NW	●	●	●	○	○	IC circuit	
				3-wire (PNP)		12 V	M9PWV	M9PW	●	●	●	○	○	—	
				2-wire		5 V, 12 V	M9BWV	M9BW	●	●	●	○	○	—	
	Water resistant (2-color indication)	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	M9NAV*1	M9NA*1	○	○	●	○	○	IC circuit	
				3-wire (PNP)		12 V	M9PAV*1	M9PA*1	○	○	●	○	○	—	
				2-wire		100 V	M9BAV*1	M9BA*1	○	○	●	○	○	—	
				2-wire		100 V or less	M9BAV*1	M9BA*1	○	○	●	○	○	—	
Red auto switch	—	Grommet	Yes	3-wire (NPN equivalent)	24 V	5 V	A96V	A96	●	—	●	—	—	IC circuit	Relay, PLC
				2-wire		100 V	A93V*2	A93	●	●	●	●	—	—	
				2-wire		100 V or less	A90V	A90	●	—	●	—	—	IC circuit	

*1 Although it is possible to mount water resistant type auto switches, note that the rotary actuator itself is not of water resistant construction.


*2 1 m type lead wire is only applicable to D-A93.

* Lead wire length symbols: 0.5 m — (Example) M9NW
 1 m M (Example) M9NWM
 3 m L (Example) M9NWL
 5 m Z (Example) M9NWZ

* Auto switches marked with "○" are produced upon receipt of order.

* Auto switches are shipped together, (but not assembled).

Made to Order Refer to the **WEB catalogue** or the Auto Switch Guide for detailed solid state auto switches with pre-wired connectors.



Made to Order

(For details, refer to pages 22 to 42.)


Symbol	Description	Applicable shaft type
-XA1 to -XA24	Shaft pattern sequencing I	S, W, Y
-XA33 to -XA59	Shaft pattern sequencing II	X, Z, T, J, K
-XC7	Reversed shaft	S, W, X, T, J
-XC8 to -XC11	Change of rotation range	S, W, Y
-XC30	Changed to fluorine grease	S, W, X, Y, Z, T, J, K
-XC31 to -XC36	Change of rotation range and shaft rotation direction	S, W, Y
-XC59 to -XC61	Change of port direction	S, W, X, Y, Z, T, J, K
-XC63, -XC64	One side air-hydro, One side air	S, W, X, Y, Z, T, J, K
-X6	Stainless steel shaft/bolt, etc.	S, W, X, Y, Z, T, J, K
-X7*	Heat resistant (100 °C)	S, W, X, Y, Z, T, J, K
-X16	Fluororubber seal	S, W, X, Y, Z, T, J, K

* X7: Not available for the built-in magnet type


Rotation Range of Keyway

The shaft rotates clockwise when the pressure is applied from the A port while it rotates counterclockwise when the pressure is applied from the B port.

Size: 30



Size: 50 to 100



Specifications

Type	Pneumatic					Air-hydro			
Size	30	50	63	80	100	50	63	80	100
Fluid	Air (Non-lube)					Turbine oil			
Max. operating pressure	1.0 MPa								
Min. operating pressure	0.1 MPa								
Ambient and fluid temperature	0 to 60 °C (No freezing)								
Cushion	Not attached, Air cushion					None			
Backlash	None*	Within 1°							
Tolerance in rotating angle	—	0 to +4°							

* Since the CRA1□30 has a stopper installed, there is no backlash produced under pressure.

Effective Torque

Size	Operating pressure [MPa]										[N·m]
	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	
30	0.38	0.76	1.14	1.53	1.91	2.29	2.67	3.05	3.44	3.82	
50	1.85	3.71	5.57	7.43	9.27	11.2	13.0	14.9	16.7	18.5	
63	3.44	6.88	10.4	13.8	17.2	20.6	24.0	27.5	31.0	34.4	
80	6.34	12.7	19.0	25.3	31.7	38.0	44.4	50.7	57.0	63.4	
100	14.9	29.7	44.6	59.4	74.3	89.1	104	119	133	149	

Allowable Kinetic Energy/Adjustable Range of Rotation Time Safe in Operation

Size	Allowable kinetic energy [J]		Adjustable range of rotation time safe in operation [s/90°]
	Without air cushion	With air cushion*	
30	0.01	0.12	0.2 to 1
50	0.05	0.98	0.2 to 2
63	0.12	1.50	0.2 to 3
80	0.16	2.00	0.2 to 4
100	0.54	2.90	0.2 to 5

* Allowable kinetic energy of the product with air cushion is the maximum absorbed energy when the cushion valve adjustment is optimised.

Weight

Size	Standard weight		Additional weight			[kg]
	90°	180°	With auto switch*	Foot bracket	Flange bracket	
30	0.27	0.36	0.1	0.1	—	
50	1.3	1.5	0.2	0.3	0.5	
63	2.2	2.6	0.4	0.5	0.9	
80	3.9	4.4	0.6	0.9	1.5	
100	7.3	8.3	0.9	1.2	2.0	

* With 2 auto switches

Foot Bracket/Part No.

Size	Foot bracket	Contents	Mounting screw size included in foot bracket
30	CRA1L30-Y-1Z	Foot bracket : 2 pcs. Mounting screw: 4 pcs. Collar* : 4 pcs.	M5 x 0.8 x 25
50	CRA1L50-Y-1Z		M8 x 1.25 x 35
63	CRA1L63-Y-1Z		M10 x 1.5 x 40
80	CRA1L80-Y-1Z		M12 x 1.75 x 50
100	CRA1L100-Y-1Z		M12 x 1.75 x 50

* Size 30 does not include collars.

* Remove the basic type mounting screws and use the mounting screws included in the foot bracket to secure the foot bracket to the cover. Use the collar as a spacer for the cover counterbore part and secure it together with the foot.






* For size 30, be careful not to drop the cover when removing the basic type mounting screws. Additionally, do not mount the foot bracket with the pressure applied to the port.

Series CRA1

Dimensions/Basic Type: C□RA1B□

Size: 30

Single shaft: C□RA1BS





- Drawing shows the appearance for rotation of 90°.
 - Dimensions show pressurisation to B port.
 - Drawing shows that the auto switch is mounted on the side opposite to the port side. (Dimensions with an asterisk mark (*) are not required for actuators without the auto switch.)
- * () are the dimensions for rotation of 180°.
- Note) A parallel key is included in the same package, (but not assembled).



Dimensions/Basic Type: C□RA1B□

Size: 50/63/80/100

Single shaft: C□RA1BS



- Drawing shows the appearance for rotation of 90° and 100°.
 - Dimensions show pressurization to B port.
 - Drawing shows the auto switch mounted on the port side.
- * () are the dimensions for rotation of 180° and 190°.

* () are the dimensions for rotation of 180° and 190°.																							[mm]		
Size	Port size	A	B	C	D (g6)	DD (h9)	F	H	J	K	With auto switch					Without auto switch	U	W	BA	BB	BC	★ CA	★ CB	Key dimensions ^(Note)	
											S	SB	SC	SD	SE	S								b	L1
50	1/8	62	48	46	15	25	2.5	36	M8 × 1.25 depth 8	5	156 (189)	1.5	5	14.5	33	144 (177)	98	17	17	8.5	6	9.5	7.5	5 ⁰ _{-0.030}	25
63	1/8	76	60	57	17	30	2.5	41	M10 × 1.5 depth 12	5	175 (213.5)	1.5	5	21.5	33	163 (201.5)	117	19.5	20	10	7	11	8	6 ⁰ _{-0.030}	30
80	1/4	92	72	70	20	35	3	50	M12 × 1.75 depth 13	5	199 (243)	1.5	5	29.5	33	186 (230)	142	22.5	23.5	12	8	13	9	6 ⁰ _{-0.030}	40
100	3/8	112	85	85	25	40	4	60	M12 × 1.75 depth 14	5	259 (325)	1.5	5	39.5	33	245 (311)	172	28	25	12.5	8	14	10	8 ⁰ _{-0.036}	45


Note) A parallel key is included in the same package, (but not assembled).

Series CRA1

Dimensions/Basic Type: C□RA1B□


Size: 30/50/63/80/100

Single shaft with four chamfers: C□RA1BX Double shaft with key: C□RA1BY Double shaft with four chamfers: C□RA1BZ




Note) Other dimensions are the same as the single shaft type. [mm]

Size	G	H	N	U	L
30	6	13	8	53	7.8
50	11	27	15	89	14
63	13	29	17	105	16
80	15	38	20	130	19
100	19	44	25	156	24



Note) Other dimensions are the same as the single shaft type. [mm]


Size	H	K	UU	L
30	25	3	90	14
50	36	5	134	25
63	41	5	158	30
80	50	5	192	40
100	60	5	232	45



Note) Other dimensions are the same as the single shaft type. [mm]


Size	D (g6)	G	H	M	N	U	UU	L
30	8	6	13	10	8	53	63	7.8
50	15	11	27	20	15	89	109	14
63	17	13	29	22	17	105	127	16
80	20	15	38	25	20	130	155	19
100	25	19	44	30	25	156	186	24

Single round shaft: C□RA1BT Double shaft (round shaft, with four chamfers): C□RA1BJ Double round shaft: C□RA1BK




Note) Other dimensions are the same as the single shaft type. [mm]

Size	D (g6)	H
30	8	25
50	15	36
63	17	41
80	20	50
100	25	60



Note) Other dimensions are the same as the single shaft type. [mm]

Size	D (g6)	G	H	M	N	UU	L
30	8	6	25	10	8	75	7.8
50	15	11	36	20	15	118	14
63	17	13	41	22	17	139	16
80	20	15	50	25	20	167	19
100	25	19	60	30	25	202	24




Note) Other dimensions are the same as the single shaft type. [mm]

Size	D (g6)	H	UU
30	8	25	90
50	15	36	134
63	17	41	158
80	20	50	192
100	25	60	232

Dimensions/Foot Type: C□RA1L□

Size: 30



- Drawing shows the appearance for rotation of 90°.
 - Dimensions show pressurisation to B port.
 - Drawing shows that the auto switch is mounted on the side opposite to the port side.
- * () are the dimensions for rotation of 180°.

CRA1

CRA1□□U

Auto Switch Mounting



Simple Specials

Made to Order

Series CRA1

Dimensions/Foot Type: C□RA1L□


Size: 50/63/80/100



- Drawing shows the appearance for rotation of 90° and 100°.
 - Dimensions show pressurisation to B port.
 - Drawing shows that the auto switch mounted on the port side.
- * () are the dimensions for rotation of 180° and 190°.

Note) Other dimensions are the same as the basic type. [mm]

Size	LA	LB	LC	With auto switch		Without auto switch		LF	LH	LT
				LD	LE	LD	LE			
50	62	9	44	212 (245)	236 (269)	200 (233)	224 (257)	41	108	4.5
63	76	11	55	247 (285.5)	275 (313.5)	235 (273.5)	263 (301.5)	48	127	5
80	92	13	67	287 (331)	329 (373)	274 (318)	316 (360)	58	154	6
100	112	13	87	347 (413)	389 (455)	333 (399)	375 (441)	73.5	189.5	6




Dimensions/Flange Type: C□RA1F□

Size: 50/63/80/100

Single shaft: C□RA1FS

Double shaft: C□RA1FW


Single shaft with four chamfers: C□RA1FX



Note) Other dimensions are the same as the basic type.

Size	F	H	MM	U	FD
50	4	39	M6 x 1.0 depth 12	114	9
63	5	45	M6 x 1.0 depth 12	136	11.5
80	5	55	M8 x 1.25 depth 16	165	13.5
100	5	60	M10 x 1.5 depth 20	190	13.5


Size	FT	FX	FY	ZX	ZY
50	13	90	50	110	81
63	15	105	59	130	101
80	18	130	76	160	119
100	18	150	92	180	133



Note) Other dimensions are the same as the single shaft type. [mm]


Size	H	N	U	UU
50	39	15	114	134
63	45	17	136	158
80	55	20	165	190
100	60	25	190	220

Double shaft with key: C□RA1FY



Note) Other dimensions are the same as the single shaft type. [mm]


Size	H	U	UU
50	39	114	150
63	45	136	177
80	55	165	215
100	60	190	250



Note) Other dimensions are the same as the single shaft type. [mm]

Size	H	N	U
50	30	15	105
63	33	17	124
80	43	20	153
100	44	25	174

Double shaft with four chamfers: C□RA1FZ



Note) Other dimensions are the same as the single shaft type. [mm]


Size	H	N	U	UU
50	30	15	105	125
63	33	17	124	146
80	43	20	153	178
100	44	25	174	204

The dimensions of shaft key and four chamfers are the same as the basic type. For details, refer to page 9.


Series CRA1

Construction: Size 30


Without air cushion



With air cushion



Without air cushion With auto switch



Component Parts

No.	Description	Material	Note
1	Body	Aluminium alloy	Anodised
2	Right cover	Aluminium alloy	Metallic coating
3	Left cover	Aluminium alloy	Metallic coating
4	Piston	Aluminium alloy	
5	Shaft	Alloy steel	
6	Rack	Carbon steel	Nitrided
7	Slider	Resin	
8	Bearing retainer	Zinc alloy	Chromated
9	Tube gasket	NBR	
10	Piston seal	NBR	
11	Bearing	High carbon chrome bearing steel	
12	Hexagon socket head cap screw with washer	Alloy steel	Zinc chromated
13	Spring pin	Steel	Zinc chromated
14	Parallel key	Carbon steel	
15	Cross-recessed pan head tapping screw	Steel	Zinc chromated
16	Auto switch	—	
17	Magnet	—	
18	Switch spacer	Resin	
19	Cushion ring	Aluminium alloy	Anodised
20	Cushion valve	Steel	Nickel plated
21	Cushion seal	Urethane	
22	O-ring	NBR	

No.	Description	Material	Note
23	Seal retainer	Steel	
24	Parallel key	Carbon steel	
25	Stopper	Alloy steel	
26	Piston holding bolt	Alloy steel	Zinc chromated
27	Hexagon socket head set screw	Alloy steel	Zinc chromated
28	Hexagon nut	Steel	Zinc chromated
29	O-ring	NBR	

Replacement Parts

Size	Part no.		
	Without air cushion	With air cushion	Air-hydro
Note 2) 90°	P694010-20	P694010-22	—
30 180°	P694010-21	P694010-23	—
Corresponding parts	⑦, ⑨, ⑩, ⑬ are included as a set. ⑦, ⑨, ⑩, ⑬, ⑰ are included as a set.		

Note 1) When ordering replacement parts, write "1" for one set of the parts per actuator.

Note 2) Replacement parts for different rotation angles are set.


A grease pack (10 g) is included.

If an additional grease pack is needed, order with the following part number.


Grease pack part number: GR-S-010 (10 g)

Construction: Size 50 to 100


Without air cushion



With air cushion



Without air cushion With auto switch



Component Parts

No.	Description	Material	Note
1	Body	Aluminium alloy	Anodised
2	Right cover	Aluminium alloy	Metallic coating
3	Left cover	Aluminium alloy	Metallic coating
4	Piston	Aluminium alloy	
5	Shaft	Alloy steel	
6	Rack	Carbon steel	Nitrided
7	Slider	Resin	
8	Bearing retainer	Aluminium alloy	Chromated
9	Tube gasket	NBR	
10	Piston seal	NBR	
11	Bearing	High carbon chrome bearing steel	
12	Hexagon socket head cap screw with washer	Alloy steel	Zinc chromated
13	Spring pin	Steel	Zinc chromated
14	Parallel key	Carbon steel	
15	Connecting screw	Carbon steel	Zinc chromated
16	Cross-recessed pan head tapping screw	Steel	Zinc chromated
17	Wear ring	Resin	
18	Auto switch	—	
19	Magnet	—	
20	Switch spacer	Resin	
21	Cushion ring	Aluminium alloy	Anodised
22	Cushion valve	Steel	Zinc chromated
23	Cushion seal	Urethane	
24	O-ring	NBR	
25	Seal retainer	Steel	
26	Retaining ring	Steel	

Replacement Parts

Size	Part no.		
	Without air cushion	With air cushion	Air-hydro
50	P694020-20	P694020-21	P694020-23
63	P694030-20	P694030-21	P694030-23
80	P694040-20	P694040-21	P694040-23
100	P694050-20	P694050-21	P694050-23
Corresponding parts	⑦, ⑨, ⑩, ⑬ are included as a set.		

Note) When ordering replacement parts, write "1" for one set of the parts per actuator. A grease pack (10 g) is included.

If an additional grease pack is needed, order with the following part number.

Grease pack part number: GR-S-010 (10 g)

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Rotary Actuator: Angle Adjustable Type

(Angle adjustment mechanism is provided as standard.)

Series CRA1□□U

RoHS

Rack & Pinion Type/Size: 50, 63, 80, 100



How to Order

CRA1 B S U 50 - 90 Z

With auto switch CDRA1 B S U 50 - 90 Z - M9BW

Mounting

B	Basic type
L (Note 1, 2)	Foot type
F	Flange type

Note 1) For foot bracket and part number, refer to page 16.
Note 2) Foot bracket is included in the same package, (but not assembled).

Built-in magnet

Shaft type

S	Single shaft
W	Double shaft
X	Single shaft with four chamfers
Y	Double shaft with key
Z	Double shaft with four chamfers
T	Single round shaft
J	Double shaft (round shaft, with four chamfers)
K	Double round shaft

* Flange type is not available for T, J, K.
* T, J, K are made to order.

Rotating angle

90	90°
180	180°
100	100°
190	190°

Auto switch

—	Without auto switch (Built-in magnet)
----------	---------------------------------------

* For applicable auto switch model, refer to the table below.

Number of auto switches

—	2 pcs.
S	1 pc.

Note) Up to two auto switches are mountable.

Angle adjustable type

Size

50
63
80
100

Port type

Size	50	63	80	100
—	Rc			
TF	G			
TN	NPT			
TT	NPTF			

Made to Order
Refer to page 16.

Applicable Auto Switches/Refer to the **WEB catalogue** or the Auto Switch Guide for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length [m]				Pre-wired connector	Applicable load		
					DC		AC	Perpendicular	In-line	0.5 (—)	1 (M)	3 (L)		5 (Z)	IC circuit	Relay, PLC
Solid state auto switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9NV	M9N	●	●	●	○	○		
	Diagnosis indication (2-color indication)			3-wire (PNP)		12 V		M9PV	M9P	●	●	●	○	○	—	
				2-wire		5 V, 12 V		M9BV	M9B	●	●	●	○	○	—	
				3-wire (NPN)		5 V, 12 V		M9NWV	M9NW	●	●	●	○	○	IC circuit	
				3-wire (PNP)		12 V		M9PWV	M9PW	●	●	●	○	○	—	
	Water resistant (2-color indication)			2-wire		5 V, 12 V		M9BWV	M9BW	●	●	●	○	○	—	
				3-wire (NPN)		12 V		M9NAV*1	M9NA*1	○	○	●	○	○	IC circuit	
				3-wire (PNP)		12 V		M9PAV*1	M9PA*1	○	○	●	○	○	—	
				2-wire		12 V		M9BAV*1	M9BA*1	○	○	●	○	○	—	
Reed auto switch	—	Grommet	Yes	3-wire (NPN equivalent)	—	5 V	—	A96V	A96	●	—	●	—	—	IC circuit	—
				2-wire	24 V	12 V	100 V	A93V*2	A93	●	●	●	●	—	—	Relay, PLC
						100 V or less	A90V	A90	●	—	●	—	—	—	IC circuit	—

*1 Although it is possible to mount water resistant type auto switches, note that the rotary actuator itself is not of water resistant construction.

*2 1 m type lead wire is only applicable to D-A93.

* Lead wire length symbols: 0.5 m — (Example) M9NW
1 m M (Example) M9NWM
3 m L (Example) M9NWL
5 m Z (Example) M9NWX


* Auto switches marked with "○" are produced upon receipt of order.

* Auto switches are shipped together, (but not assembled).



Refer to the **WEB catalogue** or Auto Switch Guide for detailed solid state auto switches with pre-wired connectors.

Rotary Actuator: Angle Adjustable Type Rack & Pinion Type **Series CRA1□□U**



Made to Order

Made to Order

(For details, refer to pages 22 to 42.)

Symbol	Description	Applicable shaft type
-XA1 to -XA24	Shaft pattern sequencing I	S, W, Y
-XA33 to -XA59	Shaft pattern sequencing II	X, Z, T, J, K
-XC7	Reversed shaft	S, W, X, T, J
-XC30	Changed to fluorine grease	S, W, X, Y Z, T, J, K
-XC37 to -XC46	Change of rotation range and angle adjusting direction	S, W, Y
-XC47 to -XC58	Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	S, W, Y
-XC59 to -XC61	Change of port direction	S, W, X, Y Z, T, J, K
-X7*	Heat resistant type (100 °C)	S, W, X, Y Z, T, J, K
-X16	Fluororubber seal	S, W, X, Y Z, T, J, K
-X10	Both sides angle adjustable	S, W, X, Y Z, T, J, K
-X11	One side angle adjustable, One side with cushion	S, W, X, Y Z, T, J, K

* -X7: Not available for the built-in magnet type.

Specifications

Type	Pneumatic			
Size	50	63	80	100
Fluid	Air (Non-lube)			
Max. operating pressure	1.0 MPa			
Min. operating pressure	0.1 MPa			
Ambient and fluid temperature	0 to 60 °C (No freezing)			
Cushion	None			
Backlash	Within 1°			
Angle adjustment range	Max. 90°			

* For details about the effective torque, allowable kinetic energy, and adjustable range of rotation time safe in operation, refer to page 6.

Weight

Size	Standard weight		Additional weight		
	90°	180°	With auto switch*	Foot bracket	Flange bracket
50	1.4	1.6	0.2	0.3	0.5
63	2.4	2.8	0.4	0.5	0.9
80	4.2	4.7	0.6	0.9	1.5
100	7.8	8.8	0.9	1.2	2.0


* With 2 auto switches

Rotation Range of Keyway/Angle Adjustment

The shaft rotates clockwise when the pressure is applied from the A port.
The clockwise rotation end position is adjusted using the angle adjusting screw.

Note) Take appropriate measures so that no excessive external impact or vibration is applied to the angle adjusting screw.

Failure to do so may cause the angle adjusting screw to become loose or drop.



Adjustment angle per rotation of angle adjusting screw

Size	50	63	80	100
Adjusting angle	9.5°	9.4°	8.2°	6.8°

Foot Bracket/Part No.

Size	Foot bracket	Contents	Mounting screw size included in foot bracket
50	CRA1L50-Y-1Z	Foot bracket : 2 pcs. Mounting screw: 4 pcs. Collar* : 4 pcs.	M8 x 1.25 x 35
63	CRA1L63-Y-1Z		M10 x 1.5 x 40
80	CRA1L80-Y-1Z		M12 x 1.75 x 50
100	CRA1L100-Y-1Z		M12 x 1.75 x 50





* Remove the basic type mounting screws and use the mounting screws included in the foot bracket to secure the foot bracket to the cover. Use the collar as a spacer for the cover counterbore part and secure it together with the foot.

Series CRA1□□U

Dimensions/Basic Type: C□RA1BSU

Size: 50/63/80/100

Single shaft: C□RA1BSU



- Drawing shows the appearance for rotation of 90° and 100°.
 - Dimensions show pressurisation to B port.
 - Drawing shows the auto switch mounted on the port side.
- * () are the dimensions for rotation of 180° and 190°.


* () are the dimensions for rotation of 180° and 190°.																					[mm]
Size	Note 1) Port size	A	B	C	D (g6)	DD (h9)	F	H	J	K	With auto switch					Without auto switch	U	W	BA	BB	BC
											S	SB	SC	SD	SE	S					
50	1/8	62	48	46	15	25	2.5	36	M8 x 1.25 depth 8	5	156 (189)	1.5	5	14.5	33	144 (177)	98	17	17	8.5	6
63	1/8	76	60	57	17	30	2.5	41	M10 x 1.5 depth 12	5	175 (213.5)	1.5	5	21.5	33	163 (201.5)	117	19.5	20	10	7
80	1/4	92	72	70	20	35	3	50	M12 x 1.75 depth 13	5	199 (243)	1.5	5	29.5	33	186 (230)	142	22.5	23.5	12	8
100	3/8	112	85	85	25	40	4	60	M12 x 1.75 depth 14	5	259 (325)	1.5	5	39.5	33	245 (311)	172	28	25	12.5	8

Size	AU	BU	CU	SU	MU	Key (Note) dimensions	
						b	L1
50	9.5	6	19	33	M12 x 1.75	5 ⁰ _{-0.030}	25
63	10.5	6	22	35.5	M14 x 2	6 ⁰ _{-0.030}	30
80	12.5	8	24	44	M16 x 2	6 ⁰ _{-0.030}	40
100	14.5	10	30	56	M20 x 2.5	8 ⁰ _{-0.036}	45

Note) A parallel key is included in the same package, (but not assembled).

The dimensions of the shaft type W: Double shaft, X: Single shaft with four chamfers, Y: Double shaft with key, Z: Double shaft with four chamfers, T: Single round shaft, J: Double shaft round shaft, with four chamfers, K: Double round shaft, foot type, and flange type are the same as the standard type. For details, refer to pages 9 to 12.

Construction



Component Parts

No.	Description	Material	Note
1	Body	Aluminium alloy	Anodised
2	Right cover	Aluminium alloy	Metallic coating
3	Left cover	Aluminium alloy	Metallic coating
4	Right piston	Aluminium alloy	
5	Left piston	Aluminium alloy	
6	Shaft	Alloy steel	
7	Rack	Carbon steel	Nitrided
8	Slider	Resin	
9	Bearing retainer	Aluminium alloy	Chromated
10	Tube gasket	NBR	
11	Piston seal	NBR	
12	Bearing	High carbon chrome bearing steel	
13	Hexagon socket head cap screw with washer	Alloy steel	Zinc chromated
14	Spring pin	Steel	Zinc chromated

No.	Description	Material	Note
15	Parallel key	Carbon steel	
16	Connecting screw	Carbon steel	Zinc chromated
17	Cross-recessed pan head tapping screw	Steel	Zinc chromated
18	Wear ring	Resin	
19	Stopper	Carbon steel	Zinc chromated
20	Hexagon socket head set screw (flat point)	Alloy steel	Zinc chromated
21	Hexagon nut	Steel	Zinc chromated
22	Seal washer	NBR	
23	O-ring	NBR	
24	Angle adjusting collar	Carbon steel	Zinc chromated
25	Auto switch	—	
26	Magnet	—	
27	Switch spacer	Resin	

Replacement Parts

Size	Part no.	Corresponding parts
50	P694020-22	⑧, ⑩, ⑪, ⑭, ②② are included as a set.
63	P694030-22	
80	P694040-22	
100	P694050-22	

Note) When ordering replacement parts, write "1" for one set of the parts per actuator.

A grease pack (10 g) is included.

If an additional grease pack is needed, order with the following part number. **Grease pack part number: GR-S-010** (10 g)

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials




Made to Order

Series CRA1 Auto Switch Mounting


Auto Switch Proper Mounting Position at Rotation End

Size: 30

Size: 50 to 100



For size 30, only the perpendicular type auto switch can be mounted since two auto switches are mounted in the same switch groove when mounting the switch on the connection port side.



Size	Rotating angle	D-M9□/M9□V D-M9□W/M9□WV D-M9□A/M9□AV		D-A9□/A9□V	
		Proper mounting position A [mm]	Operating range θ [°]	Proper mounting position A [mm]	Operating range θ [°]
30	90	13	42°	9	81°
	180	22		18	
50	90	22.5	30°	18.5	44°
	180	39		35	
63	90	25	28°	21	49°
	180	44.5		40.5	
80	90	27.5	23°	23.5	41°
	180	49.5		45.5	
100	90	42.5	15°	38.5	29°
	180	75.5		71.5	

* Values which include hysteresis are for guideline purposes only, they are not a guarantee (assuming approximately ±30 % dispersion) and may change substantially depending on the ambient environment. Adjust the auto switch after confirming the operating conditions in the actual setting.

Switch Spacer/Part No.


Size	30	50	63	80	100
Switch spacer part no.	BM Y3-016				

* The above part number includes one switch spacer.

* Two switch spacers are included with the product with built-in magnet.

Auto Switch Mounting

To fix the auto switch, hold the switch spacer, and insert into the groove. Make sure that the switch spacer is in the right position or correct the position if necessary, then slide the auto switch in the groove so that it goes into the spacer. Confirm where the mounting position is, and tighten the auto switch mounting screw using a flat head screwdriver.




Note) When tightening an auto switch mounting screw, use a watchmakers' screwdriver with a handle of approximately 5 to 6 mm in diameter.
Also, tighten with a torque of about 0.1 to 0.15 N·m.
As a guide, turn about 90° past the point at which tightening can first be felt.

Auto Switch Working Principle


[Pressure is applied from the B port.]

The auto switch B is turned ON by the magnet B in the state that the pressure is applied from the B port and the piston B moves to the left side. At this time, the auto switch A turns OFF.



[Pressure is applied from the A port.]

When the pressure is applied from the A port, the piston A moves to the right side and the shaft rotates clockwise. The auto switch B turns OFF and the auto switch A is turned ON by the magnet A at the rotation end.



CONTENTS

Rotary Actuator Series **CRA1**

Simple Specials/Made to Order

Simple specials

Shaft pattern sequencing I	-XA1 to -XA24	Page 23
Shaft pattern sequencing II	-XA33 to -XA59	Page 27

Made to Order

How to Order		Page 32
① Reversed shaft	-XC7	Page 33
② Change of rotation range	-XC8 to -XC11	Page 33
③ Changed to fluorine grease	-XC30	Page 33
④ Change of rotation range and shaft rotation direction	-XC31 to XC36	Page 34
⑤ Change of rotation range and angle adjusting direction	-XC37 to XC42	Page 35
⑥ Change of rotation range and angle adjusting direction	-XC43 to XC46	Page 36
⑦ Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	-XC47 to XC52	Page 37
⑧ Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	-XC53 to XC58	Page 38
⑨ Change of port location (Mounting location of the cover is changed.)	-XC59 to XC61	Page 39
⑩ One side air-hydro, One side air	-XC63, -XC64	Page 39
⑪ Stainless steel shaft/Bolt/Parallel key	-X6	Page 40
⑫ Heat resistant	-X7	Page 40
⑬ Both sides angle adjustable	-X10	Page 40
⑭ One side angle adjustable, One side with cushion	-X11	Page 41
⑮ Fluororubber seal	-X16	Page 41
Made to Order/-X6 to -X16		Page 42

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Series CRA1 Simple Specials

Shaft shape pattern is dealt with simple made-to-order system. A specification sheet is available for ordering. Please access SMC website, or consult your nearest sales branch.



Symbol

Shaft Pattern Sequencing I

-XA1 to -XA24

Applicable shaft type: S, W, Y

How to Order

C **D** **RA1** **B** **S** **50** **-** **90** **Z** **-** **M9BW** **-** **X** **A1** **A2** **C8** **C59**

Magnet

—	None
D	Built-in magnet

Mounting

B	Basic type
L	Foot type

Shaft type

S	Single shaft
W	Double shaft
Y	Double shaft with key

Variation

—	Without angle adjustment
U (Note)	Angle adjustable type
H (Note)	Air-hydro type

Note) Except size 30

Size

30
50
63
80
100

Port type

Size	30	50	63	80	100
—	M thread	M5	—	—	—
—	Rc	—	—	—	—
TF	G	—	1/8	1/8	1/4
TN	NPT	—	—	—	3/8
TT	NPTF	—	—	—	—

Rotating angle

90	90°
180	180°
100 (Note)	100°
190 (Note)	190°

Note) Except size 30

Cushion

—	Without air cushion
C (Note)	With air cushion

Note) Except angle adjustable type, air-hydro type.

Auto switch

—	Without auto switch (Built-in magnet)
---	---------------------------------------

Note 1) For applicable auto switch model, refer to page 5.
Note 2) Auto switches are shipped together, (but not assembled).

Number of auto switches

—	2 pcs.
S	1 pc.

Symbol for simple specials, made-to-order products

Note) Combination of XA is possible for up to 2 types.

Combination 3 types

A1	A24	C59
A13	C8	C59

Combination of applicable chart

Chart 1, 2
Chart 2, 7

Combination is available only when all the conditions are fulfilled in the combination chart.

Combination 4 types

A1	A2	C8	C59
A2	A24	C10	C60

Combination of applicable chart

Chart 1, 2, 7
Chart 1, 2, 7

Combination is available only when all the conditions are fulfilled in the combination chart.

Note 1) Combination of simple special and made-to-order is possible for up to 4 types.
Note 2) Above is the typical example of combination.

Symbol

Shaft Pattern Sequencing I**-XA1 to -XA24**

Applicable shaft type: S, W, Y

Combination Chart of Simple Specials for Shaft Shape**Chart 1. Combination between -XA□ and -XA□ (S, W, Y shaft)**

Symbol	Description	Axial direction		Applicable shaft type			Combination			
		Top	Bottom	S	W	Y	-XA1	-XA2	-XA13	-XA24
-XA1	Shaft-end female thread	●	—	●	●	●	—	●	—	●
-XA2	Shaft-end female thread	—	●	●	●	●	●	—	—	●
-XA13	Shaft through-hole	●	●	●	●	●	—	—	—	●
-XA14	Shaft through-hole + Shaft-end female thread	●	—	●	●	●	—	—	—	●
-XA15	Shaft through-hole + Shaft-end female thread	—	●	●	●	●	—	—	—	●
-XA16	Shaft through-hole + Double shaft-end female thread	●	●	●	●	●	—	—	—	●
-XA17	Shorted shaft (Long shaft with key)	●	—	●	●	●	—	●	●	—
-XA18	Shorted shaft (Short shaft and with four sided chamfer)	—	●	—	●	●	W, Y*	—	W, Y*	—
-XA19	Shorted shaft (Double shaft)	●	●	—	●	●	—	—	W, Y*	—
-XA20	Reverse shaft, Shorted shaft	●	●	—	●	●	—	—	S, W*	—
-XA24	Double key	●	—	●	●	●	—	—	—	—

* Corresponding shafts type available for combination

Combination Chart of Made to Order**Chart 2. Combination between -XA□ and -XC□**

Symbol	Description	Applicable shaft type			Applicable size	Combination	
		S	W	Y		-XA1, 2, 13 to 19	-XA20, 24
-XC7	Reversed shaft	●	●	—	50, 63, 80, 100	—	—
-XC8 to -XC11	Change of rotation range	●	●	●		●	—
-XC30	Changed to fluorine grease	●	●	●		●	●
-XC31 to -XC36	Change of rotation range and shaft rotation direction	●	●	●	50, 63, 80, 100	●	—
-XC37 to -XC46	Change of rotation range and angle adjusting direction	●	●	●		●	—
-XC47 to -XC58	Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	●	●	●		●	—
-XC59 to -XC61	Change of port location	●	●	●	30 to 100	●	●
-XC63	One side air-hydro, One side air	●	●	●	50, 63, 80, 100	●	●
-XC64	One side air-hydro, One side air	●	●	●		●	●

* -XC8 to -XC11 and -XC31 to -XC36 do not include the angle adjustable type.

* -XC37 to -XC46 and -XC47 to -XC58 are only the angle adjustable type.

* -XC63 and -XC64 are only the air-hydro type.

Chart 3. Combination between -X□ and -XA□

Symbol	Description	Applicable shaft type			Applicable size	Combination	
		S	W	X		-XA1, 2, 13 to 19	-XA20, 24
-X6	Stainless steel shaft/bolt, etc.	●	●	●	30 to 100	●	●
-X7	Heat resistant (100 °C)	●	●	●		●	●
-X10	Both sides angle adjustable	●	●	●	50 to 100	●	●
-X11	One side angle adjustable, One side with cushion	●	●	●		●	●
-X16	Fluororubber seal	●	●	●	30 to 100	●	●

* -X10 and -X11 are only the angle adjustable type.

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Shaft Pattern Sequencing I

Symbol

-XA1 to -XA17

Applicable shaft type: S, W, Y

Additional Reminders


1. Enter the dimensions within a range that allows for additional machining.
2. SMC will make appropriate arrangements if no dimensional, tolerance, or finish instructions are given in the diagram.
3. The length of the unthreaded portion is 2 to 3 pitches.
4. Unless specified otherwise, the thread pitch is based on coarse metric threads.
P = Thread pitch
M4 x 0.7, M5 x 0.8, M6 x 1, M8 x 1.25, M10 x 1.5
5. Enter the desired figures in the portion of the diagram.
6. Chamfer face of the parts machining additionally is C0.5.

Symbol: A1

Machine female threads into the long shaft.
Note) Except flange type

The maximum dimension L1 is, as a rule, twice the thread size.
(Example) For M4: L1 = 8

· Applicable shaft types: S, W, Y



[mm]


Size	Q1
30	M3
50	M4, M5, M6
63	M4, M5, M6
80	M4, M5, M6, M8
100	M5, M6, M8, M10

Symbol: A2

Machine female threads into the short shaft.
Note) Except flange type

The maximum dimension L2 is, as a rule, twice the thread size.
(Example) For M4: L2 = 8

· Applicable shaft types: S, W, Y



[mm]


Size	Q2
30	M3, M4
50	M4, M5, M6
63	M4, M5, M6
80	M4, M5, M6, M8
100	M5, M6, M8, M10

Symbol: A13

Shaft through-hole Note) Except flange type

Minimum machining diameter for d1 is 0.1.

· Applicable shaft types: S, W, Y



[mm]

Size	d1
30	Ø 2.5
50	Ø 4 to Ø 7
63	Ø 4 to Ø 8
80	Ø 6.8 to Ø 11
100	Ø 6.8 to Ø 13


Symbol: A14

Note) Except flange type

A special end is machined onto the long shaft, and a through-hole is drilled into it. Female threads are machined into the throughhole, whose diameter is equivalent to the pilot hole diameter.

The maximum dimension L1 is, as a rule, twice the thread size.
(Example) For M5: L1 = 10

· Applicable shaft types: S, W, Y



[mm]

Thread	Size	30	50	63	80	100
M3 x 0.5	Ø 2.5	—	—	—	—	—
M5 x 0.8	—	Ø 4	Ø 4	—	—	—
M6 x 1	—	Ø 5	Ø 5	—	—	—
M8 x 1.25	—	—	Ø 6.8	Ø 6.8	Ø 6.8	—
M10 x 1.5	—	—	—	Ø 8.5	Ø 8.5	—
M12 x 1.75	—	—	—	Ø 10.3	Ø 10.3	—
Rc 1/8	—	—	—	Ø 8	Ø 8	—
Rc 1/4	—	—	—	—	—	Ø 11


Symbol: A15

Note) Except flange type

A special end is machined onto the short shaft, and a through-hole is drilled into it. Female threads are machined into the through-hole, whose diameter is equivalent to the pilot hole diameter.

The maximum dimension L2 is, as a rule, twice the thread size.
(Example) For M5: L2 = 10

· Applicable shaft types: S, W, Y



[mm]

Thread	Size	30	50	63	80	100
M3 x 0.5	Ø 2.5	—	—	—	—	—
M5 x 0.8	—	Ø 4	Ø 4	—	—	—
M6 x 1	—	Ø 5	Ø 5	—	—	—
M8 x 1.25	—	—	Ø 6.8	Ø 6.8	Ø 6.8	—
M10 x 1.5	—	—	—	Ø 8.5	Ø 8.5	—
M12 x 1.75	—	—	—	Ø 10.3	Ø 10.3	—
Rc 1/8	—	—	—	Ø 8	Ø 8	—
Rc 1/4	—	—	—	—	—	Ø 11


Symbol: A16

Note) Except flange type

A special end is machined onto both the long and short shafts, and a through-hole is drilled into both shafts. Female threads are machined into the through-holes, whose diameter is equivalent to the diameter of the pilot holes.

The maximum dimension L1 is, as a rule, twice the thread size.
(Example) For M5: L1 = 10

· Applicable shaft types: S, W, Y
· Equal dimensions are indicated by the same marker.



[mm]


Thread	Size	30	50	63	80	100
M3 x 0.5	Ø 2.5	—	—	—	—	—
M5 x 0.8	—	Ø 4	Ø 4	—	—	—
M6 x 1	—	Ø 5	Ø 5	—	—	—
M8 x 1.25	—	—	Ø 6.8	Ø 6.8	Ø 6.8	—
M10 x 1.5	—	—	—	Ø 8.5	Ø 8.5	—
M12 x 1.75	—	—	—	Ø 10.3	Ø 10.3	—
Rc 1/8	—	—	—	Ø 8	Ø 8	—
Rc 1/4	—	—	—	—	—	Ø 11

Symbol: A17

Note) Except flange type

Shorten the long shaft.

· Applicable shaft types: S, W, Y



[mm]

Size	X
30	15 to 25
50	18.5 to 36
63	21 to 41
80	25 to 50
100	32.5 to 60

Symbol

-XA18 to -XA24


Shaft Pattern Sequencing I

Applicable shaft type: S, W, Y

Symbol: A18 Note) Except flange type

Shorten the short shaft.

· Applicable shaft types: W, Y




Size	Y1 W	Y2 Y
30	3 to 8	15 to 25
50	1 to 20	18.5 to 36
63	1 to 22	21 to 41
80	1 to 25	25 to 50
100	1 to 30	32.5 to 60

Symbol: A19 Note) Except flange type

Both the long shaft and short shaft are shortened.

· Applicable shaft types: W, Y




Size	X W	Y Y	Y1 W	Y2 Y
30	15 to 25	3 to 8	15 to 25	3 to 8
50	18.5 to 36	1 to 20	18.5 to 36	1 to 20
63	21 to 41	1 to 22	21 to 41	1 to 22
80	25 to 50	1 to 25	25 to 50	1 to 25
100	32.5 to 60	1 to 30	32.5 to 60	1 to 30

Symbol: A20 Note) Except flange type

Reverse the assembly of the shaft. (Thus shortening the long end and the short end of the shaft.)
(If shortening the shaft is not required, indicate “*” for dimension X and Y.)

· Applicable shaft types: S, W



Size	X W	Y S	Y W
50	2 to 11	18.5 to 36	18.5 to 36
63	2.5 to 16.5	21 to 41	21 to 41
80	3 to 20	25 to 50	25 to 50
100	3 to 22	32.5 to 60	32.5 to 60

Symbol: A24


Double key

Keys and keyways are machined additionally at 180° from the standard position.

· Applicable shaft types:

S, W, Y

· Equal dimensions are indicated by the same marker.



Size	Key dimensions	LL
30	3 x 3 x 14	3
50	5 x 5 x 25	5
63	6 x 6 x 30	5
80	6 x 6 x 40	5
100	8 x 7 x 45	5

CRA1

CRA1

Auto Switch Mounting

Simple Specials

Made to Order

Shaft Pattern Sequencing II

Applicable shaft type: X, Z, T, J, K

Symbol

-XA33 to -XA59

How to Order

C D RA1 B J 50 - 90 Z - M9BW - X A33 A34 C8 C30

Magnet

—	None
D	Built-in magnet

Mounting

B	Basic type
L	Foot type

Shaft type

X	Single shaft with four chamfers
Z	Double shaft with four chamfers
T	Single round shaft
J	Double shaft (round shaft, with four chamfers)
K	Double round shaft

Variation

—	Without angle adjustment
U (Note)	Angle adjustable type
H (Note)	Air-hydro type

Note) Except size 30

Size

30
50
63
80
100

Port type

Size	30	50	63	80	100
—	M thread	M5	—	—	—
—	Rc	—	—	—	—
TF	G	—	1/8	1/8	1/4
TN	NPT	—	—	—	—
TT	NPTF	—	—	—	—

Number of auto switches

—	2 pcs.
S	1 pc.

Auto switch

—	Without auto switch (Built-in magnet)
---	---------------------------------------

Note 1) For applicable auto switch model, refer to page 5.

Note 2) Auto switches are shipped together, (but not assembled).

Cushion

—	Without air cushion
C (Note)	With air cushion

Note) Except angle adjustable type, air-hydro type.

Rotating angle

90	90°
180	180°
100 (Note)	100°
190 (Note)	190°

Note) Except size 30

Symbol for simple specials, made-to-order products

Note) Combination of XA is possible for up to 2 types.

Combination 3 types

A33	A34	C30
A35	C9	C59

Combination of applicable chart

Chart 4, 5
Chart 5, 7

Combination is available only when all the conditions are fulfilled in the combination chart.

Combination 4 types

A33	A34	C30	C59
A45	A46	C30	C61

Combination of applicable chart

Chart 4, 5, 7
Chart 4, 5, 7

Combination is available only when all the conditions are fulfilled in the combination chart.

Note 1) Combination of simple special and made-to-order is possible for up to 4 types.

Note 2) Above is the typical example of combination.

Symbol

-XA33 to -XA59**Shaft Pattern Sequencing II**

Applicable shaft type: X, Z, T, J, K

Combination Chart of Simple Specials for Shaft Shape**Chart 4. Combination between -XA□ and -XA□**

Symbol	Description	Axial direction		Applicable shaft type					Combination			
		Top	Bottom	X	Z	T	J	K	* Corresponding shafts type available for combination			
-XA33	Shaft-end female thread	●	—	—	—	●	●	●	-XA33			
-XA34	Shaft-end female thread	—	●	—	—	●	●	●	T, J, K*	-XA34		
-XA35	Shaft-end female thread	●	—	●	●	—	—	—	—	—	-XA35	
-XA36	Shaft-end female thread	—	●	●	●	—	—	—	—	X, Z*	-XA36	
-XA37	Stepped round shaft	●	—	—	—	●	●	●	T, J, K*	—	—	-XA37
-XA38	Stepped round shaft	—	●	—	—	—	—	●	K*	—	—	K*
-XA40	Shaft through-hole	●	●	—	—	●	—	●	—	—	—	—
-XA41	Shaft through-hole	●	●	●	●	—	●	—	—	—	—	—
-XA43	Shaft through-hole + Double shaft-end female thread	●	●	—	—	●	—	●	—	—	—	—
-XA44	Shaft through-hole + Double shaft-end female thread	●	●	●	●	—	●	—	—	—	—	—
-XA45	Middle-cut chamfer	●	—	—	—	●	●	●	T, J, K*	—	—	K*
-XA46	Middle-cut chamfer	—	●	—	—	—	—	●	K*	—	—	K*
-XA51	Change of long shaft length (Without keyway)	●	—	—	—	●	●	●	T, J, K*	—	—	K*
-XA52	Change of short shaft length (Without keyway)	—	●	—	—	—	—	●	K*	—	—	K*
-XA53	Change of double shaft length (Both without keyway)	●	●	—	—	—	—	●	—	—	—	K*
-XA54	Change of long shaft length (With four chamfers)	●	—	●	●	—	—	—	—	—	X, Z*	—
-XA55	Change of short shaft length (With four chamfers)	—	●	—	●	—	●	—	J*	—	Z*	J*
-XA56	Change of double shaft length (Both with four chamfers)	●	●	—	●	—	—	—	—	—	—	Z*
-XA57	Change of double shaft length (Without keyway, With four chamfers)	●	●	—	—	—	●	—	—	—	—	J*
-XA58	Reversed shaft, Change of shaft length (With four chamfers, Without keyway)	●	●	—	—	●	●	—	—	—	—	T*
-XA59	Reversed shaft, Change of shaft length (With four chamfers)	—	●	●	—	—	—	—	—	—	—	X*

Combination Chart of Made to Order**Chart 5. Combination between -XA□ and -XC□**

Symbol	Description	Applicable shaft type					Applicable size	Combination	
		X	Z	T	J	K		-XA33 to 38, 40 to 46, 51 to 59	
-XC7	Reversed shaft	●	—	●	●	—	50, 63, 80, 100	—	
-XC8 to -XC11	Change of rotation range	—	—	—	—	—	50, 63, 80, 100	—	
-XC30	Changed to fluorine grease	●	●	●	●	●	30 to 100	●	
-XC31 to -XC36	Change of rotation range and shaft rotation direction	—	—	—	—	—	50, 63, 80, 100	—	
-XC37 to -XC46	Change of rotation range and angle adjusting direction	—	—	—	—	—		—	
-XC47 to -XC58	Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	—	—	—	—	—	50, 63, 80, 100	—	
-XC59 to -XC61	Change of port location	●	●	●	●	●	30 to 100	●	
-XC63	One side air-hydro, One side air	●	●	●	●	●	50, 63, 80, 100	●	
-XC64	One side air-hydro, One side air	●	●	●	●	●	50, 63, 80, 100	●	

* -XC8 to -XC11 and -XC31 to -XC36 do not include the angle adjustable type.

* -XC37 to -XC46 and -XC47 to -XC58 are only the angle adjustable type.

* -XC63 and -XC64 are only the air-hydro type.

Chart 6. Combination between -X□ and -XA□

Symbol	Description	Applicable shaft type					Applicable size	Combination	
		X	Z	T	J	K		-XA33 to 38, 40 to 46, 51 to 59	
-X6	Stainless steel shaft/bolt, etc.	●	●	●	●	●	30 to 100	●	
-X7	Heat resistant (100 °C)	●	●	●	●	●	30 to 100	●	
-X10	Both sides angle adjustable	●	●	●	●	●	50 to 100	●	
-X11	One side angle adjustable, One side with cushion	●	●	●	●	●	50 to 100	●	
-X16	Fluororubber seal	●	●	●	●	●	30 to 100	●	

* -X10 and -X11 are only the angle adjustable type.

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Shaft Pattern Sequencing II

Applicable shaft type: X, Z, T, J, K

Symbol

-XA33 to -XA41


Additional Reminders

1. Enter the dimensions within a range that allows for additional machining.
2. SMC will make appropriate arrangements if no dimensional, tolerance, or finish instructions are given in the diagram.
3. The length of the unthreaded portion is 2 to 3 pitches.
4. Unless specified otherwise, the thread pitch is based on coarse metric threads.
P = Thread pitch
M4 x 0.7, M5 x 0.8
M6 x 1, M8 x 1.25, M10 x 1.5
5. Enter the desired figures in the portion of the diagram.
6. Chamfer face of the parts machining additionally is C0.5.

Symbol: A33 Machine female threads into the long shaft.
Note) Except flange type

The maximum dimension L1 is, as a rule, twice the thread size.
(Example) For M4: L1 = 8

· Applicable shaft types: J, K, T




Size	Q1
30	M3
50	M4, M5, M6, M8
63	M4, M5, M6, M8, M10
80	M4, M5, M6, M8, M10, M12
100	M5, M6, M8, M10, M12

Symbol: A34 Machine female threads into the short shaft.
Note) Except flange type

The maximum dimension L2 is, as a rule, twice the thread size.
(Example) For M4: L2 = 8

· Applicable shaft types: J, K, T




Size	Q2
30	M3
50	M4, M5, M6, M8
63	M4, M5, M6, M8, M10
80	M4, M5, M6, M8, M10, M12
100	M5, M6, M8, M10, M12

Symbol: A35 Machine female threads into the long shaft.
Note) Except flange type

The maximum dimension L1 is, as a rule, twice the thread size.
(Example) For M4: L1 = 8

· Applicable shaft types: X, Z




Size	Q1
30	M3
50	M4, M5, M6, M8
63	M4, M5, M6, M8, M10
80	M4, M5, M6, M8, M10, M12
100	M5, M6, M8, M10, M12

Symbol: A36 Machine female threads into the short shaft.
Note) Except flange type

The maximum dimension L2 is, as a rule, twice the thread size.
(Example) For M4: L2 = 8

· Applicable shaft types: X, Z



Size	Q2
30	M3
50	M4, M5, M6, M8
63	M4, M5, M6, M8, M10
80	M4, M5, M6, M8, M10, M12
100	M5, M6, M8, M10, M12


Symbol: A37 Note) Except flange type

The long shaft can be further shortened by machining it into a stepped round shaft.

· The minimum unit of the dimensions within a range that allows for machining is 0.1.

(If shortening the shaft is not required, indicate "*" for dimension X.)
(If not specifying dimension C1, indicate "*" instead.)

· Applicable shaft types: J, K, T
· Equal dimensions are indicated by the same marker.



Size	X	L1max	D1
30	3 to 25	X-2	Ø 5 to Ø 7.9
50	3.5 to 36	X-2.5	Ø 5 to Ø 14.9
63	3.5 to 41	X-2.5	Ø 5 to Ø 16.9
80	4 to 50	X-3	Ø 8 to Ø 19.9
100	5 to 60	X-4	Ø 8 to Ø 24.9

Symbol: A38 Note) Except flange type


The short shaft can be further shortened by machining it into a stepped round shaft.

· The minimum unit of the dimensions within a range that allows for machining is 0.1.

(If shortening the shaft is not required, indicate "*" for dimension Y.)
(If not specifying dimension C2, indicate "*" instead.)

· Applicable shaft type: K

· Equal dimensions are indicated by the same marker.




Size	Y	L2max	D2
30	3 to 25	Y-2	Ø 5 to Ø 7.9
50	1 to 36	Y	Ø 5 to Ø 14.9
63	1 to 41	Y	Ø 5 to Ø 16.9
80	1 to 50	Y	Ø 8 to Ø 19.9
100	1 to 60	Y	Ø 8 to Ø 24.9

Symbol: A40 Shaft through-hole Note) Except flange type

· Minimum machining diameter for d1 is 0.1.

· Applicable shaft types: K, T




Size	d1
30	Ø 2.5
50	Ø 4 to Ø 7.5
63	Ø 4 to Ø 8
80	Ø 6.8 to Ø 11
100	Ø 6.8 to Ø 13

Symbol: A41 Shaft through-hole Note) Except flange type

· Minimum machining diameter for d1 is 0.1.

· Applicable shaft types: J, X, Z




Size	d1
30	Ø 2.5
50	Ø 4 to Ø 7.5
63	Ø 4 to Ø 8
80	Ø 6.8 to Ø 11
100	Ø 6.8 to Ø 13

Symbol

-XA43 to -XA55**Shaft Pattern Sequencing II****Applicable shaft type: X, Z, T, J, K****Symbol: A43** Shaft through-hole and female thread
(Note) Except flange type


- Applicable shaft types: K, T
- Equal dimensions are indicated by the same marker.



Thread	Size	30	50	63	80	100
M3 x 0.5	Ø 2.5	—	—	—	—	—
M5 x 0.8	—	Ø 4	Ø 4	—	—	—
M6 x 1	—	Ø 5	Ø 5	—	—	—
M8 x 1.25	—	—	Ø 6.8	Ø 6.8	Ø 6.8	—
M10 x 1.5	—	—	—	Ø 8.5	Ø 8.5	—
M12 x 1.75	—	—	—	Ø 10.3	Ø 10.3	—
Rc 1/8	—	—	—	Ø 8	Ø 8	—
Rc 1/4	—	—	—	—	Ø 11	—

Symbol: A46 (Note) Except flange type


- The short shaft can be further shortened by machining a middle-cut chamfer into it.
- The minimum unit of the dimensions within a range that allows for machining is 0.1.
- (The position is that of the standard flat at the keyway portion.)
- (If shortening the shaft is not required, indicate "*" for dimension Y.)
- Applicable shaft type: K



Size	Y	W2	L2max	L4max
30	8.5 to 25	1 to 2	Y-2	L2-2
50	10 to 36	1 to 5.5	Y	L2-2
63	11 to 41	1 to 6.5	Y	L2-2
80	13.5 to 50	1 to 8	Y	L2-3
100	17 to 60	1.5 to 10.5	Y	L2-4

Symbol: A53 (Note) Except flange type


- Both the long shaft and short shaft are shortened.
- Applicable shaft type: K



Size	X	Y
30	3 to 25	3 to 25
50	3.5 to 36	1 to 36
63	3.5 to 41	1 to 41
80	4 to 50	1 to 50
100	5 to 60	1 to 60

Symbol: A44 (Note) Except flange type


- Shaft through-hole and female thread machining
- Applicable shaft types: J, X, Z
- Equal dimensions are indicated by the same marker.



Thread	Size	30	50	63	80	100
M3 x 0.5	Ø 2.5	—	—	—	—	—
M5 x 0.8	—	Ø 4	Ø 4	—	—	—
M6 x 1	—	Ø 5	Ø 5	—	—	—
M8 x 1.25	—	—	Ø 6.8	Ø 6.8	Ø 6.8	—
M10 x 1.5	—	—	—	Ø 8.5	Ø 8.5	—
M12 x 1.75	—	—	—	Ø 10.3	Ø 10.3	—
Rc 1/8	—	—	—	Ø 8	Ø 8	—
Rc 1/4	—	—	—	—	Ø 11	—

Symbol: A51 (Note) Except flange type


- Shorten the long shaft.
- Applicable shaft types: J, K, T



Size	X
30	3 to 25
50	3.5 to 36
63	3.5 to 41
80	4 to 50
100	5 to 60

Symbol: A54 (Note) Except flange type


- Shorten the long shaft.
- Applicable shaft types: X, Z



Size	X
30	3 to 13
50	3.5 to 27
63	3.5 to 29
80	4 to 38
100	5 to 44

Symbol: A45 (Note) Except flange type


- The long shaft can be further shortened by machining a middle-cut chamfer into it.
- The minimum unit of the dimensions within a range that allows for machining is 0.1.
- (The position is that of the standard flat at the keyway portion.)
- (If shortening the shaft is not required, indicate "*" for dimension X.)
- Applicable shaft types: J, K, T



Size	X	W1	L1max	L3max
30	8.5 to 25	1 to 2	X-2	L1-2
50	12.5 to 36	1 to 5.5	X-2.5	L1-2
63	13.5 to 41	1 to 6.5	X-2.5	L1-2
80	16.5 to 50	1 to 8	X-3	L1-3
100	21 to 60	1.5 to 10.5	X-4	L1-4

Symbol: A52 (Note) Except flange type


- Shorten the short shaft.
- Applicable shaft type: K



Size	Y
30	3 to 25
50	1 to 36
63	1 to 41
80	1 to 50
100	1 to 60

Symbol: A55 (Note) Except flange type

- Shorten the short shaft.
- Applicable shaft types: J, Z



Size	Y
30	3 to 10
50	1 to 20
63	1 to 22
80	1 to 25
100	1 to 30

Shaft Pattern Sequencing II


-XA56 to -XA59

Applicable shaft type: X, Z, T, J, K

Symbol: A56 Note) Except flange type

Both the long shaft and short shaft are shortened.

· Applicable shaft type: Z




Size	X	Y
30	3 to 13	3 to 10
50	3.5 to 27	1 to 20
63	3.5 to 29	1 to 22
80	4 to 38	1 to 25
100	5 to 44	1 to 30

Symbol: A57 Note) Except flange type

Both the long shaft and short shaft are shortened.

· Applicable shaft type: J




Size	X	Y
30	3 to 25	3 to 10
50	3.5 to 36	1 to 20
63	3.5 to 41	1 to 22
80	4 to 50	1 to 25
100	5 to 60	1 to 30

Symbol: A58 Note) Except flange type

The rotation axis is reversed, and then shorten the long and short shafts.

· Applicable shaft types: J, T




Size	Y
50	1 to 36
63	1 to 41
80	1 to 50
100	1 to 60

Symbol: A59 Note) Except flange type

The rotation axis is reversed, and then shorten the long and short shafts.

· Applicable shaft type: X



Size	Y
50	1 to 27
63	1 to 29
80	1 to 38
100	1 to 44

Series CRA1

Made to Order

Please contact SMC for further details about dimensions, specifications and delivery.



How to Order

C D RA1 B S 50 90 Z M9BW X C8 C30 C59

Magnet

—	None
D	Built-in magnet

Mounting

B	Basic type
L	Foot type
F	Flange type

Shaft type

S	Single shaft
W	Double shaft
X	Single shaft with four chamfers
Y	Double shaft with key
Z	Double shaft with four chamfers
T	Single round shaft
J	Double shaft (round shaft, with four chamfers)
K	Double round shaft

Variation

—	Without angle adjustment
U (Note)	Angle adjustable type
H (Note)	Air-hydro type

Note) Except size 30

Size

30
50
63
80
100

Port type

Size	30	50	63	80	100
—	M thread	M5	—	—	—
—	Rc	—	—	—	—
TF	G	—	—	—	—
TN	NPT	—	1/8	1/8	1/4
TT	NPTF	—	—	—	3/8

Rotating angle

90	90°
180	180°
100 (Note)	100°
190 (Note)	190°

Note) Except size 30

Cushion

—	Without air cushion
C (Note)	With air cushion

Note) Except angle adjustable type, air-hydro type, size 30

Auto switch

—	Without auto switch (Built-in magnet)
---	---------------------------------------

Note 1) For applicable auto switch model, refer to page 5.
Note 2) Auto switches are shipped together, (but not assembled).

Number of auto switches

—	2 pcs.
S	1 pc.

Symbol for simple specials, made-to-order products

Note) Combination of XA is possible for up to 2 types.

Combination 3 types

Combination of applicable chart

C7 C30 C59 → Chart 7

Combination is available only when all the conditions are fulfilled in the combination chart.

Note 1) Combination of simple special and made-to-order is possible for up to 3 types.
Note 2) Above is the typical example of combination.

Combination Chart of Made to Order

Chart 7. Combination between -XC□ and -XC□

Symbol	Description	Applicable shaft type								Applicable size	Combination							
		S	W	X	Y	Z	T	J	K									
-XC7	Reversed shaft	●	●	●	—	—	●	●	—	50, 63, 80, 100	-XC7							
-XC8 to -XC11	Change of rotation range	●	●	—	●	—	—	—	—		—	-XC8 to -XC11						
-XC30	Changed to fluorine grease	●	●	●	●	●	●	●	●	30 to 100	S,W,X,T,J*	S,W,Y*	-XC30					
-XC31 to -XC36	Change of rotation range and shaft rotation direction	●	●	—	●	—	—	—	—		—	—	—	S,W,Y*	-XC31 to -XC36			
-XC37 to -XC46	Change of rotation range and angle adjusting direction	●	●	—	●	—	—	—	—	50, 63, 80, 100	—	—	S,W,Y*	—	-XC37 to -XC46			
-XC47 to -XC58	Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.)	●	●	—	●	—	—	—	—		—	—	—	—	—	—	-XC47 to -XC58	
-XC59 to -XC61	Change of port location	●	●	●	●	●	●	●	●	30 to 100	S,W,Y*	●	S,W,Y*	S,W,Y*	S,W,Y*	S,W,Y*	-XC59 to -XC61	
-XC63	One side air-hydro, One side air	●	●	●	●	●	●	●	●		50, 63, 80, 100	●	●	—	●	—	—	●
-XC64	One side air-hydro, One side air	●	●	●	●	●	●	●	●	80, 100	●	●	—	●	—	—	●	

* -XC8 to -XC11 and -XC31 to -XC36 are only the standard type. * -XC37 to -XC46 and -XC47 to -XC58 are only the angle adjustable type.
* -XC63 and -XC64 are only the air-hydro type.

Chart 8. Combination between -X□, -XC□

Symbol	Description	Applicable shaft type								Applicable size	Combination							
		S	W	X	Y	Z	T	J	K		-XC7	-XC8 to -XC11	-XC30	-XC31 to -XC36	-XC37 to -XC58	-XC59 to -XC61	-XC63	-XC64
-X6	Stainless steel shaft/bolt, etc.	●	●	●	●	●	●	●	●	30 to 100	●	●	●	●	—	●	●	●
-X7	Heat resistant (100 °C)	●	●	●	●	●	●	●	●		●	●	—	●	●	●	—	—
-X10	Both sides angle adjustable	●	●	●	●	●	●	●	●	50 to 100	●	—	●	—	—	●	—	—
-X11	One side angle adjustable, One side with cushion	●	●	●	●	●	●	●	●		●	—	—	—	—	●	—	—
-X16	Fluororubber seal	●	●	●	●	●	●	●	●	30 to 100	●	●	●	●	●	●	—	—

* -X10 and -X11 are only the angle adjustable type.

Series CRA1

1 Reversed Shaft Symbol -XC7

C□RA1
C□RA1□□U Standard model no. -XC7

Reversed shaft
(-XC7)

Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, X, T, J






2 Change of Rotation Range Symbol -XC8 to -XC11

C□RA1 Standard model no. -XC8

Change of rotation range
(-XC8 to -XC11)

Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y



3 Changed to Fluorine Grease Symbol -XC30

C□RA1
C□RA1□□U Standard model no. -XC30

Lubricant oil in the seal parts and inner wall of the cylinder is changed to fluorine grease. (Not the low-speed specification)

Fluorine grease
(-XC30)

Specifications

Applicable size	30, 50, 63, 80, 100
Applicable shaft type	S, W, X, Y, Z, T, J, K

* Refer to standard type and angle adjustable type for other specifications.

4 Change of Rotation Range and Shaft Rotation Direction

Symbol
-XC31 to -XC36

C□RA1

Standard model no.

-XC31

Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y

● Change of rotation range and shaft rotation direction
(-XC31 to -XC36)

CRA1

CRA1□□U


Auto Switch Mounting

Simple Specials

Made to Order

Symbol: C31


The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C32


The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C33


The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C34


The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C35


The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C36

The rotation range is changed and the rotating direction is reversed.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

5

Change of Rotation Range and Angle Adjusting Direction

Symbol
-XC37 to -XC42

C□RA1□□U

Standard model no.

-XC37


Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y

●Change of rotation range and angle adjusting direction (-XC37 to -XC42)


Symbol: C37

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°


The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.


Symbol: C38

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°


The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.


Symbol: C39

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°


The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.


Symbol: C40

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°


The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.


Symbol: C41

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°


The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.


Symbol: C42

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



Angle adjusting screw
Angle adjusting direction
Rotation range of keyway 90°

The rotation range under the adjustment of an angle at 60° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol

-XC43 to -XC46

6 Change of Rotation Range and Angle Adjusting Direction

C□RA1□□U

Standard model no.

-XC43


Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y


● Change of rotation range and angle adjusting direction (-XC43 to -XC46)

Symbol: C43

The rotation range and the angle adjusting direction of the angle adjustable type are changed.




The rotation range under the adjustment of an angle at 60° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C44

The rotation range and the angle adjusting direction of the angle adjustable type are changed.




The rotation range under the adjustment of an angle at 120° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C45

The rotation range and the angle adjusting direction of the angle adjustable type are changed.




The rotation range under the adjustment of an angle at 120° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C46

The rotation range and the angle adjusting direction of the angle adjustable type are changed.



The rotation range under the adjustment of an angle at 120° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

7 Change of Rotation Range and Angle Adjusting Direction (Angle adjusting screw is equipped on the left.)

Symbol
-XC47 to -XC52

C□RA1□□U













Standard model no.

-XC47

Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y

● Change of rotation range and angle adjusting direction
(Angle adjusting screw is equipped on the left.)
(-XC47 to -XC52)

<p>Symbol: C47</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>	<p>Symbol: C48</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>	<p>Symbol: C49</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>
<p>Symbol: C50</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>	<p>Symbol: C51</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>	<p>Symbol: C52</p> <p>For the angle adjusting type, angle adjusting screws are mounted to the left cover.</p>  <p>The rotation range under the adjustment of an angle at 60° is indicated below.</p>  <p>Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.</p>

Symbol

8 Change of Rotation Range and Angle Adjusting Direction (Angle adjusting screw is equipped on the left.)

-XC53 to -XC58

C□RA1□□U

Standard model no.

-XC53

Specifications

Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, Y

● Change of rotation range and angle adjusting direction (Angle adjusting screw is equipped on the left.) (-XC53 to -XC58)

CRA1

CRA1□□U


Auto Switch Mounting

Simple Specials


Made to Order

Symbol: C53

For the angle adjusting type, angle adjusting screws are mounted to the left cover.




The rotation range under the adjustment of an angle at 60° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C54

For the angle adjusting type, angle adjusting screws are mounted to the left cover.




The rotation range under the adjustment of an angle at 60° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C55

For the angle adjusting type, angle adjusting screws are mounted to the left cover.




The rotation range under the adjustment of an angle at 120° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C56

For the angle adjusting type, angle adjusting screws are mounted to the left cover.




The rotation range under the adjustment of an angle at 120° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C57

For the angle adjusting type, angle adjusting screws are mounted to the left cover.




The rotation range under the adjustment of an angle at 120° is indicated below.




Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

Symbol: C58

For the angle adjusting type, angle adjusting screws are mounted to the left cover.



The rotation range under the adjustment of an angle at 120° is indicated below.



Note) If it is pressurised from the port indicated with the arrow, the shaft rotates in the clockwise direction.

9 Change of Port Location (Mounting location of the cover is changed.) Symbol -XC59 to -XC61

C□RA1 Standard model no. -XC59


Specifications

Applicable size	30, 50, 63, 80, 100
Applicable shaft type	S, W, X, Y Z, T, J, K

● Change of port location (Mounting location of the cover is changed.)
(-XC59 to -XC61)


Symbol: C59

Direction of the port is changed. (Upward)




Symbol: C60

Direction of the port is changed. (Downward)



Symbol: C61

Direction of the port is changed. (Backward)



10 One Side Air-hydro, One Side Air Symbol -XC63, -XC64

C□RA1 Standard model no. -XC63

Specifications


Applicable size	50, 63, 80, 100
Applicable shaft type	S, W, X, Y Z, T, J, K

* Except angle adjustable type and air cushion equipped type

● One side air-hydro, One side air
-XC63: Left side air
Right side air-hydro
-XC64: Left side air-hydro
Right side air

Symbol: C63


One side air, one side air-hydro specification (Left side air, Right side hydro)



The figure shows the pressurised situation to the hydro pressure port.

Symbol: C64

One side air, one side air-hydro specification (Left side hydro, Right side air)



The figure shows the pressurised situation to the air pressure port.

11 Stainless Steel Shaft/Bolt/Parallel Key **-X6**

C□RA1 Standard model no. **-X6**

Stainless steel for main part ●

For applications in areas that pose a risk of rust or corrosion, a portion of the materials used in the standard parts has been changed to stainless steel.

Specifications

Type	Pneumatic, Air-hydro
Size	30, 50, 63, 80, 100
Rotating angle	90°, 180° (Size 30 to 100) 100°, 190° (Size 50 to 100)
Mounting	Flange, Foot
Shaft type	Single shaft (S), Double shaft (W), Single shaft with four chamfers (X), Double shaft with key (Y), Double shaft with four chamfers (Z), Single round shaft (T), Double shaft (round shaft, with four chamfers) (J), Double round shaft (K)
Stainless steel part	Shaft, Bolt, Screw, Parallel key
Cushion	Not attached, Air cushion (Except air-hydro type)
Auto switch	Mountable

* Refer to page 5 for other specifications.

** Except angle adjustable type

*** Only single shaft (S) and double shaft (W) types are applicable to flange type.

12 Heat Resistant **-X7**

CRA1 Standard model no. **-X7**

Heat resistant ●

In this rotary actuator, the material of the seals has been changed to the heat resistant type (to withstand up to 100 °C), for applications in environments that exceed the standard specification temperatures of 0 to 60 °C.

Specifications


Type	Pneumatic
Size	30, 50, 63, 80, 100
Rotating angle	90°, 180° (Size 30 to 100) 100°, 190° (Size 50 to 100)
Ambient and fluid temperature	0 to 100 °C
Mounting	Flange, Foot
Shaft type	Single shaft (S), Double shaft (W), Single shaft with four chamfers (X), Double shaft with key (Y), Double shaft with four chamfers (Z), Single round shaft (T), Double shaft (round shaft, with four chamfers) (J), Double round shaft (K)
Seal material	FKM
Cushion	Size 30: None Size 50 to 100: Not attached, Air cushion
Auto switch	Not mountable

* Refer to page 5 for other specifications.

13 Both Sides Angle Adjustable **-X10**

C□RA1□□U Standard model no. **-X10**

Both sides angle adjustable ●





Specifications

Type	Pneumatic
Size	50, 63, 80, 100
Rotating angle	90°, 180°, 100°, 190°
Mounting	Flange, Foot
Shaft type	Single shaft (S), Double shaft (W), Single shaft with four chamfers (X), Double shaft with key (Y), Double shaft with four chamfers (Z), Single round shaft (T), Double shaft (round shaft, with four chamfers) (J), Double round shaft (K)
Cushion	None
Angle adjustment range	Max. 90° (One side)

* Refer to page 15 for other specifications.

Adjusting direction Adjusting direction "A": When angle adjusting screw on "A" side is screwed into the right direction.
Adjusting direction "B": When angle adjusting screw on "B" side is screwed into the right direction.



CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Series CRA1

14

One Side Angle Adjustable, One Side with Cushion


Symbol

-X11

C□RA1□□U

Standard model no.

-X11



One side angle adjustable
One side with cushion

Specifications

Type	Pneumatic
Size	50, 63, 80, 100
Rotating angle	90°, 180°, 100°, 190°
Mounting	Flange, Foot
Shaft type	Single shaft (S), Double shaft (W), Single shaft with four chamfers (X), Double shaft with key (Y), Double shaft with four chamfers (Z), Single round shaft (T), Double shaft (round shaft, with four chamfers) (J), Double round shaft (K)
Cushion	With cushion on one side
Angle adjustment range	Max. 90°

* Refer to page 15 for other specifications.

15

Fluororubber Seal

Symbol

-X16

CDRA1

Standard model no.

-X16

Fluororubber seal


Seal is now changed to fluororubber.

Specifications

Type	Pneumatic
Size	30, 50, 63, 80, 100
Rotating angle	90°, 180° (Size 30 to 100) 100°, 190° (Size 50 to 100)
Ambient and fluid temperature	0 to 60 °C (No freezing)
Mounting	Flange, Foot
Shaft type	Single shaft (S), Double shaft (W), Single shaft with four chamfers (X), Double shaft with key (Y), Double shaft with four chamfers (Z), Single round shaft (T), Double shaft (round shaft, with four chamfers) (J), Double round shaft (K)
Seal material	FKM
Cushion	Not attached, Air cushion
Auto switch	Mountable

* Refer to page 5 for other specifications.

** For built-in magnet type only.



* Refer to page 17 for dimensions.

How to Order

C D RA1 B S 50 - 90 Z - M9BW - X6 - X16

Magnet

—	None
D	Built-in magnet

Mounting

B	Basic type
L	Foot type
F	Flange type

Shaft type

S	Single shaft
W	Double shaft
X	Single shaft with four chamfers
Y	Double shaft with key
Z	Double shaft with four chamfers
T	Single round shaft
J	Double shaft (round shaft, with four chamfers)
K	Double round shaft

Variation

—	Without angle adjustment
U (Note)	Angle adjustable type
H (Note)	Air-hydro type

Note) Except size 30

Size

30
50
63
80
100

Auto switch

—	Without auto switch (Built-in magnet)
---	---------------------------------------

Note 1) For applicable auto switch model, refer to page 5.
Note 2) Auto switches are shipped together, (but not assembled).

Number of auto switches

—	2 pcs.
S	1 pc.

Cushion

—	Without air cushion
C (Note)	With air cushion

Note) Except angle adjustable type, air-hydro type

Rotating angle

90	90°
180	180°
100 (Note)	100°
190 (Note)	190°

Note) Except size 30

Port type

Size	30	50	63	80	100
—	M thread	M5	—	—	—
	Rc	—	—	—	—
TF	G	—	1/8	1/4	3/8
TN	NPT	—			
TT	NPTF	—			

Made to Order

• Combination is available only when all the conditions are fulfilled in the combination chart 9.

CRA1

CRA1□□U

Auto Switch Mounting

Simple Specials

Made to Order

Combination Chart of Made to Order

Chart 9. Combination between -X□ and -X□
(S, W, X, Y, Z, T, J, K shaft)

Symbol	Description	Applicable shaft type								Applicable size	Combination		
		S	W	X	Y	Z	T	J	K				
-X6	Stainless steel shaft/bolt/parallel key	●	●	●	●	●	●	●	●	30 to 100	-X6		
-X7 (Note)	Heat resistant (100 °C)	●	●	●	●	●	●	●	●		●	-X7	
-X10	Both sides angle adjustable	●	●	●	●	●	●	●	●	50 to 100	—	●	
-X11	One side angle adjustable, One side with cushion	●	●	●	●	●	●	●	●		—	●	-X10 to -X11
-X16	Fluororubber seal	●	●	●	●	●	●	●	●	30 to 100	●	—	●

* X7: Not available for the built-in magnet type.



Series CRA1 Specific Product Precautions

Be sure to read this before handling. Refer to the back cover for Safety Instructions. For Rotary Actuator Precautions and Auto Switch Precautions, refer to “Handling Precautions for SMC Products” and the Operation Manual on SMC website, <http://www.smcworld.com>

How to Use the Air-hydro Type

Caution on Design

⚠ Warning

1. **Do not use a rotary actuator of the air-hydro type near flames, or in equipment or machinery that exceeds an ambient temperatures of 60 °C.**

There is a danger of causing a fire because the rotary actuator of the air-hydro type uses a flammable hydraulic fluid.

⚠ Caution

1. **Do not use in an environment, equipment, or machine that is not compatible with oil mist.**

Rotary actuators of the air-hydro types generate an oil mist during operation which may affect the environment.

2. **Be sure to install an exhaust cleaner on the directional control valve for the rotary actuator of the air-hydro type.**

A very small amount of hydraulic fluid is discharged from the exhaust port of the rotary actuator of the air-hydro type's directional control valve, which may contaminate the surrounding area.

3. **Install a rotary actuator of the air-hydro type in locations where it can be serviced easily.**

Since the rotary actuator of the air-hydro type requires maintenance, such as refilling of hydraulic fluid and bleeding of air, ensure sufficient space for these activities.

4. **Do not use in cases where external leakage of hydraulic oil may adversely affect equipment or machinery.**

Although it only occurs in minute amounts, a certain amount of sliding leakage from the piston seal is unavoidable with the rotary actuator of the air-hydro type. Because of the construction of the rotary actuator of the air-hydro type, hydraulic oil may leak into the outside due to sliding leakage.

Selection

⚠ Caution

1. **Select the rotary actuator of the air-hydro type based on the combination with the air-hydro unit.**

Select a proper air-hydro unit that is necessary for good operation of the rotary actuator of the air-hydro type.

Piping

⚠ Caution

1. **Use self-align fittings in conjunction with the piping for the rotary actuator of the air-hydro type.**

Do not use a one-touch fitting with the piping for the rotary actuator of the air-hydro type, as this may result in oil leakage.

Piping

⚠ Caution

2. **For rotary actuator of the air-hydro type piping, use hard nylon tubing or copper piping.**

As in the case of hydraulic circuits, surge pressures greater than the operating pressure may occur in a rotary actuator of the air-hydro type's piping, making it necessary to use safer piping materials.

Lubrication

⚠ Warning

1. **Make sure to completely discharge the compressed air in the system before filling the air-hydro unit with hydraulic oil.**

When supplying hydraulic fluid to the air-hydro unit, first confirm that safety measures are implemented to prevent dropping of objects and the release of clamped objects, etc. Then, shut off the air supply and the equipment's electric power and exhaust the compressed air in the system.


If the air-hydro unit's supply port is opened with compressed air still remaining in the system, there is a danger of hydraulic fluid being blown out.

Maintenance

⚠ Caution

1. **Bleed air from the rotary actuator of the air-hydro type on a regular basis.**

Since air may accumulate inside a rotary actuator of the air-hydro type, bleed air from it, for example before starting work. Bleed air from a bleeder valve provided on the rotary actuator of the air-hydro type or the piping.






2. **Verify the oil level of the air-hydro system on a regular basis.**

Since a very small amount of hydraulic fluid is discharged from the rotary actuator of the air-hydro type and air-hydro unit circuit, the fluid will gradually decrease. Therefore, check the fluid regularly and refill as necessary.

The oil level can be checked with a level gauge in the air-hydro converter.

Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “Caution,” “Warning” or “Danger.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)*1), and other safety regulations.

-  **Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.
-  **Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.
-  **Danger:** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

*1) ISO 4414: Pneumatic fluid power – General rules relating to systems.
ISO 4413: Hydraulic fluid power – General rules relating to systems.
IEC 60204-1: Safety of machinery – Electrical equipment of machines.
(Part 1: General requirements)
ISO 10218-1: Manipulating industrial robots - Safety.
etc.

Warning

1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalogue information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalogue.
3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

Caution

1. The product is provided for use in manufacturing industries.

The product herein described is basically provided for peaceful use in manufacturing industries.

If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary.

If anything is unclear, contact your nearest sales branch.

Limited warranty and Disclaimer/ Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”.

Read and accept them before using the product.

Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.*2)
Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided.
This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalogue for the particular products.

*2) Vacuum pads are excluded from this 1 year warranty.

A vacuum pad is a consumable part, so it is warranted for a year after it is delivered.

Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

Caution

SMC products are not intended for use as instruments for legal metrology.

Measurement instruments that SMC manufactures or sells have not been qualified by type approval tests relevant to the metrology (measurement) laws of each country. Therefore, SMC products cannot be used for business or certification ordained by the metrology (measurement) laws of each country.

Safety Instructions

Be sure to read “Handling Precautions for SMC Products” (M-E03-3) before using.

SMC Corporation (Europe)

Austria	☎ +43 (0)2262622800	www.smc.at	office@smc.at
Belgium	☎ +32 (0)33551464	www.smc-pneumatics.be	info@smc-pneumatics.be
Bulgaria	☎ +359 (0)2807670	www.smc.bg	office@smc.bg
Croatia	☎ +385 (0)13707288	www.smc.hr	office@smc.hr
Czech Republic	☎ +420 541424611	www.smc.cz	office@smc.cz
Denmark	☎ +45 70252900	www.smc.dk.com	smc@smc.dk.com
Estonia	☎ +372 6510370	www.smc-pneumatics.ee	smc@smc-pneumatics.ee
Finland	☎ +358 207513513	www.smc.fi	smc@smc.fi
France	☎ +33 (0)164761000	www.smc-france.fr	info@smc-france.fr
Germany	☎ +49 (0)61034020	www.smc.de	info@smc.de
Greece	☎ +30 210 2717265	www.smc-hellas.gr	sales@smc-hellas.gr
Hungary	☎ +36 23511390	www.smc.hu	office@smc.hu
Ireland	☎ +353 (0)14039000	www.smc-pneumatics.ie	sales@smc-pneumatics.ie
Italy	☎ +39 0292711	www.smc-italia.it	mailbox@smc-italia.it
Latvia	☎ +371 67817700	www.smc.lv	info@smc.lv

Lithuania	☎ +370 5 2308118	www.smc.lt	info@smc.lt
Netherlands	☎ +31 (0)205318888	www.smc-pneumatics.nl	info@smc-pneumatics.nl
Norway	☎ +47 67129020	www.smc-norge.no	post@smc-norge.no
Poland	☎ +48 222119600	www.smc.pl	office@smc.pl
Portugal	☎ +351 226166570	www.smc.eu	postpt@smc-smc.es
Romania	☎ +40 213205111	www.smc-romania.ro	smcromania@smcromania.ro
Russia	☎ +7 8127185445	www.smc-pneumatik.ru	info@smc-pneumatik.ru
Slovakia	☎ +421 (0)413213212	www.smc.sk	office@smc.sk
Slovenia	☎ +386 (0)73885412	www.smc.si	office@smc.si
Spain	☎ +34 902184100	www.smc.eu	post@smc-smc.es
Sweden	☎ +46 (0)86031200	www.smc.nu	post@smc.nu
Switzerland	☎ +41 (0)523963131	www.smc.ch	info@smc.ch
Turkey	☎ +90 212 489 0 440	www.smc-pneumatik.com.tr	info@smc-pneumatik.com.tr
UK	☎ +44 (0)845 121 5122	www.smc-pneumatics.co.uk	sales@smc-pneumatics.co.uk

SMC CORPORATION Akihara UDX 15F, 4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021, JAPAN Phone: 03-5207-8249 FAX: 03-5298-5362

1st printing TT printing TU 00 Printed in Spain

Specifications are subject to change without prior notice and any obligation on the part of the manufacturer.