

**Direct Operated** **Pilot Operated**

# 2-Port Solenoid Valve

*Improved environmental resistance due to the stainless steel coil cover [IP67 enclosure]*



Refer to page 37 for details.



Body material • **Stainless steel** • **Brass/Bronze** \*1 • **Aluminium**

Environmental resistance Enclosure: **IP67** \*2

\*1 The bronze body is only selectable for the pilot operated type. \*2 IP65 for models with a DIN terminal

## Direct Operated 2-Port Solenoid Valve JSX Series



Port size  
1/8 to 3/8

## New Pilot Operated 2-Port Solenoid Valve JSXD Series



Port size  
1/4 to 2

**New** • Modular mounting type 2-port solenoid valve

**New** • Body material: Brass/Aluminium  
• M12 connector



**JSX/JSXD**  **Series**



CAT.EUS70-56B-UK

**Space saving**

**Compact**

Valve volume: **25 % reduction**\*1

**Lightweight**

Weight: **30 % reduction**\*1

\*1 Compared with the existing model

**Energy saving**

Coil force: **10 % increase**  
(Compared with the existing model)  
Power consumption: **14 % reduction**  
(Compared with the existing model)  
The coil attraction force has been improved by 10 % and the power consumption has been reduced by 14 % for optimal magnetic efficiency.

**Stopper construction**

Metal noise reduced by the resin stopper  
Longer service life

**Improved armature durability**


**IP67 enclosure**

\* IP65 for models with a DIN terminal

**Choice of body material**

· Stainless steel · Brass/Bronze\*2  
· Aluminium

\*2 The bronze body is only selectable for the pilot operated type.



**360° lead wire insertion and removal is possible.**

As the coil rotates 360°, the lead wire is easy to handle.



**Power consumption** \* For DC voltages

| Model                             | Size | [W] |    |    |    |    |    |    |    |    |
|-----------------------------------|------|-----|----|----|----|----|----|----|----|----|
|                                   |      | 10  | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 |
| JSX Series                        |      | 4   | 6  | 8  | —  | —  | —  | —  | —  | —  |
| JSXD Series                       |      | —   | —  | 6  | 6  | 6  | 8  | 8  | 8  | 8  |
| Modular mounting type JSXM Series |      | —   | 6  | 8  | 8  | —  | —  | —  | —  | —  |

**Full-wave rectifier type (AC specification: Insulation type Class B)**

- Improved durability**  
Extended service life due to the special construction (Compared with the existing shading coil)
- Reduced buzzing noise**  
Due to being rectified to DC by the full-wave rectifier
- Reduced apparent power**  
\* Class B, N.C. valve (Compared with the existing model)  
9.5 VA → **8 VA** (JSX20/JSXD60, 70 Series)  
12 VA → **9.5 VA** (JSX30/JSXD80, 90 Series)
- Improved OFF response**  
Specially constructed to improve the OFF response when operated with high viscosity fluids such as oil
- Low-noise construction**  
Specially constructed to reduce metal noise during operation

**Electrical entry variations**



## Series Variations



### Direct Operated JSX Series p. 5, 7

| Model        | Port size | Orifice diameter [mmØ] | Flow rate*1 [l/min] |    |    |                     | Fluid                                 | Body material      | Seal material                                       | Electrical entry |
|--------------|-----------|------------------------|---------------------|----|----|---------------------|---------------------------------------|--------------------|---|------------------|
|              |           |                        | 5                   | 10 | 20 | 30                  |                                       |                    |   |                  |
| JSX10 Series | 1/8       | 1.6<br>2.4             | 5                   |    |    |                     |                                       |                    |   |                  |
| JSX20 Series | 1/8       | 3.2                    |                     |    | 15 | Air<br>Water<br>Oil | Stainless steel<br>Brass<br>Aluminium | NBR<br>FKM<br>EPDM | Grommet<br>DIN terminal<br>Conduit<br>M12 connector |                  |
|              | 1/4, 3/8  | 3.2, 4<br>5.6, 7.1     |                     |    |    |                     |                                       |                    |   |                  |
| JSX30 Series | 1/4, 3/8  | 4, 5.6, 7.1            |                     |    | 25 |                     |                                       |                    |   |                  |

\*1 At the max. operating pressure differential (Fluid: Water)




### Pilot Operated JSXD Series p. 21

| Model         | Port size     | Orifice diameter [mmØ] | Flow rate*1 [l/min] |      |      | Fluid               | Body material                                | Seal material      | Electrical entry                                    |
|---------------|---------------|------------------------|---------------------|------|------|---------------------|--|--------------------|---|
|               |               |                        | 200                 | 400  | 1000 |                     |  |                    |   |
| JSXD30 Series | 1/4, 3/8, 1/2 | 10                     | 100                 |      |      | Air<br>Water<br>Oil | Stainless steel<br>Brass/Bronze<br>Aluminium | NBR<br>FKM<br>EPDM | Grommet<br>DIN terminal<br>Conduit<br>M12 connector |
| JSXD40 Series | 3/8, 1/2      | 15                     | 200                 |      |      |                     |  |                    |   |
| JSXD50 Series | 3/4           | 20                     |                     | 430  |      |                     |  |                    |   |
| JSXD60 Series | 1             | 25                     |                     | 580  |      |                     |  |                    |   |
| JSXD70 Series | 1 1/4         | 35                     |                     | 1000 |      |                     |  |                    |   |
| JSXD80 Series | 1 1/2         | 40                     |                     | 1400 |      |                     |  |                    |   |
| JSXD90 Series | 2             | 50                     |                     | 2200 |      |                     |  |                    |   |

\*1 At the max. operating pressure differential (Fluid: Water)


**Modular Mounting Type 2-Port Solenoid Valve JSXM Series** p. 30



\*1 The blow port position is selectable.

|           |   |
|-----------|---|
| Coil: OFF | Coil: ON  |
| IN1 ↔ IN2 | IN1/IN2 → Blow port<br>Front or bottom (Selectable) |

Can be connected to modular type F.R.L. units



Modular Mounting Type 2-Port Solenoid Valve JSXM Series

Air Filter AF Series

Regulator AR Series



**Simple Specials System**

A system designed to respond quickly and easily to your special ordering needs

For modular connection units (shipped assembled), the simple specials system can be used.

**Short lead times**

This system enables us to respond to your special needs (additional machining, accessory assembly, or the designing of a modular unit) and deliver your personalised products as quickly as standard products.


**Repeat orders**

Once we receive a simple special part number from one of your previous orders, we will process the order, manufacture the product, and deliver it to you as quickly as possible.


Please contact your local sales representative for more details.

**The coil orientation and blow port position can be selected.**

Coil: Upward



Coil: Downward



**Series Variations**

| Model         | Port size     | Orifice diameter [mmØ] | Flow rate*1 [l/min (ANR)] |      | Fluid | Body material | Seal material | Electrical entry                                    |
|---------------|---------------|------------------------|---------------------------|------|-------|---------------|---------------|---|
|               |               |                        | 500                       | 1000 |       |               |               |   |
| JSXM20 Series | 1/8, 1/4      | 3.2                    | 650                       |      | Air   | Aluminium     | NBR<br>FKM    | Grommet<br>DIN terminal<br>Conduit<br>M12 connector |
| JSXM30 Series | 1/4, 3/8      | 4                      | 1300                      |      |       |               |               |   |
| JSXM40 Series | 1/4, 3/8, 1/2 | 4                      | 1300                      |      |       |               |               |   |

\*1 At the max. operating pressure differential (Fluid: Air)

# CONTENTS

## Direct Operated 2-Port Solenoid Valve JSX Series



For **Water** **Air** **Oil** **Body Material** **Stainless Steel, Brass**


How to Order, Flow Rate Characteristics, Applicable Fluid Check List ..... p. 5  
 Construction, Common Specifications ..... p. 6

For **Air** **Body Material** **Aluminium**

How to Order, Flow Rate Characteristics ..... p. 7  
 Construction, Common Specifications ..... p. 8  
 Dimensions

**JSX10** **Port Size** 1/8 **Body Material** **Stainless Steel, Brass** ..... p. 9  
**JSX20** **Port Size** 1/8 **Body Material** **Stainless Steel** ..... p. 11  
**JSX20, 30** **Port Size** 1/4, 3/8 **Body Material** **Stainless Steel** ..... p. 13  
**JSX20, 30** **Port Size** 1/8, 1/4, 3/8 **Body Material** **Brass** ..... p. 15  
**JSX20, 30** **Port Size** 1/8, 1/4, 3/8 **Body Material** **Aluminium** ..... p. 17  
 Bracket Options ..... p. 19

## Pilot Operated 2-Port Solenoid Valve JSXD Series



How to Order ..... p. 21  
 Flow Rate Characteristics, Applicable Fluid Check List, Common Specifications ..... p. 22  
 Construction ..... p. 23

Dimensions

**JSXD30** **Port Size** 1/4, 3/8, 1/2 **Body Material** **Aluminium, Brass, Stainless Steel** ..... p. 25  
**JSXD40** **Port Size** 3/8, 1/2 **Body Material** **Brass, Stainless Steel** ..... p. 27  
**JSXD50, 60** **Port Size** 3/4, 1 **Body Material** **Brass, Stainless Steel** ..... p. 28  
**JSXD70, 80, 90** **Port Size** 1 1/4, 1 1/2, 2 **Body Material** **Bronze** ..... p. 29

## Modular Mounting Type 2-Port Solenoid Valve JSXM Series



How to Order ..... p. 30  
 Flow Rate Characteristics, Common Specifications ..... p. 31  
 Construction ..... p. 32  
 Dimensions ..... p. 33  
 Modular Connection Examples ..... p. 35  
 Spacer / Spacer with Bracket ..... p. 36

Table of UL-compliant Products (**JSX Series**) ..... p. 37  
 Option: Cable for M12 Connector ..... p. 38  
 Glossary of Terms ..... p. 39  
 Solenoid Valve Flow Rate Characteristics ..... p. 40  
 Flow Rate Characteristics (**JSXD Series**) ..... p. 45  
 Specific Product Precautions ..... p. 47

# Direct Operated 2-Port Solenoid Valve

## JSX Series

Body Material **Stainless Steel, Brass**




For **Water** **Air** **Oil**

### How to Order

JSX **2** **1** - **S** **N** **302** **R** - **5** **G** - **B**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨



RoHS

#### ① Size

| Symbol | Size |
|--------|------|
| 1      | 10   |
| 2      | 20   |
| 3      | 30   |

#### ② Valve type

| Symbol | Valve type            |
|--------|-----------------------|
| 1      | N.C.  2(O)UT<br>1(IN) |

#### ③ Body material

| Symbol | Body material   |
|--------|-----------------|
| S      | Stainless steel |
| C      | Brass           |

#### ⑧ Electrical entry

| Symbol | Electrical entry  | Size |    |    | Rated voltage         | UL Standards      |
|--------|---|------|----|----|-----------------------|-------------------|
|        |   | 10   | 20 | 30 |                       |                   |
| G      | Grommet*1   | ●    | ●  | ●  | 5<br>6                | Refer to page 37. |
| GS     | Grommet with PCB (With surge voltage suppressor)                        | ●    | ●  | ●  | 1<br>5<br>6<br>8<br>B |                   |
| CS     | Conduit (With surge voltage suppressor)                                 | —    | ●  | ●  | All voltages          |                   |
| DS     | DIN terminal (With surge voltage suppressor)                            | ●    | ●  | ●  | All voltages          |                   |
| DZ     | DIN terminal with light (With surge voltage suppressor)                 | ●    | ●  | ●  | All voltages          |                   |
| DN     | DIN terminal without connector (With surge voltage suppressor)          | ●    | ●  | ●  | All voltages          |                   |
| WN     | M12 connector/Without connector cable (With surge voltage suppressor)*2 | ●    | ●  | ●  | All voltages          |                   |

#### ④ Seal material

| Symbol | Seal material |
|--------|---------------|
| N      | NBR           |
| F      | FKM           |
| E      | EPDM          |

#### ⑤ Orifice diameter and port size

| Symbol | Orifice diameter [mmØ] | Port size | Size |    |    |
|--------|------------------------|-----------|------|----|----|
|        |                        |           | 10   | 20 | 30 |
| 101    | 1.6                    | 1/8       | ●    | —  | —  |
| 201    | 2.4                    | 1/8       | ●    | —  | —  |
| 301    | 3.2                    | 1/8       | —    | ●  | —  |
| 302    |                        | 1/4       | —    | ●  | —  |
| 303    | 3/8                    | —         | ●    | —  |    |
| 402    | 4.0                    | 1/4       | —    | ●  | ●  |
| 403    |                        | 3/8       | —    | ●  | ●  |
| 502    | 5.6                    | 1/4       | —    | ●  | ●  |
| 503    |                        | 3/8       | —    | ●  | ●  |
| 702    | 7.1                    | 1/4       | —    | ●  | ●  |
| 703    |                        | 3/8       | —    | ●  | ●  |

#### ⑥ Thread type

| Symbol | Thread type |
|--------|-------------|
| R      | Rc          |
| N      | NPT         |
| F      | G           |

#### ⑦ Rated voltage

| AC     |               |        |               | DC     |               |
|--------|---------------|--------|---------------|--------|---------------|
| Symbol | Rated voltage | Symbol | Rated voltage | Symbol | Rated voltage |
| 1      | 100 VAC       | 7      | 240 VAC       | 5      | 24 VDC        |
| 2      | 200 VAC       | 8      | 48 VAC        | 6      | 12 VDC        |
| 3      | 120 (110) VAC | B      | 24 VAC        |        |               |
| 4      | 220 VAC       | J      | 230 VAC       |        |               |

#### ⑨ Option

| Symbol | Option                           |
|--------|----------------------------------|
| —      | None                             |
| B      | With bracket*1 (Stainless steel) |

\*1 Bracket assembly part nos. (page 49)

\*1 DC voltage only

\*2 A cable for the M12 connector is not included with the product. Refer to "Option" on page 38 to order it separately.

### Flow Rate Characteristics

| Size | Port size | Orifice diameter [mmØ] | Flow rate characteristics*1  |      |      |            |               |                            | Max. operating pressure differential [MPa] | Model | Weight*2 [g]           |            |
|------|-----------|------------------------|------------------------------|------|------|------------|---------------|----------------------------|--|-------|------------------------|------------|
|      |           |                        | Air                          |      |      | Water, Oil |               |                            |  |       | Stainless steel body*3 | Brass body |
|      |           |                        | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   | Kv         | Conversion Cv | Conversion Cv              |  |       |                        |            |
| 10   | 1/8       | 1.6                    | 0.36                         | 0.58 | 0.08 | 0.07       | 0.08          | 0.9                        | JSX11- $\frac{1}{8}$ -□101                 | 160   | 160                    |            |
|      |           | 2.4                    | 0.62                         | 0.45 | 0.15 | 0.13       | 0.15          | 0.4                        | JSX11- $\frac{1}{8}$ -□201                 | 160   | 160                    |            |
| 20   | 1/8       | 3.2                    | 1.35                         | 0.48 | 0.35 | 0.30       | 0.35          | 0.7                        | JSX21- $\frac{1}{8}$ -□301                 | 320   | 330                    |            |
|      |           | 3.2                    | 1.35                         | 0.48 | 0.35 | 0.30       | 0.35          | 0.7                        | JSX21- $\frac{1}{8}$ -□302                 | 320   | 330                    |            |
|      |           | 4.0                    | 2.02                         | 0.48 | 0.52 | 0.45       | 0.52          | 0.3                        | JSX21- $\frac{1}{8}$ -□402                 | 320   | 330                    |            |
|      |           | 5.6                    | 2.62                         | 0.43 | 0.73 | 0.63       | 0.73          | 0.2                        | JSX21- $\frac{1}{8}$ -□502                 | 320   | 330                    |            |
|      | 1/4       | 7.1                    | 3.15                         | 0.44 | 0.88 | 0.76       | 0.88          | 0.1                        | JSX21- $\frac{1}{4}$ -□702                 | 320   | 330                    |            |
|      |           | 3.2                    | 1.35                         | 0.48 | 0.35 | 0.30       | 0.35          | 0.7                        | JSX21- $\frac{1}{4}$ -□303                 | 320   | 360                    |            |
|      |           | 4.0                    | 2.02                         | 0.48 | 0.52 | 0.45       | 0.52          | 0.3                        | JSX21- $\frac{1}{4}$ -□403                 | 320   | 360                    |            |
|      |           | 5.6                    | 2.62                         | 0.43 | 0.73 | 0.63       | 0.73          | 0.2                        | JSX21- $\frac{1}{4}$ -□503                 | 320   | 360                    |            |
| 30   | 3/8       | 7.1                    | 3.15                         | 0.44 | 0.88 | 0.76       | 0.88          | 0.1                        | JSX21- $\frac{3}{8}$ -□703                 | 320   | 360                    |            |
|      |           | 4.0                    | 2.02                         | 0.48 | 0.52 | 0.45       | 0.52          | 1.0                        | JSX31- $\frac{3}{8}$ -□402                 | 450   | 490                    |            |
|      |           | 5.6                    | 2.62                         | 0.43 | 0.73 | 0.63       | 0.73          | 0.5                        | JSX31- $\frac{3}{8}$ -□502                 | 450   | 490                    |            |
|      | 1/4       | 7.1                    | 3.15                         | 0.44 | 0.88 | 0.76       | 0.88          | 0.2                        | JSX31- $\frac{1}{4}$ -□702                 | 450   | 490                    |            |
|      |           | 4.0                    | 2.02                         | 0.48 | 0.52 | 0.45       | 0.52          | 1.0                        | JSX31- $\frac{1}{4}$ -□403                 | 450   | 520                    |            |
|      |           | 5.6                    | 2.62                         | 0.43 | 0.73 | 0.63       | 0.73          | 0.5                        | JSX31- $\frac{1}{4}$ -□503                 | 450   | 520                    |            |
| 3/8  | 7.1       | 3.15                   | 0.44                         | 0.88 | 0.76 | 0.88       | 0.2           | JSX31- $\frac{3}{8}$ -□703 | 450  | 520   |                        |            |

\*1 The flow rate characteristics of this product have variations.

\*2 Add 20 g for grommet with PCB, 70 g for conduit, 50 g for DIN terminal, and 15 g for M12 connector.

\*3 The values were calculated based on the combination of Rc, NPT thread, and grommet. Add 30 g for G thread (port size 3/8).

### Applicable Fluid Check List


| Applicable fluid | Seal material |     |      |
|------------------|---------------|-----|------|
|                  | NBR           | FKM | EPDM |
| Air              | ●             | ●   | ●    |
| Water            | ●             | ●   | ●    |
| Oil              | —             | ●   | —    |

\* The list shows the compatibility between general fluids and seal materials. Consider the operating environment and application sufficiently before selecting the seal material. Fluid and component compatibility should be checked in the application before use. If something is not clear, please contact SMC.

## Construction

### JSX10

Body material: Stainless steel, Brass




#### Component Parts

| No. | Description       | Material                              |
|-----|-------------------|---------------------------------------|
| 1   | Clip              | Stainless steel                       |
| 2   | Solenoid coil     | Stainless steel, Cu, Resin            |
| 3   | Stopper           | PPS                                   |
| 4   | Tube assembly     | Stainless steel                       |
| 5   | Armature assembly | Stainless steel, PPS, NBR (FKM, EPDM) |
| 6   | Spring            | Stainless steel                       |
| 7   | Set nut           | Stainless steel                       |
| 8   | Gasket            | NBR, (FKM, EPDM)                      |
| 9   | Body              | Stainless steel   Brass               |

### JSX20, 30


Body material: Stainless steel



#### Component Parts

| No. | Description       | Material                              |
|-----|-------------------|---------------------------------------|
| 1   | Clip              | Stainless steel                       |
| 2   | Solenoid coil     | Stainless steel, Cu, Resin            |
| 3   | Stopper           | PPS                                   |
| 4   | Spring            | Stainless steel                       |
| 5   | Tube assembly     | Stainless steel                       |
| 6   | Armature assembly | Stainless steel, PPS, NBR (FKM, EPDM) |
| 7   | Nut               | Stainless steel                       |
| 8   | Gasket            | NBR (FKM, EPDM)                       |
| 9   | Body              | Stainless steel                       |

Body material: Brass



#### Component Parts

| No. | Description       | Material                              |
|-----|-------------------|---------------------------------------|
| 1   | Clip              | Stainless steel                       |
| 2   | Solenoid coil     | Stainless steel, Cu, Resin            |
| 3   | Stopper           | PPS                                   |
| 4   | Spring            | Stainless steel                       |
| 5   | Tube assembly     | Stainless steel                       |
| 6   | Armature assembly | Stainless steel, PPS, NBR (FKM, EPDM) |
| 7   | Mounting screw    | Fe                                    |
| 8   | Bonnet            | Stainless steel                       |
| 9   | Gasket            | NBR (FKM, EPDM)                       |
| 10  | Body              | Brass                                 |

## Common Specifications

| Size                            |   | 10  | 20  | 30   |        |
|---------------------------------|---|---|---|------|--------|
| Valve specifications            | Valve construction  | Direct operated poppet  |   |      |        |
|                                 | Valve type  | Normally closed (N.C.)  |   |      |        |
|                                 | Fluid and fluid temperature                                     | Air : -10 to 60 °C (Dew point temperature: -10 °C or less)<br>Water: 1 to 60 °C (No freezing)<br>Oil : -5 to 60 °C (Kinematic viscosity: 50 mm <sup>2</sup> /s or less) |   |      |        |
|                                 | Withstand pressure  | 2.0 MPa   |   |      |        |
|                                 | Max. system pressure  | 1.0 MPa   |   |      |        |
|                                 | Ambient temperature   | -20 to 60 °C  |   |      |        |
|                                 | Valve leakage* <sup>1</sup> /<br>External leakage* <sup>1</sup> | Air   | 1 cm <sup>3</sup> /min (ANR) or less                        |      |        |
|                                 |   | Water, Oil  | 0.1 cm <sup>3</sup> /min or less                            |      |        |
|                                 | Mounting orientation  | Unrestricted  |   |      |        |
|                                 | Enclosure* <sup>2</sup>   | IP67 (IP65 for the DIN terminal)  |   |      |        |
|                                 | Standards* <sup>3</sup>   | CE, UL Recognised, UL Listed  |   |      |        |
|                                 | Operating environment   | Location without the presence of corrosive gases, explosive gases, or constant fluid adhesion   |   |      |        |
| Body material                   | Stainless steel, Brass  |   |   |      |        |
| Seal material                   | NBR, FKM, EPDM  |   |   |      |        |
| Coil specifications             | Rated voltage   | AC  | 24 V, 48 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V |      |        |
|                                 |   | DC  | 12 V, 24 V  |      |        |
|                                 | Allowable voltage fluctuation                                   | ±10 % of rated voltage  |   |      |        |
|                                 | Allowable leakage voltage                                       | AC  | 5 % or less of rated voltage                                |      |        |
|                                 |   | DC  | 2 % or less of rated voltage                                |      |        |
|                                 | Apparent power* <sup>4</sup> , * <sup>5</sup>                   | AC  | 4.5 VA  | 8 VA | 9.5 VA |
| Power consumption* <sup>4</sup> | DC  | 4 W   | 6 W   | 8 W  |        |
| Temperature rise* <sup>6</sup>  | AC/DC   | 70/65 °C  |   |      |        |

\*1 The leakage amount value at a differential pressure of 0.01 MPa or higher and an ambient temperature of 20 °C

\*2 This product ensures IP67, but if water enters the product, it may result in operation failure or breakage.

Therefore, take appropriate measures to prevent water from entering the product when used in an environment where it is constantly exposed to water.

\*3 Conformance to standards varies depending on the model. For details, refer to pages 5 and 37.

\*4 Power consumption/Apparent power: The value at an ambient temperature of 20 °C and when the rated voltage is applied (Variation: ±10 %)

\*5 There is no difference in the frequency and the inrush and energized apparent power, since a rectifying circuit is used in the AC.

\*6 Temperature rise: The value at an ambient temperature of 20 °C and when the rated voltage is applied. The value depends on the ambient environment. This is for reference.

**Be sure to read "Specific Product Precautions" before handling.**

# Direct Operated 2-Port Solenoid Valve

## JSX Series

Body Material **Aluminium**



For **Air**

### How to Order



**JSX** **2** **1** - **A** **N** **302** **R** - **5** **G** - **B**

1 2 3 4 5 6 7 8 9

#### 1 Size

| Symbol | Size |
|--------|------|
| 2      | 20   |
| 3      | 30   |

#### 2 Valve type

| Symbol | Valve type |
|--------|------------|
| 1      | N.C.       |

#### 3 Body material

| Symbol | Body material |
|--------|---------------|
| A      | Aluminium     |

#### 4 Seal material

| Symbol | Seal material |
|--------|---------------|
| N      | NBR           |
| F      | FKM           |

#### 5 Orifice diameter and port size

| Symbol | Orifice diameter [mmØ] | Port size | Size                 |                      |
|--------|------------------------|-----------|----------------------|----------------------|
|        |                        |           | 20<br>Aluminium body | 30<br>Aluminium body |
| 301    | 3                      | 1/8       | ●                    | —                    |
| 302    |                        | 1/4       | ●                    | —                    |
| 402    | 4                      | 1/4       | —                    | ●                    |
| 403    |                        | 3/8       | —                    | ●                    |
| 501    | 5                      | 1/8       | ●                    | —                    |
| 502    |                        | 1/4       | ●                    | —                    |
| 702    | 7                      | 1/4       | —                    | ●                    |
| 703    |                        | 3/8       | —                    | ●                    |

#### 6 Thread type

| Symbol | Thread type |
|--------|-------------|
| R      | Rc          |
| N      | NPT         |
| F      | G           |

#### 7 Rated voltage

| AC     |               | DC     |               |
|--------|---------------|--------|---------------|
| Symbol | Rated voltage | Symbol | Rated voltage |
| 1      | 100 VAC       | 7      | 240 VAC       |
| 2      | 200 VAC       | 8      | 48 VAC        |
| 3      | 120 (110) VAC | B      | 24 VAC        |
| 4      | 220 VAC       | J      | 230 VAC       |
|        |               | 5      | 24 VDC        |
|        |               | 6      | 12 VDC        |

#### 9 Option

| Symbol | Option         |
|--------|----------------|
| —      | None           |
| B      | With bracket*1 |

\*1 Bracket assembly part nos. (page 50)

#### 8 Electrical entry

| Symbol | Electrical entry  | Size |    | Rated voltage |
|--------|---|------|----|---------------|
|        |   | 20   | 30 |               |
| G      | Grommet*1   | ●    | ●  | 5             |
|        |   |      |    | 6             |
| GS     | Grommet with PCB (With surge voltage suppressor)                        |      |    | 1             |
|        |   |      |    | 5             |
|        |   |      |    | 6             |
|        |   |      |    | 8             |
|        |   |      |    | B             |
| CS     | Conduit (With surge voltage suppressor)                                 | ●    | ●  | All voltages  |
|        |   |      |    |               |
| DS     | DIN terminal (With surge voltage suppressor)                            | ●    | ●  | All voltages  |
|        |   |      |    |               |
| DZ     | DIN terminal with light (With surge voltage suppressor)                 | ●    | ●  | All voltages  |
|        |   |      |    |               |
| DN     | DIN terminal without connector (With surge voltage suppressor)          | ●    | ●  | All voltages  |
|        |   |      |    |               |
| WN     | M12 connector/Without connector cable (With surge voltage suppressor)*2 | ●    | ●  | All voltages  |
|        |   |      |    |               |

\*1 DC voltage only

\*2 A cable for the M12 connector is not included with the product. Refer to "Option" on page 38 to order it separately.

## Flow Rate Characteristics

### Aluminium Body Type

| Size | Port size | Orifice diameter [mmØ] | Flow rate characteristics*1  |      |      | Max. operating pressure differential [MPa] | Model       | Weight*2 [g] |
|------|-----------|------------------------|------------------------------|------|------|--|-------------|--------------|
|      |           |                        | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   |  |             |              |
| 20   | 1/8, 1/4  | 3                      | 1.41                         | 0.54 | 0.35 | 0.7  | JSX21-A□30□ | 240          |
|      |           | 5                      | 1.66                         | 0.54 | 0.52 | 0.2  | JSX21-A□50□ | 240          |
| 30   | 1/4, 3/8  | 4                      | 1.57                         | 0.59 | 0.52 | 1.0  | JSX31-A□40□ | 400          |
|      |           | 7                      | 3.02                         | 0.53 | 0.88 | 0.2  | JSX31-A□70□ | 400          |

\*1 The flow rate characteristics of this product have variations.


\*2 Indicates case of grommet type

Add 20 g for grommet with PCB, 70 g for conduit, 50 g for DIN terminal, and 15 g for M12 connector.

## Construction

JSX20, 30

Body material: Aluminium



### Component Parts

| No. | Description       | Material                         |
|-----|-------------------|----------------------------------|
| 1   | Clip              | Stainless steel                  |
| 2   | Solenoid coil     | Stainless steel, Cu, Resin       |
| 3   | Stopper           | PPS                              |
| 4   | Spring            | Stainless steel                  |
| 5   | Tube assembly     | Stainless steel                  |
| 6   | Armature assembly | Stainless steel, PPS, NBR, (FKM) |
| 7   | Mounting screw    | Fe                               |
| 8   | Bonnet            | Stainless steel                  |
| 9   | Gasket            | NBR, (FKM)                       |
| 10  | Body              | Aluminium                        |

## Common Specifications

| Size                            |   | 10  | 20  | 30   |
|---------------------------------|---|---|---|------|
| Valve specifications            | Valve construction  | Direct operated poppet  |   |      |
|                                 | Valve type  | Normally closed (N.C.)  |   |      |
|                                 | Fluid and fluid temperature                                 | Air: -10 to 60 °C (Dew point temperature: -10 °C or less)                                     |   |      |
|                                 | Withstand pressure  | 2.0 MPa   |   |      |
|                                 | Max. system pressure  | 1.0 MPa   |   |      |
|                                 | Ambient temperature   | -20 to 60 °C  |   |      |
|                                 | Valve leakage* <sup>1</sup> /External leakage* <sup>1</sup> | Air   | 1 cm <sup>3</sup> /min (ANR) or less                        |      |
|                                 | Mounting orientation  | Unrestricted  |   |      |
|                                 | Enclosure* <sup>2</sup>                                     | IP67 (IP65 for the DIN terminal)  |   |      |
|                                 | Standards* <sup>3</sup>                                     | CE  |   |      |
|                                 | Operating environment                                       | Location without the presence of corrosive gases, explosive gases, or constant fluid adhesion |   |      |
| Body material                   | Aluminium   |   |   |      |
| Seal material                   | NBR, FKM  |   |   |      |
| Coil specifications             | Rated voltage   | AC  | 24 V, 48 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V |      |
|                                 |   | DC  | 12 V, 24 V  |      |
|                                 | Allowable voltage fluctuation                               | ±10 % of rated voltage  |   |      |
|                                 | Allowable leakage voltage                                   | AC  | 5 % or less of rated voltage                                |      |
|                                 |   | DC  | 2 % or less of rated voltage                                |      |
|                                 | Apparent power* <sup>4</sup> , * <sup>5</sup>               | AC  | 4.5 VA  | 8 VA |
| Power consumption* <sup>4</sup> | DC  | 4 W   | 6 W   | 8 W  |
| Temperature rise* <sup>6</sup>  | AC/DC   | 70/65 °C  |   |      |

\*1 The leakage amount value at a differential pressure of 0.01 MPa or higher and an ambient temperature of 20 °C

\*2 This product ensures IP67, but if water enters the product, it may result in operation failure or breakage.

Therefore, take appropriate measures to prevent water from entering the product when used in an environment where it is constantly exposed to water.

\*3 Conformance to standards varies depending on the model. For details, refer to page 7.

\*4 Power consumption/Apparent power: The value at an ambient temperature of 20 °C and when the rated voltage is applied (Variation: ±10 %)

\*5 There is no difference in the frequency and the inrush and energized apparent power, since a rectifying circuit is used in the AC.


\*6 Temperature rise: The value at an ambient temperature of 20 °C and when the rated voltage is applied. The value depends on the ambient environment. This is for reference.

**Be sure to read "Specific Product Precautions" before handling.**


# JSX Series

Dimensions: JSX **10** Port Size **1/8** Body Material **Stainless Steel, Brass**

## G: Grommet




## GS: Grommet with PCB




## DS: DIN terminal

## DZ: DIN terminal with light




Dimensions: JSX **10** Port Size **1/8** Body Material **Stainless Steel, Brass**

**DN: DIN terminal without connector**




**WN: M12 connector**



**G thread type**


\* Dimensions other than those below are the same as those of the Rc type.




# JSX Series

Dimensions: **JSX20** Port Size **1/8** Body Material **Stainless Steel**


## G: Grommet



## GS: Grommet with PCB




## CS: Conduit





## DS: DIN terminal

## DZ: DIN terminal with light





Dimensions: **JSX20** Port Size **1/8** Body Material **Stainless Steel**

**DN: DIN terminal without connector**





**WN: M12 connector**



**G thread type**


\* Dimensions other than those below are the same as those of the Rc type.




# JSX Series

Dimensions: JSX **20, 30** Port Size **1/4, 3/8** Body Material **Stainless Steel**


## G: Grommet



## GS: Grommet with PCB



## CS: Conduit



| [mm] |           |      |    |    |    |      |    |
|------|-----------|------|----|----|----|------|----|
| Size | Port size | A    | B  | C  | D  | E    | F  |
| 20   | 1/4       | 28.1 | 40 | 69 | 36 | 12.5 | 18 |
|      | 3/8       |      | 48 |    |    | 14   |    |
|      | G3/8      |      | 72 | 14 |    |      |    |
| 30   | 1/4       | 28.1 | 40 | 78 | 42 | 12.5 | 21 |
|      | 3/8       |      | 48 |    |    | 14   |    |
|      | G3/8      |      | 81 | 14 |    |      |    |


| Size | Port size | Grommet |      | Grommet with PCB |    | Conduit |      |
|------|-----------|---------|------|------------------|----|---------|------|
|      |           | J       | K    | J                | K  | J       | K    |
| 20   | 1/4       | 39      | 28.5 | 44.8             | 38 | 46.4    | 48.9 |
|      | 3/8       |         |      | 47.8             |    | 49.4    |      |
|      | G3/8      |         |      | 42               |    | 49.4    |      |
| 30   | 1/4       | 40      | 31.1 | 45.8             | 41 | 47.4    | 51.9 |
|      | 3/8       |         |      | 48.8             |    | 50.4    |      |
|      | G3/8      |         |      | 43               |    | 50.4    |      |

Dimensions: **JSX20, 30** Port Size **1/4, 3/8** Body Material **Stainless Steel**


**DS:** DIN terminal

**DZ:** DIN terminal with light

**DN:** DIN terminal without connector



**WN:** M12 connector




| [mm] |           |      |    |    |    |      |    |
|------|-----------|------|----|----|----|------|----|
| Size | Port size | A    | B  | C  | D  | E    | F  |
| 20   | 1/4       | 28.1 | 40 | 69 | 36 | 12.5 | 18 |
|      | 3/8       |      | 48 |    |    |      |    |
|      | G3/8      |      | 72 | 14 |    |      |    |
| 30   | 1/4       | 28.1 | 40 | 78 | 42 | 12.5 | 21 |
|      | 3/8       |      | 48 |    |    |      |    |
|      | G3/8      |      | 81 | 14 |    |      |    |

| Size | Port size | DIN terminal |      |    | DIN terminal without connector |      | M12 connector |      |
|------|-----------|--------------|------|----|--------------------------------|------|---------------|------|
|      |           | J            | K    | L  | J                              | K    | J             | K    |
| 20   | 1/4       | 47.9         | 55.3 | 67 | 47.9                           | 31.3 | 46.7          | 41.1 |
|      | 3/8       |              |      |    | 50.9                           |      | 49.7          |      |
|      | G3/8      |              |      |    | 50.9                           |      | 49.7          |      |
| 30   | 1/4       | 48.9         | 58.3 | 70 | 48.9                           | 34.3 | 47.7          | 44.1 |
|      | 3/8       |              |      |    | 51.9                           |      | 50.7          |      |
|      | G3/8      |              |      |    | 51.9                           |      | 50.7          |      |




# JSX Series

Dimensions: JSX **20, 30** Port Size **1/8, 1/4, 3/8** Body Material **Brass**



## G: Grommet



## GS: Grommet with PCB



## CS: Conduit



[mm]

| Size | Port size | A  | B  | C    | D  | E  | F  | G    | H    | N   |
|------|-----------|----|----|------|----|----|----|------|------|-----|
| 20   | 1/8       | 14 | 30 | 69.2 | 36 | 9  | 18 | 15   | 17.5 | 6.4 |
|      | 1/4       | 19 | 40 | 67.7 |    |    |    | 22.2 | 22.2 | 7.6 |
|      | 3/8       | 22 | 48 | 70.7 |    | 11 |    | 19   | 20.6 | 6   |
| 30   | 1/4       | 19 | 40 | 76.7 | 42 | 9  | 21 | 22.2 | 22.2 | 7.6 |
|      | 3/8       | 22 | 48 | 79.7 |    | 11 |    | 19   | 20.6 | 6   |


| Size | Port size | Grommet |      | Grommet with PCB |    | Conduit |      |
|------|-----------|---------|------|------------------|----|---------|------|
|      |           | J       | K    | J                | K  | J       | K    |
| 20   | 1/8       | 39.4    | 28.5 | 45.2             | 38 | 46.8    | 48.9 |
|      | 1/4       | 37.9    |      | 43.7             |    | 45.3    |      |
|      | 3/8       | 40.9    |      | 46.7             |    | 48.3    |      |
| 30   | 1/4       | 39      | 31.1 | 44.7             | 41 | 46.3    | 51.9 |
|      | 3/8       | 42      |      | 47.7             |    | 49.3    |      |

Dimensions: **JSX20, 30** Port Size **1/8, 1/4, 3/8** Body Material **Brass**


**DS:** DIN terminal

**DZ:** DIN terminal with light

**DN:** DIN terminal without connector



**WN:** M12 connector



[mm]



| Size | Port size | A  | B  | C    | D  | E  | F  | G    | H    | N   |
|------|-----------|----|----|------|----|----|----|------|------|-----|
| 20   | 1/8       | 14 | 30 | 69.2 | 36 | 9  | 18 | 15   | 17.5 | 6.4 |
|      | 1/4       | 19 | 40 | 67.7 |    |    |    | 22.2 | 22.2 | 7.6 |
|      | 3/8       | 22 | 48 | 70.7 |    | 11 |    | 19   | 20.6 | 6   |
| 30   | 1/4       | 19 | 40 | 76.7 | 42 | 9  | 21 | 22.2 | 22.2 | 7.6 |
|      | 3/8       | 22 | 48 | 79.7 |    | 11 |    | 19   | 20.6 | 6   |

| Size | Port size | DIN terminal |      |    | DIN terminal without connector |      | M12 connector |      |
|------|-----------|--------------|------|----|--------------------------------|------|---------------|------|
|      |           | J            | K    | L  | J                              | K    | J             | K    |
| 20   | 1/8       | 48.3         | 55.3 | 67 | 48.3                           | 31.3 | 47            | 41.1 |
|      | 1/4       | 46.8         |      |    | 46.8                           |      | 45.5          |      |
|      | 3/8       | 49.8         |      |    | 49.8                           |      | 48.5          |      |
| 30   | 1/4       | 47.8         | 58.3 | 70 | 47.8                           | 34.3 | 46.6          | 44.1 |
|      | 3/8       | 50.8         |      |    | 50.8                           |      | 49.6          |      |



# JSX Series

Dimensions: JSX **20, 30** Port Size **1/8, 1/4, 3/8** Body Material **Aluminium**



## G: Grommet



## GS: Grommet with PCB



## CS: Conduit



| Size | Port size | A  | B  | B <sub>1</sub> | C    | D  | E   | F  | G    | M  | N |
|------|-----------|----|----|----------------|------|----|-----|----|------|----|---|
| 20   | 1/8, 1/4  | 19 | 43 | 21             | 64.3 | 36 | 9.5 | 18 | 12.8 | M4 | 6 |
| 30   | 1/4, 3/8  | 24 | 45 | 22.5           | 80.7 | 42 | 12  | 21 | 19   | M5 | 8 |

[mm]


| Size | Port size | Grommet |      | Grommet with PCB |    | Conduit |      |
|------|-----------|---------|------|------------------|----|---------|------|
|      |           | J       | K    | J                | K  | J       | K    |
| 20   | 1/8, 1/4  | 34.6    | 28.5 | 40.3             | 38 | 41.9    | 48.9 |
| 30   | 1/4, 3/8  | 43      | 31.1 | 48.7             | 41 | 50.3    | 51.9 |

Dimensions: **JSX20, 30** Port Size **1/8, 1/4, 3/8** Body Material **Aluminium**


**DS:** DIN terminal

**DZ:** DIN terminal with light

**DN:** DIN terminal without connector



**WN:** M12 connector



| Size | Port size | A  | B  | B <sub>1</sub> | C    | D  | E   | F  | G    | M  | N |
|------|-----------|----|----|----------------|------|----|-----|----|------|----|---|
| 20   | 1/8, 1/4  | 19 | 43 | 21             | 64.3 | 36 | 9.5 | 18 | 12.8 | M4 | 6 |
| 30   | 1/4, 3/8  | 24 | 45 | 22.5           | 80.7 | 42 | 12  | 21 | 19   | M5 | 8 |


| Size | Port size | DIN terminal |      |    | DIN terminal without connector |      | M12 connector |      |
|------|-----------|--------------|------|----|--------------------------------|------|---------------|------|
|      |           | J            | K    | L  | J                              | K    | J             | K    |
| 20   | 1/8, 1/4  | 43.4         | 55.3 | 67 | 43.4                           | 31.3 | 42.2          | 41.1 |
| 30   | 1/4, 3/8  | 51.8         | 58.3 | 70 | 51.8                           | 34.3 | 50.6          | 44.1 |

[mm]


# JSX Series

## Dimensions: Bracket Options


### JSX10 Body Material Stainless Steel, Brass



### JSX20, 30 Body Material Aluminium



### JSX20, 30 Body Material Brass



#### Body Material: Brass

| Size   | Port size | A  | B  | C | D  | E  | F   | ØJ |
|--------|-----------|----|----|---|----|----|-----|----|
| 20     | 1/8       | 52 | 24 | 9 | 36 | 64 | 1.5 | 6  |
| 20, 30 | 1/4       | 52 | 24 | 9 | 36 | 64 | 1.5 | 6  |
|        | 3/8       |    |    |   |    |    |     |    |



#### Body Material: Aluminium

| Size | Port size | A  | B  | C | D  | E  | F   | ØJ  |
|------|-----------|----|----|---|----|----|-----|-----|
| 20   | 1/8, 1/4  | 11 | 36 | 6 | 34 | 46 | 1.5 | 5.3 |
| 30   | 1/4, 3/8  | 13 | 46 | 7 | 40 | 56 | 1.5 |     |

**Dimensions: Bracket Options**

**JSX20, 30** Body Material **Stainless Steel**  
(Port size 1/8 type)

**JSX20, 30** Body Material **Stainless Steel**  
(Port size 1/4, 3/8 type)



**Stainless Steel**


[mm]

| Size   | Port size | A  | B  | C | D  | E  | F   | G    | H    | ØJ  |
|--------|-----------|----|----|---|----|----|-----|------|------|-----|
| 20     | 1/8       | 13 | 46 | 7 | 40 | 56 | 1.5 | —    | —    | 5.3 |
| 20, 30 | 1/4, 3/8  | 13 | 46 | 4 | 33 | 56 | 1.5 | 22.2 | 22.2 | 5.3 |
|        | G3/8      |    |    |   |    |    |     | 19   | 20.6 |     |

# Pilot Operated 2-Port Solenoid Valve JSXD Series



## How to Order



JSXD **3** **1** - **C** **N** **02** **R** - **5** **G** - **D** - **B**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

### ① Size

| Symbol | Size |
|--------|------|
| 3      | 30   |
| 4      | 40   |
| 5      | 50   |
| 6      | 60   |
| 7      | 70   |
| 8      | 80   |
| 9      | 90   |

### ② Valve type

| Symbol | Valve type |
|--------|------------|
| 1      | N.C.       |

### ③ Body material

| Symbol | Body material   | Size |            |            |
|--------|-----------------|------|------------|------------|
|        |                 | 30   | 40, 50, 60 | 70, 80, 90 |
| C      | Brass           | ●    | ●          | —          |
| S      | Stainless steel | ●    | ●          | —          |
| B      | Bronze          | —    | —          | ●          |
| A      | Aluminium       | ●    | —          | —          |

### ④ Seal material

| Symbol | Seal material |
|--------|---------------|
| N      | NBR           |
| F      | FKM           |
| E*1    | EPDM          |

\*1 Cannot be used in combination with the aluminium body

### ⑤ Port size

| Symbol | Connection | Port size | Size |    |    |    |    |    |    |
|--------|------------|-----------|------|----|----|----|----|----|----|
|        |            |           | 30   | 40 | 50 | 60 | 70 | 80 | 90 |
| 02     | Thread     | 1/4       | ●    | —  | —  | —  | —  | —  | —  |
| 03     |            | 3/8       | ●    | ●  | —  | —  | —  | —  |    |
| 04     |            | 1/2       | ●    | ●  | —  | —  | —  | —  |    |
| 06     |            | 3/4       | —    | —  | ●  | —  | —  | —  |    |
| 10     |            | 1         | —    | —  | —  | ●  | —  | —  |    |
| 12     |            | 1 1/4     | —    | —  | —  | —  | ●  | —  |    |
| 14     |            | 1 1/2     | —    | —  | —  | —  | —  | ●  |    |
| 20     |            | 2         | —    | —  | —  | —  | —  | —  | ●  |

### ⑧ Electrical entry

| Symbol | Electrical entry   | Rated voltage |
|--------|--|---------------|
| G      | Grommet*1  | 6             |
|        |  | 5             |
| GS     | Grommet with PCB (With surge voltage suppressor)               | 1             |
|        |  | 5             |
|        |  | 6             |
|        |  | 8             |
| B      |  |               |
| CS     | Conduit (With surge voltage suppressor)                        | All voltages  |
| DS     | DIN terminal (With surge voltage suppressor)                   | All voltages  |
| DZ     | DIN terminal with light (With surge voltage suppressor)        | All voltages  |
| DN     | DIN terminal without connector (With surge voltage suppressor) | All voltages  |
| WN     | M12 connector without cable (With surge voltage suppressor)*2  | All voltages  |

### ⑥ Thread type

| Symbol | Thread type |
|--------|-------------|
| R      | Rc          |
| N      | NPT         |
| F      | G           |

### ⑦ Rated voltage

| AC     |               |        |               | DC     |               |
|--------|---------------|--------|---------------|--------|---------------|
| Symbol | Rated voltage | Symbol | Rated voltage | Symbol | Rated voltage |
| 1      | 100 VAC       | 7      | 240 VAC       | 5      | 24 VDC        |
| 2      | 200 VAC       | 8      | 48 VAC        | 6      | 12 VDC        |
| 3      | 120 (110) VAC | B      | 24 VAC        |        |               |
| 4      | 220 VAC       | J      | 230 VAC       |        |               |

### ⑨ Oil-free option

| Symbol | Option   |
|--------|----------|
| —      | None     |
| D      | Oil-free |

### ⑩ Bracket

| Symbol | With bracket | Size |            |            |
|--------|--------------|------|------------|------------|
|        |              | 30   | 40, 50, 60 | 70, 80, 90 |
| —      | None         | ●    | ●          | ●          |
| B      | With bracket | ●    | ●          | —*1        |

\*1 Sizes 70 to 90 are not available with a bracket.

\*1 DC voltage only

\*2 A cable for the M12 connector is not included with the product. Refer to "Option" on page 38 to order it separately.

## Flow Rate Characteristics

| Size | Body material            | Port size  | Orifice diameter [mmØ] | Flow rate characteristics*1  |      |      |                                   |            |               | Min. operating pressure differential [MPa] | Max. operating pressure differential [MPa] | Model       | Weight*2 [g]      |           |
|------|--------------------------|------------|------------------------|------------------------------|------|------|-----------------------------------|------------|---------------|--|--|-------------|-------------------|-----------|
|      |                          |            |                        | Air                          |      |      |                                   | Water, Oil |               |  |  |             |                   |           |
|      |                          |            |                        | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   | Effective area [mm <sup>2</sup> ] | Kv         | Conversion Cv |  |  |             |                   |           |
| 30   | Aluminium                | 1/4        | 10                     | 8.5                          | 0.35 | 2.0  | —                                 | —          | —             | 0.02                                       | 1.0  | JSXD31-A□02 | 410               |           |
|      |                          | 3/8        |                        | 9.2                          |      | 2.4  |                                   |            |               |  |  | JSXD31-A□03 | 410               |           |
|      |                          | 1/2        |                        | 9.2                          |      | 2.4  |                                   |            |               |  |  | JSXD31-A□04 | 410               |           |
|      | Brass<br>Stainless steel | 1/4        |                        | 8.5                          | 2.0  | 1.6  |                                   | 1.9        | JSXD31-□□02   |  |  | 500         |                   |           |
|      |                          | 3/8        |                        | 9.2                          | 2.4  | 2.0  |                                   | 2.4        | JSXD31-□□03   |  |  | 500         |                   |           |
|      |                          | 1/2        |                        | 9.2                          | 2.4  | 2.0  |                                   | 2.4        | JSXD31-□□04   |  |  | 500         |                   |           |
| 40   | Brass<br>Stainless steel | 3/8        | 15                     | 18                           | 0.35 | 0.35 | —                                 | 3.9        | 4.5           | 0.03                                       | 1.0  | JSXD41-□□03 | 720               |           |
|      |                          | 1/2        |                        | 20                           |      | 0.35 |                                   | 4.6        | 5.5           |  |  | JSXD41-□□04 | 720               |           |
| 50   | Brass/Stainless steel    | 3/4        | 20                     | 38                           | 0.30 | 9.5  | —                                 | 8.2        | 9.5           | —  | —  | JSXD51-□□06 | 880               |           |
| 60   | Brass/Stainless steel    | 1          | 25                     | —                            | —    | —    | —                                 | 225        | 11.0          | 13.0                                       | —  | —           | JSXD61-□□10       | 1460      |
| 70   | Bronze                   | 1 1/4, 32A | 35                     | —                            | —    | —    | —                                 | 415        | 19.6          | 23.0                                       | 0.03                                       | 1.0         | JSXD71-B□(12, 32) | 5500/3000 |
| 80   | Bronze                   | 1 1/2, 40A | 40                     | —                            | —    | —    | —                                 | 560        | 26.4          | 31.0                                       |  |             | JSXD81-B□(14, 40) | 6900/4100 |
| 90   | Bronze                   | 2, 50A     | 50                     | —                            | —    | —    | —                                 | 880        | 42.8          | 49.0                                       |  |             | JSXD91-B□(20, 50) | 8500/5500 |

\*1 The flow rate characteristics of this product have variations.

\*2 Indicates case of grommet type

Add 20 g for grommet with PCB, 70 g for conduit, 50 g for DIN terminal, and 15 g for M12 connector.

For sizes 70, 80, and 90, the weight on the left is for the flange type, and the weight on the right is for the thread type.

## Applicable Fluid Check List

| Applicable fluid | Seal material |     |      |
|------------------|---------------|-----|------|
|                  | NBR           | FKM | EPDM |
| Air              | ●             | ●   | ●    |
| Water            | ●             | ●   | ●    |
| Oil              | —             | ●   | —    |

\* The list shows the compatibility between general fluids and seal materials. Consider the operating environment and application sufficiently before selecting the seal material. Fluid and component compatibility should be checked in the application before use. If something is not clear, please contact SMC.

## Common Specifications

| Size                  |  | 30                               | 40  | 50   | 60  | 70     | 80                                    | 90 |   |
|-----------------------|--|----------------------------------|---|--|-----|--------|---------------------------------------|----|---|
| Valve specifications  | Body material  | Aluminium                        | Brass, Stainless steel                                      | Brass, Stainless steel   |     |        | Bronze                                |    |   |
|                       | Valve construction   | Pilot operated diaphragm         |   |  |     |        |                                       |    |   |
|                       | Valve type   | Normally closed (N.C.)           |   |  |     |        |                                       |    |   |
|                       | Fluid and fluid temperature  | Air*1                            | -10 to 60 °C  |  |     |        |                                       |    |   |
|                       |  | Water, Oil                       | —   | Water: 1 to 60 °C (No freezing), Oil: -5 to 60 °C (Kinematic viscosity: 50 mm <sup>2</sup> /s or less) |     |        |                                       |    | — |
|                       | Withstand pressure   | 2 MPa                            |   |  |     |        |                                       |    |   |
|                       | Max. system pressure   | 1 MPa                            |   |  |     |        |                                       |    |   |
|                       | Ambient temperature  | -20 to 60 °C                     |   |  |     |        |                                       |    |   |
|                       | Valve leakage*2  | Air                              | 15 cm <sup>3</sup> /min (ANR) or less                       | 2 cm <sup>3</sup> /min (ANR) or less   |     |        | 10 cm <sup>3</sup> /min (ANR) or less |    |   |
|                       |  | Water, Oil                       | —   | 0.2 cm <sup>3</sup> /min or less   |     |        | 1 cm <sup>3</sup> /min or less        |    |   |
|                       | External leakage*2   | Air                              | 15 cm <sup>3</sup> /min (ANR) or less                       | 1 cm <sup>3</sup> /min (ANR) or less   |     |        |                                       |    | — |
|                       |  | Water, Oil                       | —   | 0.1 cm <sup>3</sup> /min (ANR) or less   |     |        |                                       |    | — |
|                       | Mounting orientation   | Unrestricted                     |   |  |     |        |                                       |    |   |
|                       | Enclosure*3  | IP67 (IP65 for the DIN terminal) |   |  |     |        |                                       |    |   |
| Standards*4           | CE   |                                  |   |  |     |        |                                       |    |   |
| Operating environment | Indoors, Location without the presence of corrosive gases, explosive gases, or constant fluid adhesion |                                  |   |  |     |        |                                       |    |   |
| Seal material         | NBR, FKM, EPDM   |                                  |   |  |     |        |                                       |    |   |
| Coil specifications   | Rated voltage  | AC                               | 24 V, 48 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V |  |     |        |                                       | —  |   |
|                       |  | DC                               | 12 V, 24 V  |  |     |        |                                       | —  |   |
|                       | Allowable voltage fluctuation  | ±10 % of rated voltage           |   |  |     |        |                                       |    |   |
|                       | Allowable leakage voltage  | AC                               | 5 % or less of rated voltage                                |  |     |        |                                       |    |   |
|                       |  | DC                               | 2 % or less of rated voltage                                |  |     |        |                                       |    |   |
|                       | Apparent power*5, *6   | AC                               | 8 VA  |  |     | 9.5 VA |                                       |    |   |
| Power consumption*5   | DC   | 6 W                              |   |  | 8 W |        |                                       |    |   |
| Temperature rise*7    | AC/DC  | 70/65 °C                         |   |  |     |        |                                       |    |   |

\*1 Dew point temperature: -10 °C or less

\*2 The leakage amount value at a differential pressure the same as or higher than the min. operating pressure differential, and an ambient temperature of 20 °C

\*3 This product ensures IP67, but if water enters the product, it may result in operation failure or breakage.

Therefore, take appropriate measures to prevent water from entering the product when used in an environment where it is constantly exposed to water.

\*4 Conformance to standards varies depending on the model. For details, refer to page 21.

\*5 Power consumption/Apparent power: The value at an ambient temperature of 20 °C and when the rated voltage is applied (Variation: ±10 %)

\*6 There is no difference in the frequency and the inrush and energized apparent power, since a rectifying circuit is used in the AC.

\*7 Temperature rise: The value at an ambient temperature of 20 °C and when the rated voltage is applied. The value depends on the ambient environment. This is for reference.


Be sure to read "Specific Product Precautions" before handling.

# JSXD Series

## Construction

JSXD30, Normally closed (N.C.)

Body material: Brass, Stainless steel, Aluminium




### Component Parts

| No. | Description        | Material                               |                                  |            |
|-----|--------------------|--|----------------------------------|------------|
|     |                    | Brass                                  | Stainless steel                  | Aluminium  |
| 1   | Clip               | Stainless steel                        |                                  |            |
| 2   | Solenoid coil      | Stainless steel, Cu, Resin             |                                  |            |
| 3   | Stopper            | PPS                                    |                                  |            |
| 4   | Spring             | Stainless steel                        |                                  |            |
| 5   | Tube assembly      | Stainless steel                        |                                  |            |
| 6   | Armature assembly  | Stainless steel, PPS, NBR, (FKM, EPDM) | Stainless steel, PPS, NBR, (FKM) |            |
| 7   | Bracket            | Fe                                     |                                  |            |
| 8   | Mounting screw     | Fe                                     |                                  |            |
| 9   | Bonnet             | Stainless steel                        |                                  |            |
| 10  | Gasket             | NBR, (FKM, EPDM)                       | NBR, (FKM)                       |            |
| 11  | Bolt               | Fe                                     |                                  |            |
| 12  | Body               | Brass                                  | Stainless steel                  | Aluminium  |
| 13  | O-ring             | NBR, (FKM, EPDM)                       |                                  | NBR, (FKM) |
| 14  | Diaphragm assembly | Stainless steel, NBR, (FKM, EPDM)      | Stainless steel, NBR, (FKM)      |            |
| 15  | Valve spring       | Stainless steel                        |                                  |            |
| 16  | Buffer             | PPS                                    |                                  |            |
| 17  | Bonnet             | Stainless steel                        |                                  |            |
| 18  | Bolt               | Fe                                     |                                  |            |

JSXD40, Normally closed (N.C.)

Body material: Brass, Stainless steel




### Component Parts

| No. | Description        | Material                               |                 |
|-----|--------------------|--|-----------------|
|     |                    | Brass                                  | Stainless steel |
| 1   | Clip               | Stainless steel                        |                 |
| 2   | Solenoid coil      | Stainless steel, Cu, Resin             |                 |
| 3   | Stopper            | PPS                                    |                 |
| 4   | Spring             | Stainless steel                        |                 |
| 5   | Tube assembly      | Stainless steel                        |                 |
| 6   | Armature assembly  | Stainless steel, PPS, NBR, (FKM, EPDM) |                 |
| 7   | Mounting screw     | Fe                                     |                 |
| 8   | Bonnet             | Stainless steel                        |                 |
| 9   | Gasket             | NBR, (FKM, EPDM)                       |                 |
| 10  | Body               | Brass                                  | Stainless steel |
| 11  | O-ring             | NBR, (FKM, EPDM)                       |                 |
| 12  | Diaphragm assembly | Stainless steel, NBR, (FKM, EPDM)      |                 |
| 13  | Valve spring       | Stainless steel                        |                 |
| 14  | Buffer             | PPS                                    |                 |
| 15  | Bonnet             | Stainless steel                        |                 |
| 16  | Bolt               | Fe                                     |                 |
| 17  | Bracket            | Fe                                     |                 |

## Construction


**JSXD50, 60, Normally closed (N.C.)**  
**Body material: Brass, Stainless steel**



### Component Parts

| No. | Description        | Material                               |                 |
|-----|--------------------|--|-----------------|
|     |                    | Brass                                  | Stainless steel |
| 1   | Clip               |  | Stainless steel |
| 2   | Solenoid coil      | Stainless steel, Cu, Resin             |                 |
| 3   | Stopper            | PPS                                    |                 |
| 4   | Spring             | Stainless steel                        |                 |
| 5   | Tube assembly      | Stainless steel                        |                 |
| 6   | Armature assembly  | Stainless steel, PPS, NBR, (FKM, EPDM) |                 |
| 7   | Mounting screw     | Fe                                     |                 |
| 8   | Bonnet             | Stainless steel                        |                 |
| 9   | Gasket             | NBR, (FKM, EPDM)                       |                 |
| 10  | Body               | Brass                                  | Stainless steel |
| 11  | O-ring             | NBR, (FKM, EPDM)                       |                 |
| 12  | Diaphragm assembly | Stainless steel, NBR, (FKM, EPDM)      |                 |
| 13  | Valve spring       | Stainless steel                        |                 |
| 14  | Bonnet             | Brass                                  | Stainless steel |
| 15  | Bolt               | Fe                                     |                 |
| 16  | Bracket            | Fe                                     |                 |

**JSXD70, 80, 90, Normally closed (N.C.)**  
**Body material: Bronze**




### Component Parts

| No. | Description        | Material                               |                 |
|-----|--------------------|--|-----------------|
|     |                    | Brass                                  | Stainless steel |
| 1   | Clip               |  | Stainless steel |
| 2   | Solenoid coil      | Stainless steel, Cu, Resin             |                 |
| 3   | Stopper            | PPS                                    |                 |
| 4   | Spring             | Stainless steel                        |                 |
| 5   | Tube assembly      | Stainless steel                        |                 |
| 6   | Armature assembly  | Stainless steel, PPS, NBR, (FKM, EPDM) |                 |
| 7   | Mounting screw     | Fe                                     |                 |
| 8   | Bonnet             | Stainless steel                        |                 |
| 9   | Gasket             | NBR, (FKM, EPDM)                       |                 |
| 10  | Bonnet             | Bronze                                 |                 |
| 11  | Body               | Bronze                                 |                 |
| 12  | Bolt               | Fe                                     |                 |
| 13  | Valve spring       | Stainless steel                        |                 |
| 14  | Diaphragm assembly | Stainless steel, NBR, (FKM, EPDM)      |                 |


# JSXD Series

Dimensions: JSXD**30** Port Size **1/4, 3/8** Body Material **Aluminium, Brass, Stainless Steel**


**G: Grommet**



**GS: Grommet with PCB**




**CS: Conduit**




**DS: DIN terminal**


**DZ: DIN terminal with light**



**DN: DIN terminal without connector**




**WN: M12 connector**




Dimensions: **JSXD30** Port Size **1/2** Body Material **Aluminium, Brass, Stainless Steel**


**G: Grommet**



**GS: Grommet with PCB**




**CS: Conduit**




**DS: DIN terminal**


**DZ: DIN terminal with light**



**DN: DIN terminal without connector**




**WN: M12 connector**



**JSXD31-□□04**


\* Only the JSXD31 with port size of 04 (1/2) has threads on the bottom of the body.



# JSXD Series

Dimensions: JSXD40 Port Size 3/8, 1/2 Body Material Brass, Stainless Steel




G: Grommet



GS: Grommet with PCB



CS: Conduit

DS: DIN terminal  
DZ: DIN terminal with light




DN: DIN terminal without connector

WN: M12 connector




Dimensions: JSXD**50, 60** Port Size **3/4, 1** Body Material **Brass, Stainless Steel**


G: Grommet



GS: Grommet with PCB




CS: Conduit




DS: DIN terminal


DZ: DIN terminal with light



DN: DIN terminal without connector



WN: M12 connector



| Size | Port size | A     | B  | C  | D  | E  | F   | I  | J    | K    | L    | M  | Grommet |      | Grommet with PCB |    |
|------|-----------|-------|----|----|----|----|-----|----|------|------|------|----|---------|------|------------------|----|
|      |           |       |    |    |    |    |     |    |      |      |      |    | T       | U    | T                | U  |
| 50   | 3/4       | 110.6 | 29 | 36 | 71 | 18 | 4.5 | 17 | 51   | 32.5 | 38.5 | 35 | 51.9    | 28.5 | 57.6             | 38 |
| 60   | 1         | 131   | 33 | 42 | 95 | 21 | 4.5 | 20 | 59.5 | 45.5 | 49.5 | 42 | 60.4    | 31.1 | 66               | 41 |


  

| Size | Port size | Conduit |      | DIN terminal |      | V  | DIN terminal without connector |      | M12 connector |      | Bracket mount dimensions |      |    |    |      |
|------|-----------|---------|------|--------------|------|----|--------------------------------|------|---------------|------|--------------------------|------|----|----|------|
|      |           | T       | U    | T            | U    |    | T                              | U    | T             | U    | a                        | b    | d  | e  | f    |
| 50   | 3/4       | 59.2    | 48.9 | 60.7         | 55.3 | 67 | 60.7                           | 31.3 | 59.5          | 41.1 | 50.5                     | 77.5 | 74 | 51 | 45.5 |
| 60   | 1         | 67.6    | 51.9 | 69.1         | 58.3 | 70 | 69.1                           | 34.3 | 67.9          | 44.1 | 55.5                     | 85.5 | 81 | 58 | 49.5 |

# JSXD Series

Dimensions: JSXD **70, 80, 90** Port Size **1 1/4, 1 1/2, 2** Body Material **Bronze**

G: Grommet






GS: Grommet with PCB

CS: Conduit



DS: DIN terminal

DZ: DIN terminal with light



DN: DIN terminal without connector

WN: M12 connector



[mm]

| Size | Port size | A     | B    | C  | D   | E  | F    | I    | K    | L    | M  |
|------|-----------|-------|------|----|-----|----|------|------|------|------|----|
| 70   | 1 1/4     | 132.6 | 26.5 | 42 | 125 | 21 | 51.5 | 43.5 | 67.5 | 57.5 | 53 |
| 80   | 1 1/2     | 139.3 | 30   | 42 | 132 | 21 | 54.5 | 46.5 | 72   | 60   | 60 |
| 90   | 2         | 150.3 | 35.5 | 42 | 150 | 21 | 59   | 52   | 81   | 69   | 71 |

| Size | Port size | Grommet |      | Grommet with PCB |    | Conduit |      | DIN terminal |      |    | DIN terminal without connector |      | M12 connector |      |
|------|-----------|---------|------|------------------|----|---------|------|--------------|------|----|--------------------------------|------|---------------|------|
|      |           | T       | U    | T                | U  | T       | U    | T            | U    | V  | T                              | U    | T             | U    |
| 70   | 1 1/4     | 68.4    | 31.1 | 74.1             | 41 | 75.7    | 51.9 | 77.2         | 58.3 | 70 | 77.2                           | 34.3 | 76            | 44.1 |
| 80   | 1 1/2     | 71.6    | 31.1 | 77.3             | 41 | 78.9    | 51.9 | 80.4         | 58.3 | 70 | 80.4                           | 34.3 | 79.2          | 44.1 |
| 90   | 2         | 77.1    | 31.1 | 82.8             | 41 | 84.4    | 51.9 | 85.9         | 58.3 | 70 | 85.9                           | 34.3 | 84.7          | 44.1 |

# Modular Mounting Type 2-Port Solenoid Valve

## JSXM Series



### How to Order

JSXM **2** **1** - **A** **N** **301** **R** - **5** **G** - **U** - **F** - **D**

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

#### ① Size

| Symbol | Size |
|--------|------|
| 2      | 20   |
| 3      | 30   |
| 4      | 40   |

#### ② Valve type

| Symbol | Valve type |
|--------|------------|
| 1      | N.C.       |

#### ③ Body material

| Symbol | Body material |
|--------|---------------|
| A      | Aluminium     |

#### ④ Seal material

| Symbol | Seal material |
|--------|---------------|
| N      | NBR           |
| F      | FKM           |

#### ⑤ Orifice diameter and port size

| Symbol | Orifice diameter [mmØ] | Port size | Size |    |    |
|--------|------------------------|-----------|------|----|----|
|        |                        |           | 20   | 30 | 40 |
| 301    | 3.2                    | 1/8       | ●    | —  | —  |
| 302    |                        | 1/4       | ●    | —  | —  |
| 402    | 4.0                    | 1/4       | —    | ●  | ●  |
| 403    |                        | 3/8       | —    | ●  | ●  |
| 404    |                        | 1/2       | —    | —  | ●  |

#### ⑥ Thread type

| Symbol | Thread type |
|--------|-------------|
| R      | Rc          |
| N      | NPT         |
| F      | G           |

#### ⑦ Rated voltage

| AC     |               |        |               | DC     |               |
|--------|---------------|--------|---------------|--------|---------------|
| Symbol | Rated voltage | Symbol | Rated voltage | Symbol | Rated voltage |
| 1      | 100 VAC       | 7      | 240 VAC       | 5      | 24 VDC        |
| 2      | 200 VAC       | 8      | 48 VAC        | 6      | 12 VDC        |
| 3      | 120 (110) VAC | B      | 24 VAC        |        |               |
| 4      | 220 VAC       | J      | 230 VAC       |        |               |

#### ⑧ Electrical entry

| Symbol | Electrical entry   | Rated voltage |
|--------|--|---------------|
| G      | Grommet*1  | 6             |
| GS     | Grommet with PCB (With surge voltage suppressor)               | 5             |
|        |  | 1             |
|        |  | 5             |
|        |  | 6             |
| CS     | Conduit (With surge voltage suppressor)                        | 8             |
|        |  | B             |
| DS     | DIN terminal (With surge voltage suppressor)                   | All voltages  |
| DZ     | DIN terminal with light (With surge voltage suppressor)        | All voltages  |
| DN     | DIN terminal without connector (With surge voltage suppressor) | All voltages  |
| WN     | M12 connector without cable (With surge voltage suppressor)*2  | All voltages  |

\*1 DC voltage only

\*2 A cable for the M12 connector is not included with the product. Refer to "Option" on page 38 to order it separately.

#### ⑨ Coil orientation

| Symbol | Orientation |
|--------|-------------|
| —      | Upward      |
| U      | Downward    |

#### ⑩ Blow port position

Coil orientation: Upward (When "—" is selected for ⑨)

Coil orientation: Downward (When "U" is selected for ⑨)

| Symbol | Position | Symbol | Position |
|--------|----------|--------|----------|
| —      | Bottom   | —      | Top      |
| F      | Front    | F      | Front    |

#### ⑪ Oil-free option

| Symbol | Option   |
|--------|----------|
| —      | None     |
| D      | Oil-free |

## Simple Specials System

A system designed to respond quickly and easily to your special ordering needs

For modular connection units (shipped assembled), the simple specials system can be used.



#### Short lead times


This system enables us to respond to your special needs (additional machining, accessory assembly, or the designing of a modular unit) and deliver your personalised products as quickly as standard products.

#### Repeat orders

Once we receive a simple special part number from one of your previous orders, we will process the order, manufacture the product, and deliver it to you as quickly as possible.

Please contact your local sales representative for more details.

#### Connection Example



#### Ordering Example

|  |        |
|--|--------|
| ① Air combination AC20B-02E-D                                      | 1 pc.  |
| ② Modular mounting type 2-port solenoid valve JSXM21-AN302R-5G-U-F | 3 pcs. |
| ③ Spacer with bracket Y200T-D                                      | 1 pc.  |
| ④ Spacer Y200-D  | 2 pcs. |

## Flow Rate Characteristics

| Size | Port size | Orifice diameter [mmØ] | Flow rate characteristics*1  |      |      | Max. operating pressure differential [MPa] | Model       | Weight*2 [g] |
|------|-----------|------------------------|------------------------------|------|------|--|-------------|--------------|
|      |           |                        | Air                          |      |      |  |             |              |
|      |           |                        | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   |  |             |              |
| 20   | 1/8       | 3.2                    | 1.36                         | 0.47 | 0.40 | 0.7  | JSXM21-A□01 | 300          |
|      | 1/4       |                        |                              |      |      |  | JSXM21-A□02 | 300          |
| 30   | 1/4       | 4.0                    | 1.55                         | 0.59 | 0.50 | 1.0  | JSXM31-A□02 | 500          |
|      | 3/8       |                        |                              |      |      |  | JSXM31-A□03 | 500          |
| 40   | 1/4       | 4.0                    | 1.55                         | 0.59 | 0.50 | 1.0  | JSXM41-A□02 | 630          |
|      | 3/8       |                        |                              |      |      |  | JSXM41-A□03 | 630          |
|      | 1/2       |                        |                              |      |      |  | JSXM41-A□04 | 630          |

\*1 The flow rate characteristics of this product have variations.

\*2 Indicates case of grommet type

Add 20 g for grommet with PCB, 70 g for conduit, 50 g for DIN terminal, and 15 g for M12 connector.

## Common Specifications

| Size                 |                                    | 20   | 30  | 40     |
|----------------------|------------------------------------|--|---|--------|
| Valve specifications | Valve construction                 | Direct operated poppet   |   |        |
|                      | Valve type                         | Normally closed (N.C.)   |   |        |
|                      | Fluid and fluid temperature        | Air: -10 to 60 °C (Dew point temperature: -10 °C or less)  |   |        |
|                      | Withstand pressure                 | 2 MPa  |   |        |
|                      | Max. system pressure               | 1 MPa  |   |        |
|                      | Ambient temperature                | -20 to 60 °C   |   |        |
|                      | Valve leakage*1/External leakage*1 | Air  | 1 cm <sup>3</sup> /min (ANR) or less                        |        |
|                      | Mounting orientation               | Unrestricted   |   |        |
|                      | Enclosure*2                        | IP67 (IP65 for the DIN terminal)   |   |        |
|                      | Standards*3                        | CE   |   |        |
|                      | Operating environment              | Indoors, Location without the presence of corrosive gases, explosive gases, or constant fluid adhesion |   |        |
| Body material        | Aluminium                          |  |   |        |
| Seal material        | NBR, FKM                           |  |   |        |
| Coil specifications  | Rated voltage                      | AC   | 24 V, 48 V, 100 V, 110 V, 120 V, 200 V, 220 V, 230 V, 240 V |        |
|                      |                                    | DC   | 12 V, 24 V  |        |
|                      | Allowable voltage fluctuation      | ±10 % of rated voltage   |   |        |
|                      | Allowable leakage voltage          | AC   | 5 % or less of rated voltage                                |        |
|                      |                                    | DC   | 2 % or less of rated voltage                                |        |
|                      | Apparent power*4, *5               | AC   | 8 VA  | 9.5 VA |
| Power consumption*4  | DC                                 | 6 W  | 8 W   |        |
| Temperature rise*6   | AC/DC                              | 70/65 °C   |   |        |

\*1 The leakage amount value at a differential pressure of 0.01 MPa or higher and an ambient temperature of 20 °C

\*2 This product ensures IP67, but if water enters the product, it may result in operation failure or breakage.

Therefore, take appropriate measures to prevent water from entering the product when used in an environment where it is constantly exposed to water.

\*3 Conformance to standards varies depending on the model. For details, refer to page 30.

\*4 Power consumption/Apparent power: The value at an ambient temperature of 20 °C and when the rated voltage is applied (Variation: ±10 %)

\*5 There is no difference in the frequency and the inrush and energized apparent power, since a rectifying circuit is used in the AC.


\*6 Temperature rise: The value at an ambient temperature of 20 °C and when the rated voltage is applied. The value depends on the ambient environment. This is for reference.

**Be sure to read "Specific Product Precautions" before handling.**

## Construction

JSXM20, 30, 40, Normally closed (N.C.)

Body material: Aluminium




## Component Parts

| No. | Description       | Material                         |
|-----|-------------------|----------------------------------|
| 1   | Clip              | Stainless steel                  |
| 2   | Solenoid coil     | Stainless steel, Cu, Resin       |
| 3   | Stopper           | PPS                              |
| 4   | Spring            | Stainless steel                  |
| 5   | Tube assembly     | Stainless steel                  |
| 6   | Armature assembly | Stainless steel, PPS, NBR, (FKM) |
| 7   | Screw             | Fe                               |
| 8   | Bonnet            | Stainless steel                  |
| 9   | Gasket            | NBR, (FKM)                       |
| 10  | Body              | Aluminium                        |
| 11  | Plug              | Fe                               |
| 12  | Cover             | POM                              |


# JSXM Series

## Dimensions


### G: Grommet



### GS: Grommet with PCB



### CS: Conduit



[mm]


| Size | Port size     | A  | B  | C     | D  | E    | F  | G    |
|------|---------------|----|----|-------|----|------|----|------|
| 20   | 1/8, 1/4      | 42 | 40 | 77.6  | 36 | 17.5 | 18 | 15.5 |
| 30   | 1/4, 3/8      | 53 | 53 | 94.5  | 42 | 21.5 | 21 | 18   |
| 40   | 1/4, 3/8, 1/2 | 71 | 70 | 102.5 | 42 | 25.5 | 21 | 22.5 |

| Size | Port size     | Grommet |      | Grommet with PCB |    | Conduit |      |
|------|---------------|---------|------|------------------|----|---------|------|
|      |               | J       | K    | J                | K  | J       | K    |
| 20   | 1/8, 1/4      | 47.9    | 28.5 | 53.6             | 38 | 55.2    | 48.9 |
| 30   | 1/4, 3/8      | 56.8    | 31.1 | 62.5             | 41 | 64.1    | 51.9 |
| 40   | 1/4, 3/8, 1/2 | 64.8    | 31.1 | 70.5             | 41 | 72.1    | 51.9 |


## Dimensions

**DS: DIN terminal**  
**DS: DIN terminal with light**

**DN: DIN terminal without connector**



**WN: M12 connector**



[mm]

| Size | Port size     | A  | B  | C     | D  | E    | F  | G    |
|------|---------------|----|----|-------|----|------|----|------|
| 20   | 1/8, 1/4      | 42 | 40 | 77.6  | 36 | 17.5 | 18 | 15.5 |
| 30   | 1/4, 3/8      | 53 | 53 | 94.5  | 42 | 21.5 | 21 | 18   |
| 40   | 1/4, 3/8, 1/2 | 71 | 70 | 102.5 | 42 | 25.5 | 21 | 22.5 |

| Size | Port size     | DIN terminal |      |    | DIN terminal without connector |      | M12 connector |      |
|------|---------------|--------------|------|----|--------------------------------|------|---------------|------|
|      |               | J            | K    | L  | J                              | K    | J             | K    |
| 20   | 1/8, 1/4      | 56.7         | 55.3 | 67 | 56.7                           | 31.3 | 55.5          | 41.1 |
| 30   | 1/4, 3/8      | 65.6         | 58.3 | 70 | 65.6                           | 34.3 | 64.4          | 44.1 |
| 40   | 1/4, 3/8, 1/2 | 73.6         | 58.3 | 70 | 73.6                           | 34.3 | 72.4          | 44.1 |

# JSXM Series


## Modular Connection Examples (Dimensions)

Please note that products do not come assembled. They should be ordered separately and assembled by the customer.

For modular connection units (shipped assembled), the simple specials system can be used. For details, refer to page 3.

### Combination example ①


Air combination AC20B-02E-D ————— 1 pc.  
 Spacer with bracket Y200T-D ————— 1 pc.  
 Modular mounting type 2-port solenoid valve  
 JSXM21-AN301R-5G-U-F ————— 1 pc.



| Applicable air combination model | A    | B    | C     | D     |
|----------------------------------|------|------|-------|-------|
| AC20-D                           | 41.6 | 43.2 | 126.4 | 60.12 |
| AC30-D                           | 55.1 | 57.2 | 167.4 | 73.01 |
| AC40-D                           | 72.6 | 75.2 | 220.3 | 77.01 |

### Combination example ②

Modular mounting type 2-port solenoid valve  
 JSXM21-AN301R-5G-U ————— 4 pcs.  
 Spacer with bracket Y200T-D ————— 3 pcs.



| Series | Bracket mount dimensions |       |      |      |      |    |      |    |    |     |      |     |      |      |  |
|--------|--------------------------|-------|------|------|------|----|------|----|----|-----|------|-----|------|------|--|
|        | A                        | F     | L1   | L2   | L3   | M  | N    | Q1 | Q2 | R   | S    | U   | V1   | V2   |  |
| JSXM20 | 169.6                    | 41.6  | 9    | 20   | 43.2 | 30 | 43.2 | 24 | 33 | 5.5 | 11.5 | 3.5 | 29   | 38   |  |
| JSXM30 | 224.6                    | 55.1  | 14.5 | 26.4 | 57.2 | 41 | 57.2 | 35 | —  | 7   | 14   | 6   | 42.5 | 42.5 |  |
| JSXM40 | 295.3                    | 72.55 | 14.5 | 34.9 | 75.1 | 50 | 75.1 | 40 | 55 | 9   | 18   | 7   | 50   | 65   |  |

# JSXM Series

# Spacer / Spacer with Bracket

## Spacer / Spacer with Bracket

Y **300**    - D

①      ②

|   |         |             |                                |                 |                 |
|---|---------|-------------|--------------------------------|-----------------|-----------------|
|   | Symbol  | Description | ①                              |                 |                 |
|   |         |             | Body size<br>[Applicable size] |                 |                 |
|   |         |             | 200<br>[JSXM20]                | 300<br>[JSXM30] | 400<br>[JSXM40] |
| ② | Bracket | —           | ●                              | ●               | ●               |
|   |         | T           | ●                              | ●               | ●               |

Spacer  
(Y□-D)



Spacer with bracket  
(Y□T-D)



### Standard Specifications


|                                |                           |
|--------------------------------|---------------------------|
| Fluid                          | Air                       |
| Ambient and fluid temperatures | -5 to 60 °C (No freezing) |
| Proof pressure                 | 1.5 MPa                   |
| Max. operating pressure        | 1.0 MPa                   |

### Replacement Parts


| Description | Material | Part number       |                   |                   |
|-------------|----------|-------------------|-------------------|-------------------|
|             |          | Y200-D<br>Y200T-D | Y300-D<br>Y300T-D | Y400-D<br>Y400T-D |
| Seal        | HNBR     | Y220P-050S        | Y320P-050S        | Y420P-050S        |

### Dimensions

#### Spacer



#### Spacer with bracket



| Part no. | A   | B  | C    | D  | E   | Applicable size |
|----------|-----|----|------|----|-----|-----------------|
| Y200-D   | 3.2 | 35 | 13.2 | 42 | 0.6 | JSXM20          |
| Y300-D   | 4.2 | 43 | 16.2 | 53 | —   | JSXM30          |
| Y400-D   | 5.2 | 51 | 19.2 | 71 | —   | JSXM40          |

| Part no. | A   | B   | C    | D    | E  | EE | F    | G   | H    | J   | K  | Applicable size |
|----------|-----|-----|------|------|----|----|------|-----|------|-----|----|-----------------|
| Y200T-D  | 3.2 | 67  | 29   | 51   | 24 | 33 | 11.5 | 5.5 | 15.5 | 3.5 | 30 | JSXM20          |
| Y300T-D  | 4.2 | 85  | 42.5 | 67.5 | 35 | —  | 14   | 7   | 20   | 6   | 41 | JSXM30          |
| Y400T-D  | 5.2 | 115 | 50   | 85.5 | 40 | 55 | 18   | 9   | 26   | 7   | 50 | JSXM40          |

# JSX10, 20, 30 Series

## Table of UL-compliant Products

\* Refer to the table below for UL-compliant products.

**cUL<sup>®</sup> US Recognised**

**G** Grommet 

**GS** Grommet with PCB 

**DN** DIN terminal without connector 

| JSX11 | Series/Valve type | Body material | Seal material | Orifice diameter/Port size | Thread type | Rated voltage | Electrical entry | Option |
|-------|-------------------|---------------|---------------|----------------------------|-------------|---------------|------------------|--------|
|       | JSX11             |               | S             |                            | N           |               | R                |        |
|       |                   |               | F             | 101                        | N           | 1             | GS               |        |
|       |                   |               | E             | 201                        | F           | 2             | DN               |        |
|       |                   |               |               |                            |             | 3             |                  |        |
|       |                   |               |               |                            |             | 4             |                  |        |
|       |                   |               |               |                            |             | 5             |                  |        |
|       |                   |               |               |                            |             | 6             |                  |        |
|       |                   |               |               |                            |             | 7             |                  |        |
|       |                   |               |               |                            |             | 8             |                  |        |
|       |                   |               |               |                            |             | B             |                  |        |
|       |                   |               |               |                            |             | J             |                  |        |

| JSX21 | Series/Valve type | Body material | Seal material | Orifice diameter/Port size | Thread type | Rated voltage | Electrical entry | Option |
|-------|-------------------|---------------|---------------|----------------------------|-------------|---------------|------------------|--------|
|       | JSX21             |               | S             |                            | N           |               | R                |        |
|       |                   |               | F             | 301                        | N           | 1             | GS               |        |
|       |                   |               | E             | 302                        | F           | 2             | DN               |        |
|       |                   |               |               | 303                        |             | 3             |                  |        |
|       |                   |               |               | 402                        |             | 4             |                  |        |
|       |                   |               |               | 403                        |             | 5             |                  |        |
|       |                   |               |               | 502                        |             | 6             |                  |        |
|       |                   |               |               | 503                        |             | 7             |                  |        |
|       |                   |               |               | 702                        |             | 8             |                  |        |
|       |                   |               |               | 703                        |             | B             |                  |        |
|       |                   |               |               |                            |             | J             |                  |        |

| JSX31 | Series/Valve type | Body material | Seal material | Orifice diameter/Port size | Thread type | Rated voltage | Electrical entry | Option |
|-------|-------------------|---------------|---------------|----------------------------|-------------|---------------|------------------|--------|
|       | JSX31             |               | S             |                            | N           |               | R                |        |
|       |                   |               | F             | 402                        | N           | 1             | GS               |        |
|       |                   |               | E             | 403                        | F           | 2             | DN               |        |
|       |                   |               |               | 502                        |             | 3             |                  |        |
|       |                   |               |               | 503                        |             | 4             |                  |        |
|       |                   |               |               | 702                        |             | 5             |                  |        |
|       |                   |               |               | 703                        |             | 6             |                  |        |
|       |                   |               |               |                            |             | 7             |                  |        |
|       |                   |               |               |                            |             | 8             |                  |        |
|       |                   |               |               |                            |             | B             |                  |        |
|       |                   |               |               |                            |             | J             |                  |        |

\*1 Only applicable to rated voltage symbols "5" and "6"

**cUL<sup>®</sup> US LISTED Listed**

**CS** Conduit 

| JSX21 | Series/Valve type | Body material | Seal material | Orifice diameter/Port size | Thread type | Rated voltage | Electrical entry | Option |
|-------|-------------------|---------------|---------------|----------------------------|-------------|---------------|------------------|--------|
|       | JSX21             |               | S             |                            | N           |               | R                |        |
|       |                   |               | F             | 301                        | N           | 1             | CS               |        |
|       |                   |               | E             | 302                        | F           | 2             |                  |        |
|       |                   |               |               | 303                        |             | 3             |                  |        |
|       |                   |               |               | 402                        |             | 4             |                  |        |
|       |                   |               |               | 403                        |             | 5             |                  |        |
|       |                   |               |               | 502                        |             | 6             |                  |        |
|       |                   |               |               | 503                        |             | 7             |                  |        |
|       |                   |               |               | 702                        |             | 8             |                  |        |
|       |                   |               |               | 703                        |             | B             |                  |        |
|       |                   |               |               |                            |             | J             |                  |        |

| JSX31 | Series/Valve type | Body material | Seal material | Orifice diameter/Port size | Thread type | Rated voltage | Electrical entry | Option |
|-------|-------------------|---------------|---------------|----------------------------|-------------|---------------|------------------|--------|
|       | JSX31             |               | S             |                            | N           |               | R                |        |
|       |                   |               | F             | 402                        | N           | 1             | CS               |        |
|       |                   |               | E             | 403                        | F           | 2             |                  |        |
|       |                   |               |               | 502                        |             | 3             |                  |        |
|       |                   |               |               | 503                        |             | 4             |                  |        |
|       |                   |               |               | 702                        |             | 5             |                  |        |
|       |                   |               |               | 703                        |             | 6             |                  |        |
|       |                   |               |               |                            |             | 7             |                  |        |
|       |                   |               |               |                            |             | 8             |                  |        |
|       |                   |               |               |                            |             | B             |                  |        |
|       |                   |               |               |                            |             | J             |                  |        |

# JSXD30, 40, 50, 60, 70, 80, 90 Series

## Table of UL-compliant Products

\* Refer to the table below for UL-compliant products.



Recognised

G\*1  
Grommet



GS  
Grommet  
with PCB



DN  
Without DIN  
connector



\*1 Only applicable to rated  
voltage symbols "5" and "6"

| Series/<br>Valve type | Body<br>material | Seal<br>material | Port size | Thread<br>type | Rated<br>voltage | Electrical<br>entry | Oil-free<br>option | Bracket<br>option |
|-----------------------|------------------|------------------|-----------|----------------|------------------|---------------------|--------------------|-------------------|
| <b>JSXD31</b>         | C                | N                | 02        | R              | 1                | G                   | None               | None              |
|                       | S                | F                | 03        | N              | 2                | GS                  | D                  | B                 |
|                       | A                | E*3              | 04        | F              | 3                | DN                  |                    |                   |
|                       |                  |                  |           |                | 4                |                     |                    |                   |
|                       |                  |                  |           |                | 5                |                     |                    |                   |
|                       |                  |                  |           |                | 6                |                     |                    |                   |
|                       |                  |                  |           |                | 7                |                     |                    |                   |
|                       |                  |                  |           |                | 8                |                     |                    |                   |
|                       |                  |                  |           |                | B                |                     |                    |                   |
|                       |                  |                  |           |                | J                |                     |                    |                   |
| <b>JSXD41</b>         | C                | N                | 03        | R              | 1                | G                   | None               | None              |
|                       | S                | F                | 04        | N              | 2                | GS                  | D                  | B                 |
|                       |                  | E                |           | F              | 3                | DN                  |                    |                   |
|                       |                  |                  |           |                | 4                |                     |                    |                   |
|                       |                  |                  |           |                | 5                |                     |                    |                   |
|                       |                  |                  |           |                | 6                |                     |                    |                   |
|                       |                  |                  |           |                | 7                |                     |                    |                   |
|                       |                  |                  |           |                | 8                |                     |                    |                   |
|                       |                  |                  |           |                | B                |                     |                    |                   |
|                       |                  |                  |           |                | J                |                     |                    |                   |
| <b>JSXD51</b>         | C                | N                | 06        | R              | 1                | G                   | None               | None              |
|                       | S                | F                |           | N              | 2                | GS                  | D                  | B                 |
|                       |                  | E                |           | F              | 3                | DN                  |                    |                   |
|                       |                  |                  |           |                | 4                |                     |                    |                   |
|                       |                  |                  |           |                | 5                |                     |                    |                   |
|                       |                  |                  |           |                | 6                |                     |                    |                   |
|                       |                  |                  |           |                | 7                |                     |                    |                   |
|                       |                  |                  |           |                | 8                |                     |                    |                   |
|                       |                  |                  |           |                | B                |                     |                    |                   |
|                       |                  |                  |           |                | J                |                     |                    |                   |
| <b>JSXD61</b>         | C                | N                | 10        | R              | 1                | G                   | None               | None              |
|                       | S                | F                |           | N              | 2                | GS                  | D                  | B                 |
|                       |                  | E                |           | F              | 3                | DN                  |                    |                   |
|                       |                  |                  |           |                | 4                |                     |                    |                   |
|                       |                  |                  |           |                | 5                |                     |                    |                   |
|                       |                  |                  |           |                | 6                |                     |                    |                   |
|                       |                  |                  |           |                | 7                |                     |                    |                   |
|                       |                  |                  |           |                | 8                |                     |                    |                   |
|                       |                  |                  |           |                | B                |                     |                    |                   |
|                       |                  |                  |           |                | J                |                     |                    |                   |
| <b>JSXD71</b>         | B                | N                | 12        | R              | 1                | G                   | None               |                   |
|                       |                  | F                |           | N              | 2                | GS                  | D                  |                   |
|                       |                  | E                |           | F              | 3                | DN                  |                    |                   |
|                       |                  |                  |           |                | 4                |                     |                    |                   |
|                       |                  |                  |           |                | 5                |                     |                    |                   |
|                       |                  |                  |           |                | 6                |                     |                    |                   |
|                       |                  |                  |           |                | 7                |                     |                    |                   |
|                       |                  |                  |           |                | 8                |                     |                    |                   |
|                       |                  |                  |           |                | B                |                     |                    |                   |
|                       |                  |                  |           |                | J                |                     |                    |                   |

\*3 Cannot be used in combination with body material A

# JSXD30, 40, 50, 60, 70, 80, 90 Series

## Table of UL-compliant Products

\* Refer to the table below for UL-compliant products.



Recognised

G\*1  
Grommet



GS  
Grommet  
with PCB



DN  
Without DIN  
connector



\*1 Only applicable to rated  
voltage symbols "5" and "6"

| JSXD81 | Series/<br>Valve type | Body<br>material | Seal<br>material | Port size | Thread<br>type | Rated<br>voltage | Electrical<br>entry | Oil-free<br>option |
|--------|-----------------------|------------------|------------------|-----------|----------------|------------------|---------------------|--------------------|
|        | JSXD81                | B                | N                | 14        | R              | 1                | G                   | None               |
|        |                       | F                |                  | N         | 2              | GS               | D                   |                    |
|        |                       | E                |                  | F         | 3              | DN               |                     |                    |
|        |                       |                  |                  |           | 4              |                  |                     |                    |
|        |                       |                  |                  |           | 5              |                  |                     |                    |
|        |                       |                  |                  |           | 6              |                  |                     |                    |
|        |                       |                  |                  |           | 7              |                  |                     |                    |
|        |                       |                  |                  |           | 8              |                  |                     |                    |
|        |                       |                  |                  |           | B              |                  |                     |                    |
|        |                       |                  |                  |           | J              |                  |                     |                    |

| JSXD91 | Series/<br>Valve type | Body<br>material | Seal<br>material | Port size | Thread<br>type | Rated<br>voltage | Electrical<br>entry | Oil-free<br>option |
|--------|-----------------------|------------------|------------------|-----------|----------------|------------------|---------------------|--------------------|
|        | JSXD91                | B                | N                | 20        | R              | 1                | G                   | None               |
|        |                       | F                |                  | N         | 2              | GS               | D                   |                    |
|        |                       | E                |                  | F         | 3              | DN               |                     |                    |
|        |                       |                  |                  |           | 4              |                  |                     |                    |
|        |                       |                  |                  |           | 5              |                  |                     |                    |
|        |                       |                  |                  |           | 6              |                  |                     |                    |
|        |                       |                  |                  |           | 7              |                  |                     |                    |
|        |                       |                  |                  |           | 8              |                  |                     |                    |
|        |                       |                  |                  |           | B              |                  |                     |                    |
|        |                       |                  |                  |           | J              |                  |                     |                    |

# Table of UL-compliant Products *JSXD Series*



Listed

C\*1  
Conduit



| Series/<br>Valve type | Body material | Seal material | Port size | Thread type | Rated voltage | Electrical entry | Oil-free option | Bracket option |                       |
|-----------------------|---------------|---------------|-----------|-------------|---------------|------------------|-----------------|----------------|-----------------------|
|                       |               |               |           |             |               |                  |                 |                | Series/<br>Valve type |
| <b>JSXD31</b>         | <b>JSXD31</b> | <b>C</b>      | <b>N</b>  | <b>02</b>   | <b>R</b>      | <b>1</b>         | <b>CS</b>       | <b>None</b>    | <b>None</b>           |
|                       |               | <b>S</b>      | <b>F</b>  | <b>03</b>   | <b>N</b>      | <b>2</b>         |                 | <b>D</b>       | <b>B</b>              |
|                       |               | <b>A</b>      | <b>E</b>  | <b>04</b>   | <b>F</b>      | <b>3</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>4</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>5</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>6</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>7</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>8</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>B</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>J</b>         |                 |                |                       |
| <b>JSXD41</b>         | <b>JSXD41</b> | <b>C</b>      | <b>N</b>  | <b>03</b>   | <b>R</b>      | <b>1</b>         | <b>CS</b>       | <b>None</b>    | <b>None</b>           |
|                       |               | <b>S</b>      | <b>F</b>  | <b>04</b>   | <b>N</b>      | <b>2</b>         |                 | <b>D</b>       | <b>B</b>              |
|                       |               |               | <b>E</b>  |             | <b>F</b>      | <b>3</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>4</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>5</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>6</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>7</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>8</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>B</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>J</b>         |                 |                |                       |
| <b>JSXD51</b>         | <b>JSXD51</b> | <b>C</b>      | <b>N</b>  | <b>06</b>   | <b>R</b>      | <b>1</b>         | <b>CS</b>       | <b>None</b>    | <b>None</b>           |
|                       |               | <b>S</b>      | <b>F</b>  |             | <b>N</b>      | <b>2</b>         |                 | <b>D</b>       | <b>B</b>              |
|                       |               |               | <b>E</b>  |             | <b>F</b>      | <b>3</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>4</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>5</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>6</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>7</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>8</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>B</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>J</b>         |                 |                |                       |
| <b>JSXD61</b>         | <b>JSXD61</b> | <b>C</b>      | <b>N</b>  | <b>10</b>   | <b>R</b>      | <b>1</b>         | <b>CS</b>       | <b>None</b>    | <b>None</b>           |
|                       |               | <b>S</b>      | <b>F</b>  |             | <b>N</b>      | <b>2</b>         |                 | <b>D</b>       | <b>B</b>              |
|                       |               |               | <b>E</b>  |             | <b>F</b>      | <b>3</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>4</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>5</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>6</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>7</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>8</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>B</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>J</b>         |                 |                |                       |
| <b>JSXD71</b>         | <b>JSXD71</b> | <b>B</b>      | <b>N</b>  | <b>12</b>   | <b>R</b>      | <b>1</b>         | <b>CS</b>       | <b>None</b>    |                       |
|                       |               |               | <b>F</b>  |             | <b>N</b>      | <b>2</b>         |                 | <b>D</b>       |                       |
|                       |               |               | <b>E</b>  |             | <b>F</b>      | <b>3</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>4</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>5</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>6</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>7</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>8</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>B</b>         |                 |                |                       |
|                       |               |               |           |             |               | <b>J</b>         |                 |                |                       |

# JSXD30, 40, 50, 60, 70, 80, 90 Series

## Table of UL-compliant Products

\* Refer to the table below for UL-compliant products.



Listed

C\*1  
Conduit



| Series/<br>Valve type | Body material | Seal material | Port size | Thread type | Rated voltage | Electrical entry | Oil-free option |
|-----------------------|---------------|---------------|-----------|-------------|---------------|------------------|-----------------|
|                       |               |               |           |             |               |                  |                 |
| JSXD81                | B             | N             | 14        | R           | 1             | CS               | None            |
|                       |               | F             |           | N           | 2             |                  | D               |
|                       |               | E             |           | F           | 3             |                  |                 |
|                       |               |               |           |             | 4             |                  |                 |
|                       |               |               |           |             | 5             |                  |                 |
|                       |               |               |           |             | 6             |                  |                 |
|                       |               |               |           |             | 7             |                  |                 |
|                       |               |               |           |             | 8             |                  |                 |
|                       |               |               |           |             | B             |                  |                 |
|                       |               |               |           |             | J             |                  |                 |
| JSXD91                | B             | N             | 20        | R           | 1             | CS               | None            |
|                       |               | F             |           | N           | 2             |                  | D               |
|                       |               | E             |           | F           | 3             |                  |                 |
|                       |               |               |           |             | 4             |                  |                 |
|                       |               |               |           |             | 5             |                  |                 |
|                       |               |               |           |             | 6             |                  |                 |
|                       |               |               |           |             | 7             |                  |                 |
|                       |               |               |           |             | 8             |                  |                 |
|                       |               |               |           |             | B             |                  |                 |
|                       |               |               |           |             | J             |                  |                 |

# JSX/JSX□ Series Option

## Cable for M12 Connector (Female Connector with Cable)

The solenoid valve does not come with a cable for the M12 connector.  
Please order it separately if necessary.

**JSX022-30-1-1**

● Specification


|   |                 |
|---|-----------------|
| 1 | For DC voltages |
| 2 | For AC voltages |

● Cable length L [mm]


|   |      |
|---|------|
| 1 | 1000 |
| 2 | 2000 |
| 5 | 5000 |

## Specifications


| Part number                             |                             | JSX022-30-1-□                    | JSX022-30-2-□ |
|---|-----------------------------|----------------------------------|---------------|
| Key type                                |                             | A-coded                          | B-coded       |
| Rating/Performance                      | Rated current               | 4 A                              |               |
|   | Rated voltage               | 250 V                            |               |
|   | Contact resistance          | 40 mΩ or less                    |               |
|   | Insulation resistance       | 1000 MΩ or more                  |               |
|   | Withstand voltage           | 1500 VAC                         |               |
|   | Operating temperature range | -25 to 70 °C                     |               |
|   | Min. bending radius (Fixed) | 50 mm                            |               |
|   | Protection class            | IP67 (Only with screw tightened) |               |
| Allowable repeated insertion/withdrawal |                             | 200                              |               |
| Material                                | Material of knurl           | Brass (Ni plating)               |               |
|   | Contact (Surface treatment) | Copper alloy (Au plating)        |               |
|   | Connector material          | PBT                              |               |
|   | Cover                       | Soft PBT                         |               |



**For DC voltages  
(A-coded)**




**Socket connector  
pin arrangement**




**Connections**

**For AC voltages  
(B-coded)**



**Socket connector  
pin arrangement**



**Connections**

\* The solenoid valve has no polarity for DC voltages.


# JSX/JSX□ Series Replacement Parts

## Solenoid Coil Assembly (Applicable to the JSX, JSXD, and JSXM series)

---

When ordering, be sure to add the “-KT1” suffix to the end of the part number of the valve currently in use.

**JSX 2 1 - S N 101 R - 5 G - B - KT1**



● **Enter the standard product number.**

JSX (Stainless steel/Brass) ..... p. 5

JSX (Aluminium) ..... p. 7

JSXD ..... p. 21

JSXM ..... p. 30

The solenoid coil assembly is shipped with a name plate with the valve part number printed on it. In addition, the name plate has the marks of all applicable standards printed on it.

For the solenoid coil assembly, eligibility for CE marking and UL/CSA standard certification varies depending on the electrical entry type and the rated voltage.

When ordering a solenoid coil assembly with different specifications than the valve currently in use, refer to “How to Order” in the catalog to confirm the status of standard compliance.

For solenoid coil replacement instructions, refer to “Specific Product Precautions 8” on page 53-1.

## Glossary of Terms

### Pressure Terminology

#### 1. Max. operating pressure differential

The max. pressure differential (the difference between the inlet and outlet pressure) which is allowed for operation. When the outlet pressure is 0 MPa, this becomes the max. operating pressure.

#### 2. Min. operating pressure differential

The min. pressure differential (the difference between the inlet pressure and outlet pressure) required to keep the main valve fully open.

#### 3. Max. system pressure

The max. pressure that can be applied inside the pipelines (line pressure).

[The pressure differential of the solenoid valve portion must not exceed the max. operating pressure differential.]

#### 4. Withstand pressure

The pressure in which the valve must be withstood without a drop in performance after holding for one minute under prescribed pressure and returning to the operating pressure range. (value under the prescribed conditions)

### Electrical Terminology

#### 1. Apparent power (VA)

Volt-ampere is the product of voltage (V) and current (A).

Power consumption (W): For AC,  $W = V \cdot A \cdot \cos \theta$ .

For DC,  $W = V \cdot A$ .

\*  $\cos \theta$  shows power factor.  $\cos \theta \approx 0.9$

#### 2. Surge voltage

A high voltage which is momentarily generated by shutting off the power in the shut-off area.

#### 3. Degrees of protection

A degree defined in the "JIS C 0920: Waterproof test of electric machinery/appliance and the degree of protection against the intrusion of solid foreign objects."

IP -

First digit      Second digit

##### ● First Digit:

##### Degree of protection against solid foreign objects

|   |   |
|---|---|
| 0 | Not protected   |
| 1 | Protected against solid foreign objects of 50 mmØ and larger  |
| 2 | Protected against solid foreign objects of 12 mmØ and larger  |
| 3 | Protected against solid foreign objects of 2.5 mmØ and larger |
| 4 | Protected against solid foreign objects of 1.0 mmØ and larger |
| 5 | Dust protected  |
| 6 | Dust-tight  |

##### ● Second Digit:

##### Degree of protection against water

|   |  |                               |
|---|--|-------------------------------|
| 0 | Not protected  | —                             |
| 1 | Protected against vertically falling water droplets                                    | Dripproof type 1              |
| 2 | Protected against vertically falling water droplets when enclosure is tilted up to 15° | Dripproof type 2              |
| 3 | Protected against rainfall when enclosure is tilted up to 60°                          | Rainproof type                |
| 4 | Protected against splashing water  | Splashproof type              |
| 5 | Protected against water jets   | Water-jet-proof type          |
| 6 | Protected against powerful water jets  | Powerful water-jet-proof type |
| 7 | Protected against the effects of temporary immersion in water                          | Immersible type               |
| 8 | Protected against the effects of continuous immersion in water                         | Submersible type              |

### Others

#### 1. Material

NBR: Nitrile rubber

FKM: Fluororubber

EPDM: Ethylene propylene rubber

#### 2. Symbol

In the symbol ()<sub>(M)</sub>, when the valve is closed, flow is blocked from port 1 to port 2. However, if the pressure in port 2 is higher than port 1, the valve will not be able to block the fluid and it will flow from port 2 to port 1.

# Solenoid Valve Flow Rate Characteristics

## (How to indicate flow rate characteristics)

### 1. Indication of flow rate characteristics

The flow rate characteristics of equipment, such as a solenoid valve, etc., are indicated in their specifications as shown in Table (1).

Table (1) Indication of Flow Rate Characteristics

| Corresponding equipment         | Indication by international standard | Other indications | Compliant standards   |
|---------------------------------|--------------------------------------|-------------------|---|
| Pneumatic equipment             | <b>C, b</b>                          | —                 | ISO 6358:1989<br>JIS B 8390:2000                            |
|                                 | —                                    | <b>S</b>          | JIS B 8390:2000<br>Equipment: JIS B 8379, 8381-1, 8381-2    |
|                                 |                                      | <b>Cv</b>         | ANSI/(NFPA)T3.21.3 R1-2008                                  |
| Process fluid control equipment | <b>Kv</b>                            | —                 | IEC 60534-1:2005<br>IEC 60534-2-3:1997<br>JIS B 2005-1:2012 |
|                                 | —                                    | <b>Cv</b>         | JIS B 2005-2-3:2004<br>Equipment: JIS B 8471, 8472, 8473    |

### 2. Pneumatic equipment

#### 2.1 Indication according to the international standards

##### (1) Compliant standards

**ISO 6358:1989 : Pneumatic fluid power—Components using compressible fluids—Determination of flow rate characteristics**

**JIS B 8390:2000 : Pneumatic fluid power—Components using compressible fluids—How to test flow rate characteristics**

##### (2) Definition of flow rate characteristics

The flow rate characteristics are indicated as a result of a comparison between the sonic conductance **C** and the critical pressure ratio **b**.

**Sonic conductance C** : Value which divides the passing mass flow rate of a piece of equipment in a choked flow condition by the product of the upstream absolute pressure and the density in a standard condition.

**Critical pressure ratio b** : Pressure ratio (downstream pressure/upstream pressure) which will turn to a choked flow when the value is smaller than this ratio.

**Choked flow** : Flow in which the upstream pressure is higher than the downstream pressure and where sonic speed in a certain part of a piece of equipment is reached.

Gaseous mass flow rate is in proportion to the upstream pressure and not dependent on the downstream pressure.

**Subsonic flow** : Flow greater than the critical pressure ratio.

**Standard condition** : Air in a temperature state of 20 °C, absolute pressure 0.1 MPa (= 100 kPa = 1 bar), relative humidity 65 %.

It is stipulated by adding the “(ANR)” after the unit depicting air volume. (Standard reference atmosphere)

Compliant standards: ISO 8778:1990 Pneumatic fluid power—Standard reference atmosphere, JIS B 8393:2000: Pneumatic fluid power—Standard reference atmosphere

##### (3) Formula for flow rate

It is described by the practical units as following.

When

$$\frac{P_2 + 0.1}{P_1 + 0.1} \leq b, \text{ choked flow}$$

$$Q = 600 \times C (P_1 + 0.1) \sqrt{\frac{293}{273 + T}} \dots\dots\dots(1)$$

When

$$\frac{P_2 + 0.1}{P_1 + 0.1} > b, \text{ subsonic flow}$$

$$Q = 600 \times C (P_1 + 0.1) \sqrt{1 - \left[ \frac{P_2 + 0.1}{P_1 + 0.1} - b \right]^2} \sqrt{\frac{293}{273 + T}} \dots\dots\dots(2)$$

**Q** : Air flow rate [l/min (ANR)]

**C** : Sonic conductance [ $\text{dm}^3/(\text{s}\cdot\text{bar})$ ],  $\text{dm}^3$  (Cubic decimeter) of SI units = L (litre)

**b** : Critical pressure ratio [—]

**P<sub>1</sub>** : Upstream pressure [MPa]

**P<sub>2</sub>** : Downstream pressure [MPa]

**T** : Temperature [ $^{\circ}\text{C}$ ]

\* Formula of subsonic flow is the elliptic analogous curve.

Flow rate characteristics are shown in Graph (1). For details, please use the calculation software available from the SMC website.


Example)

Obtain the air flow rate for **P<sub>1</sub>** = 0.4 [MPa], **P<sub>2</sub>** = 0.3 [MPa], **T** = 20 [ $^{\circ}\text{C}$ ] when a solenoid valve is performed in **C** = 2 [ $\text{dm}^3/(\text{s}\cdot\text{bar})$ ] and **b** = 0.3.

According to formula 1, the max. flow rate =  $600 \times 2 \times (0.4 + 0.1) \times \sqrt{\frac{293}{273 + 20}} = 600$  [l/min (ANR)]

$$\text{Pressure ratio} = \frac{0.3 + 0.1}{0.4 + 0.1} = 0.8$$


Based on Graph (1), it will be 0.7 if the pressure ratio is 0.8 and the flow rate ratio is **b** = 0.3.  
Hence, the flow rate = Max. flow x flow ratio =  $600 \times 0.7 = 420$  [l/min (ANR)]



**Graph (1) Flow rate characteristics**

#### (4) Test method

Connect the piece of test equipment to the test circuit as shown in Fig. (1). While maintaining the upstream pressure at a fixed value above 0.3 MPa, measure the max. flow to be saturated initially. Next, measure this flow rate at 80 %, 60 %, 40 %, and 20 %, as well as the upstream and downstream pressure. The sonic conductance **C** can be calculated based on this max. flow rate. Use the data of the others and the subsonic flow formula to find **b**, and calculate the critical pressure ratio **b** from that average.



**Fig. (1) Test circuit based on ISO 6358:1989, JIS B 8390:2000**

**2.2 Effective area S**

(1) Compliant standards

**JIS B 8390:2000: Pneumatic fluid power—Components using compressible fluids—  
How to test flow rate characteristics**

Equipment standards: **JIS B 8373: Solenoid valve for pneumatics**

**JIS B 8379: Silencer for pneumatics**

**JIS B 8381-1: Fittings for pneumatics—Part 1: Push-in fittings for thermoplastic resin tubing**

**JIS B 8381-2: Fittings for pneumatics—Part 2: Compression fittings for thermoplastic resin tubing**

(2) Definition of flow rate characteristics

Effective area **S**: Cross-sectional area that has an ideal throttle without friction or reduced flow. The value is derived by calculating pressure changes inside of an air tank when the compressed air is discharged from a piece of equipment mounted on the tank in a choked flow. The value of the effective area **S**, like that of sonic conductance **C**, expresses the “ease of flow.”

(3) Formula for flow rate

When

$$\frac{P_2 + 0.1}{P_1 + 0.1} \leq 0.5, \text{ choked flow}$$

$$Q = 120 \times S (P_1 + 0.1) \sqrt{\frac{293}{273 + T}} \dots\dots\dots(3)$$

When

$$\frac{P_2 + 0.1}{P_1 + 0.1} > 0.5, \text{ subsonic flow}$$

$$Q = 240 \times S \sqrt{(P_2 + 0.1) (P_1 - P_2)} \sqrt{\frac{293}{273 + T}} \dots\dots\dots(4)$$

Conversion with sonic conductance **C**:

$$S = 5.0 \times C \dots\dots\dots(5)$$

**Q** : Air flow rate [l/min (ANR)]

**S** : Effective area [mm<sup>2</sup>]

**P<sub>1</sub>** : Upstream pressure [MPa]

**P<sub>2</sub>** : Downstream pressure [MPa]

**T** : Temperature [°C]

\* The formula for subsonic flow (4) is only applicable when the critical pressure ratio **b** is the unknown piece of equipment. In the sonic conductance **C** formula (2), it is the same formula as when **b** = 0.5.

(4) Test method

Connect the piece of test equipment to the test circuit as shown in Fig. (2). Discharge the air from the air tank filled with compressed air at a fixed value above 0.6 MPa (0.5 MPa) into the atmosphere until the pressure inside the tank falls to 0.25 MPa (0.2 MPa). Measure the discharge time and the residual pressure inside the tank after discharging until it has returned to the normal value. Then, calculate the effective area **S** using the following formula. Select an air tank with a volume within the specified range of the test equipment’s effective area. For JIS B 8379, the pressure values are in parentheses and the coefficient of the formula is 12.9.

$$S = 12.1 \frac{V}{t} \log_{10} \left( \frac{P_s + 0.1}{P + 0.1} \right) \sqrt{\frac{293}{T}} \dots\dots\dots(6)$$

**S** : Effective area [mm<sup>2</sup>]


**V** : Air tank capacity [L]

**t** : Discharging time [s]

**P<sub>s</sub>** : Pressure inside air tank before discharging [MPa]

**P** : Residual pressure inside air tank after discharging [MPa]

**T** : Temperature inside air tank before discharging [K]



**Fig. (2) Test circuit based on JIS B 8390:2000**

## 2.3 Flow coefficient $C_v$ factor

The United States Standard ANSI/(NFPA)T3.21.3:R1-2008R: Pneumatic fluid power—Flow rating test procedure and reporting method for fixed orifice components

This standard defines the  $C_v$  factor of the flow coefficient by the following formula that is based on the test conducted by the test circuit analogous to ISO 6358.

$$C_v = \frac{Q}{114.5 \sqrt{\frac{\Delta P (P_2 + P_a)}{T_1}}} \dots\dots\dots (7)$$

$\Delta P$  : Pressure drop between the static pressure tapping ports [bar]

$P_1$  : Pressure of the upstream tapping port [bar gauge]

$P_2$  : Pressure of the downstream tapping port [bar gauge]:  $P_2 = P_1 - \Delta P$

$Q$  : Flow rate [L/s standard condition]

$P_a$  : Atmospheric pressure [bar absolute]

$T_1$  : Upstream absolute temperature [K]

The test conditions are  $P_1 + P_a = 6.5 \pm 0.2$  bar absolute,  $T_1 = 297 \pm 5K$ ,  $0.07 \text{ bar} \leq \Delta P \leq 0.14 \text{ bar}$ .

This is the same concept as the effective area  $A$  which ISO 6358 stipulates as being applicable only when the pressure drop is smaller than the upstream pressure and the compression of air does not become a problem.

## 3. Process fluid control equipment

### (1) Compliant standards

**IEC 60534-1:2005: Industrial-process control valves. Part 1: Control valve terminology and general considerations**

**IEC 60534-2-3:1997: Industrial-process control valves. Part 2: Flow capacity, Section Three- Test procedures**

**JIS B 2005-1:2012: Industrial-process control valves – Part 1: Control valve terminology and general considerations**

**JIS B 2005-2-3:2004: Industrial-process control valves – Part 2: Flow capacity – Section 3: Test procedures**

**Equipment standards: JIS B 8471: Solenoid valve for water**

**JIS B 8472: Solenoid valve for steam**

**JIS B 8473: Solenoid valve for fuel oil**

### (2) Definition of flow rate characteristics

**$K_v$  factor:** Value of the clean water flow rate (represented by  $m^3/h$ ) which runs through a valve (test equipment) at 5 to 40 °C when the pressure difference is  $1 \times 10^5$  Pa (1 bar). It is calculated using the following formula.

$$K_v = Q \sqrt{\frac{1 \times 10^5}{\Delta P} \cdot \frac{\rho}{1000}} \dots\dots\dots (8)$$

$K_v$  : Flow coefficient [ $m^3/h$ ]

$Q$  : Flow rate [ $m^3/h$ ]

$\Delta P$  : Pressure difference [Pa]

$\rho$  : Density of fluid [ $kg/m^3$ ]

### (3) Formula of flow rate

It is described by practical units. Also, the flow rate characteristics are shown in Graph (2).

In the case of liquids:

$$Q = 53 K_v \sqrt{\frac{\Delta P}{G}} \dots\dots\dots (9)$$

$Q$  : Flow rate [l/min]

$K_v$  : Flow coefficient [ $m^3/h$ ]

$\Delta P$  : Pressure difference [MPa]

$G$  : Relative density [water = 1]

In the case of saturated aqueous vapour:

$$Q = 232 K_v \sqrt{\Delta P (P_2 + 0.1)} \dots\dots\dots (10)$$

$Q$  : Flow rate [kg/h]

$K_v$  : Flow coefficient [ $m^3/h$ ]

$\Delta P$  : Pressure difference [MPa]

$P_1$  : Upstream pressure [MPa]:  $\Delta P = P_1 - P_2$

$P_2$  : Downstream pressure [MPa]

Conversion of flow coefficient:

$$Kv = 0.865 Cv \dots\dots\dots(11)$$


Here,

**Cv** factor: Value of the clean water flow rate (represented by US gal/min) which runs through a valve at 40 to 100°F when the pressure difference is 1 lbf/in<sup>2</sup> (psi)


The values of **Kv** and **Cv** factors for pneumatic purposes are different due to different test methods.

(4) Test method

Connect the piece of test equipment to the test circuit as shown in Fig. (3), and run water at 5 to 40 °C. Then, measure the flow rate with a pressure difference where vapourization does not occur in a turbulent flow (pressure difference of 0.035 MPa to 0.075 MPa when the inlet pressure is within 0.15 MPa to 0.6 MPa). However, as the turbulent flow is definitely caused, the pressure difference needs to be set with a large enough difference so that the Reynolds number does not fall below  $1 \times 10^5$ , and the inlet pressure needs to be set slightly higher to prevent vapourization of the liquid. Substitute the measurement results in formula (8) to calculate **Kv**.



**Fig. (3) Test circuit based on IEC 60534-2-3, JIS B 2005-2-3**



**Graph (2) Flow rate characteristics**

Example 1)

Obtain the pressure difference when 15 [l/min] of water runs through a solenoid valve with a **Kv** = 1.5 [m<sup>3</sup>/h]. As the flow rate when **Kv** = 1 is calculated as the formula:  $Q_0 = 15 \times 1/1.5 = 10$  [l/min], read off  $\Delta P$  when  $Q_0$  is 10 [l/min] in Graph (2). The reading is 0.036 [MPa].

Example 2)


Obtain the saturated steam flow rate when  $P_1 = 0.8$  [MPa] and  $\Delta P = 0.008$  [MPa] with a solenoid valve with a **Kv** = 0.05 [m<sup>3</sup>/h]. Read off  $Q_0$  when  $P_1$  is 0.8 and  $\Delta P$  is 0.008 in Graph (2), the reading is 20 [kg/h]. Therefore, the flow rate is calculated as the formula:  $Q = 0.05/1 \times 20 = 1$  [kg/h].

# JSXD Series

# Flow Rate Characteristics

\* Use this graph as a guide. In the case of obtaining an accurate flow rate, refer to pages 40 to 44.

For Air (Orifice diameter:  $\varnothing$  10 mm,  $\varnothing$  15 mm,  $\varnothing$  20 mm,  $\varnothing$  25 mm)




## How to read the graph

The sonic range pressure to generate a flow rate of 6000 l/min (ANR) is as follows.  
 For a  $\varnothing$  15 orifice (JSXD40/Port size 3/8),  $P_1 \approx 0.57$  MPa,  
 for a  $\varnothing$  20 orifice (JSXD50/Port size 3/4),  $P_1 \approx 0.22$  MPa


## Warning

In the area located left to the min. operating pressure differential origin line in the flow rate characteristics table, the min. operating pressure is not generated. Do not use the product in this area as this may cause operation failure (valve opening failure, valve closing failure) or damage of the valve. Select valves with suitable size.

For Air (Orifice diameter:  $\varnothing$  35 mm,  $\varnothing$  40 mm,  $\varnothing$  50 mm)



## For Water



## How to read the graph

The pressure differential to generate a flow rate of 100 l/min water is as follows.  
 For a Ø 15 orifice (JSXD40/Port size 1/2),  $\Delta P \approx 0.16$  MPa,  
 for a Ø 20 orifice (JSXD50),  $\Delta P \approx 0.055$  MPa,  
 for a Ø 25 orifice (JSXD60),  $\Delta P \approx 0.032$  MPa



# JSX/JSX□ Series Specific Product Precautions 1

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

## Design

### ⚠ Warning

#### 1. Confirm the specifications.

Give careful consideration to the operating conditions, such as the application, fluid, and environment, and use within the specified operating ranges. If the product is used beyond the specification range, this may cause the product to break or malfunction. We do not guarantee against any damage if the product is used outside of the specification range.

#### 2. Cannot be used as an emergency shutoff valve, etc.

This product is not designed for safety applications such as an emergency shutoff valve. If the valves are used in this type of system, other reliable safety assurance measures should also be adopted.

#### 3. Cannot be used for pressure (including vacuum) holding

It is not usable for an application such as holding the pressure (including vacuum) inside of a pressure vessel because air leakage is entailed in valves.

#### 4. Closed liquid circuit

In a closed circuit, when liquid is static, pressure could rise due to changes in temperature. This pressure rise could cause malfunction and damage to components such as valves. To prevent this, install a relief valve in the system.

#### 5. Actuator drive

When an actuator, such as a cylinder, is to be driven using a valve, take appropriate measures to prevent potential danger caused by actuator operation.

#### 6. Extended periods of continuous energization

The solenoid coil will generate heat when continuously energized. Avoid using in a tightly shut container. Install the valve in a well-ventilated area. Furthermore, do not touch it while it is being energized or right after it has been energized.

#### 7. Water hammer

When an impact, such as water hammer, etc., caused by rapid pressure fluctuation is applied, the valve may be damaged. Install water hammer relief equipment (accumulator, etc.) or use an SMC water hammer relief valve (VXR series). Please contact SMC for details.

#### 8. Reverse pressure

If there is a possibility that reverse pressure will be applied, take countermeasures by installing a check valve, etc., on the downstream side.

#### 9. Do not disassemble the product and replacement parts or make any modifications, including additional machining.

Doing so may cause human injury and/or an accident.

## Operating Environment

### ⚠ Warning

Do not use the product in such locations as those described below.

#### 1. Locations with atmospheres where water vapour is present or locations where corrosive fluids (chemicals), sea water, or water may come into contact with the product

Implement appropriate protective measures if water will be applied to the product for long periods of time, even for products which have IP65 or IP67 enclosures. Such water may enter through microscopic gaps in the product's external surfaces, resulting in fire damage or short-circuiting of the solenoid valve coils. If installing the product in close proximity to equipment, such as machine tools, processing machines, etc., which uses large amounts of liquids or oils, be sure to confirm that liquid dispersal or spatter from the peripheral equipment does not come into contact with the product.

#### 2. Locations with explosive atmospheres

#### 3. Locations subject to vibration or impact

#### 4. Locations where radiated heat will be received from nearby heat sources

## Operating Environment

### ⚠ Warning

#### 5. Locations that are outdoors (Excludes outdoor specification valves)

Although using an indoor specification product outdoors voids its product warranty, if outdoor use proves unavoidable, be sure to implement the protective measures mentioned below.

1) Install a protective cover, etc., to protect the product from direct sunlight.

2) Encase the product in an enclosure to protect it from rain and wind.

\* If only a roof-type cover is provided for the product, it will not be sufficiently protected from side winds or rain splashing up from the ground, which will result in water adhering to and entering the product. In addition, when the product is encased in an enclosure, be sure to implement proper ventilation measures to prevent overheating due to long-term energizing of the product.

3) Be sure to confirm that the location is not one in which condensation is easily generated.

\* If the product is used in an environment with large temperature changes, etc., condensation may be generated and water may adhere to the external surface of the product. Be sure to implement protective measures against condensation, such as ambient temperature control, in such locations where condensation is easily generated.

#### 6. Locations where freezing may occur within piping lines

##### [When the fluid is liquid]

If the product is to be used in cold regions or in winter, be sure to implement measures to prevent the freezing of fluids.

If the fluid is likely to freeze, implement measures such as draining the water in the piping when the equipment is OFF, or installing a heater or insulation in the piping.

If warming the solenoid valve, be sure to avoid the coil portion as it will result in poor heat dissipation.

##### [When the fluid is air]

With large flow rates, drain may be generated due to adiabatic expansion, resulting in freezing.

Be sure to periodically drain the product or conduct drain removal using an air dryer.

## Fluid

### ⚠ Warning

#### 1. Fluid selection

1) Compatibility between the components and fluids should be checked in the application before use.

2) Since the compatibility of the fluid used may vary depending on its type, additives, concentration, temperature, etc., give sufficient consideration when selecting the material. Please contact SMC if anything is unclear.

3) Use a fluid with a kinematic viscosity of 50 mm<sup>2</sup>/s or less.

#### 2. Do not use the product with the fluids shown below.

1) Fluids that are harmful to humans

2) Combustion-supporting or flammable fluids

3) Corrosive gas

4) Sea water, Saline solution

#### 3. Take measures to prevent static electricity, since some fluids can cause static electricity.

#### 4. Fluid temperature

Operate within the specified operating fluid temperature range.

#### 5. Install a filter (strainer) to ensure clean fluids.

1) The use of a fluid that contains foreign matter can cause problems, such as malfunction and seal failure by promoting the wear of the valve seat and armature, by sticking to the sliding parts of the armature, etc. Install a filter (strainer) on the upstream side of the valve to remove foreign matter.  
Air: 5 μm or less Water: 100 mesh or more

2) Replace or clean the filter (strainer) when the pressure drop reaches 0.1 MPa to prevent them from getting clogged.



# JSX/JSX□ Series

## Specific Product Precautions 2

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

### Fluid Quality

#### ⚠ Warning

##### 1. Air

- 1) Do not use compressed air that contains chemicals, synthetic oils that include organic solvents, salt, corrosive gases, etc., as it can cause malfunction or damage.
- 2) Compressed air that contains excessive drainage may cause the malfunction of valves and other pneumatic equipment. Install an aftercooler or an air dryer on the inlet side of the valve as a countermeasure against drainage.
- 3) If excessive carbon powder is generated by the compressor, it may adhere to the inside of the valves and cause malfunction. Install a mist separator on the inlet side of the valve as a countermeasure to remove any carbon powder.
- 4) For compressed air quality, refer to the Best Pneumatics No. 6 catalogue.
- 5) When operating fluid air with a dew point of  $-70^{\circ}\text{C}$  or lower, the inside of the valve may wear and the product life will be shortened.

##### 2. Water

- 1) Be aware that rust stains, chloride separation, etc., from the piping may cause malfunction, leakage, or, in worse case scenarios, damage due to corrosion. Also, such damage may result in the spraying of fluids or scattering of parts. Please be sure to have protective measures in place in case such incidents should occur.
- 2) In the case that water contains substances such as calcium and magnesium, which generate hard scale and sludge, install water softening equipment and a filter (strainer) directly upstream from the valve to remove these substances, as this scale and sludge can cause the valve to malfunction.
- 3) The water pressure of tap water is usually 0.4 MPa or less, but the pressure can sometimes increase to 1.0 MPa in tall buildings. Therefore, pay attention to the max. operating pressure differential.

##### 3. Oil

Generally, FKM is used as seal material, as it is resistant to oil. The resistance of the seal material may deteriorate depending on the type of oil, manufacturer, or additives. Check the resistance before use.

The kinematic viscosity must not exceed  $50\text{ mm}^2/\text{s}$ .

### Mounting

#### ⚠ Warning

1. Ensure sufficient space for maintenance and inspection.
2. When mounting the product, avoid sources of vibration, or adjust the arm from the body to the min. length so that resonance will not occur.
3. Do not install the product near a heat source and install it in locations where the product is not affected by radiant heat.
4. Do not apply external force to the coil section.  
When the product is installed, apply a wrench to the outside of the piping connection while paying attention that it will not come into contact with the coil.
5. Do not warm the coil section with a heat insulator, etc.  
When insulation is used as a countermeasure against freezing, the insulation should be limited to the piping and body only. Do not insulate the coil. This can cause the coil to burn out.
6. If air leakage increases or equipment does not operate properly, stop operation.  
After installation or during maintenance, check that the product is correctly mounted with appropriate functional and leakage inspections by supplying compressed air and power supplies. Do not use the product when the equipment does not operate correctly.
7. Do not touch the valve while it is being energized or right after it has been energized.  
Valves will reach high temperatures after operation. Use caution, as there is a danger of being burnt if a valve is touched directly.

#### ⚠ Caution

##### 1. Painting and coating

Warnings or specifications printed or labelled on the product should not be erased, removed, or covered up.



# JSX/JSX□ Series Specific Product Precautions 3

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

## How to Assemble Brackets


### ⚠ Caution

#### 1. JSX Series

Body material: Stainless steel (Port size 1/8), Brass, Aluminium

#### How to assemble

- Mount the bracket ① to the bottom of the valve using mounting screws ②.
- Tightening torque  
JSX10: 0.6 N·m ±5 %  
JSX20, 30: 1.5 N·m ±5 %



#### Bracket Assembly Part Nos. (With mounting screws)


| Size | Body material          | Port size     | Thread type    | Bracket assembly part no. | Bracket material |
|------|------------------------|---------------|----------------|---------------------------|------------------|
| 10   | Brass, Stainless steel | 1/8           | Rc<br>NPT<br>G | JSX021-12A-3              | Stainless steel  |
| 20   | Stainless steel        |               |                | JSX022-12A-3              |                  |
| 30   | Brass                  | 1/8, 1/4, 3/8 |                | JSX20-12A-4               |                  |
|      |                        | 1/4, 3/8      |                | VX021N-12A                |                  |
| 20   | Aluminium              | 1/8, 1/4, 3/8 |                | VX022N-12A                |                  |
| 30   |                        | 1/4, 3/8      |                | VX022N-12A                |                  |

#### 2. JSX Series

Body material: Stainless steel (Port sizes 1/4, 3/8)

#### How to assemble

- Insert bracket ① to the IN port side of the valve.
  - Secure it with the hexagon socket set screw ②.
- Tightening torque: 0.4 N·m ±5 %



#### Caution on assembly

- Pay attention to the bracket inserting direction. The positioning hole is on the IN port side only. The bracket cannot be mounted to the OUT port side.
  - The bracket should be mounted after connecting the fitting. (Refer to the “Piping” in the Specific Product Precautions.)
- \* The bracket is shipped together with the product.


#### Bracket Assembly Part Nos. (With set screw)

| Size   | Port size | Thread type | Bracket assembly part no. (With set screw) | Material        |
|--------|-----------|-------------|--|-----------------|
| 20, 30 | 1/4       | Rc, NPT, G  | JSX022-12A-2-1                             | Stainless steel |
|        |           | Rc, NPT     | JSX022-12A-2-1                             |                 |
|        | 3/8       | G           | JSX022-12A-2-2                             |                 |

#### 3. JSXD30 Series: How to assemble brackets

For port sizes 1/4, 3/8

For port sizes 1/2



| Size | Port size | Bracket assembly part no. (With screws) |
|------|-----------|---|
| 30   | 1/4, 3/8  | VXD30S-14A-1                            |
|      | 1/2       | VXD30S-14A-3                            |

\* For the JSXD30 series, the bracket is shipped together with the product.

## Piping

### ⚠ Warning

- There may be cases in which the tubing detaches from the fitting and thrashes around uncontrollably due to tubing degradation or fitting breakage. To prevent this, fit the tubing with a protective cover or secure it in place.
- If using tube piping, secure the product to a permanent fixture. Do not suspend it by the tubing.

### ⚠ Caution


- For handling One-touch fittings, refer to the “Fittings and Tubing Precautions” in the Handling Precautions for SMC Products.

#### 2. Preparation before piping

Before piping is connected, it should be thoroughly blown out with air (flushing) or washed to remove chips, cutting oil, and other debris from inside the pipe. Install piping so that it does not apply pulling, pressing, bending, or other forces on the valve body.

#### 3. Winding of sealant tape

When connecting pipes, fittings, etc., be sure that chips from the pipe threads and sealing material do not enter the valve. Furthermore, when sealant tape is used, leave 1.5 to 2 thread ridges exposed at the end of the threads.



#### 4. Screw tightening torque for piping

When connecting piping to the valve, tighten with the proper tightening torque shown below.

#### Tightening Torque for Piping

| Connection thread | Proper tightening torque [N·m] |
|-------------------|--------------------------------|
| Rc1/8             | 7 to 9                         |
| Rc1/4             | 12 to 14                       |
| Rc3/8             | 22 to 24                       |
| Rc1/2             | 28 to 30                       |
| Rc3/4             | 28 to 30                       |
| Rc1               | 36 to 38                       |
| Rc1 1/2           | 40 to 42                       |
| Rc2               | 48 to 50                       |

#### 5. When using a fitting other than an SMC fitting

Follow the instructions given by the fitting manufacturer.

#### 6. Avoid connecting ground lines to piping, as this may cause the electric corrosion of the system.

#### 7. When connecting piping to a product, avoid mistakes regarding the supply port, etc.

⚠ If the tightening torque is applied to the fitting while the valve is secured to the bracket, the bracket might be broken.



# JSX/JSX□ Series Specific Product Precautions 4

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

## Piping

### ⚠ Caution

#### 8. Recommended piping conditions

When connecting piping to the One-touch fitting, use a pipe length with sufficient margin, in accordance with the piping conditions shown in Fig. 1. Also, when using a tying band, etc., to bind the piping together, make sure that external force does not come to bear on the fitting. (See Fig. 2.)




Fig. 1 Recommended piping

Unit: mm

| Tubing size | Mounting pitch A |                   |                     | Straight line length |
|-------------|------------------|-------------------|---------------------|----------------------|
|             | Nylon tubing     | Soft nylon tubing | Polyurethane tubing |                      |
| Ø 1/8"      | 44 or more       | 29 or more        | 25 or more          | 16 or more           |
| Ø 6         | 84 or more       | 39 or more        | 39 or more          | 30 or more           |
| Ø 1/4"      | 89 or more       | 56 or more        | 57 or more          | 32 or more           |
| Ø 8         | 112 or more      | 58 or more        | 52 or more          | 40 or more           |
| Ø 10        | 140 or more      | 70 or more        | 69 or more          | 50 or more           |
| Ø 12        | 168 or more      | 82 or more        | 88 or more          | 60 or more           |





Fig. 2 When using a tying band to bind the piping together

#### 9. When connecting a fitting to the valve, clamp the side of the body with a vise.

When the vise is used



#### 10. When using a bracket for 1/4 or 3/8 port size, connect the fitting in accordance with the following procedure.

- Step 1) Connect the fittings to both the IN and OUT sides of the valve.
- Step 2) Insert the IN side port of the valve into the bracket hole.
- Step 3) Secure the valve to the bracket with the hexagon socket set screw.

⚠ If the tightening torque is applied to the fitting while the valve is secured to the bracket, the bracket might be broken.


## Wiring

### ⚠ Warning

The solenoid valve is an electrical product. For safety, install an appropriate fuse and circuit breaker before use. When using multiple solenoid valves, it is not sufficient to merely install one fuse. For protecting the equipment more safely, select an appropriate fuse to each circuit of the solenoid valve.

### ⚠ Caution

1. As a rule, use electrical wire with a cross sectional area of 0.5 to 1.25 mm<sup>2</sup> for wiring.
2. External force applied to the lead wire  
If an excessive force is applied to the lead wire, this may cause faulty wiring. Take appropriate measures so that a force of 10 N or more is not applied to the lead wire. Do not bend the lead wires beyond 90° with a radius of less than 20 mm or damage may occur.



3. Use electrical circuits which do not generate chattering in their contacts.
4. Use voltage which is within ±10 % of the rated voltage. In cases with a DC power supply where importance is placed on responsiveness, stay within ±5 % of the rated value. The voltage drop is the value in the lead wire section connecting the coil.
5. When a surge from the solenoid affects the electrical circuitry, install a surge voltage suppressor, etc., in parallel with the solenoid. Or, use the product with a surge voltage suppressor.


Residual voltage of the surge voltage suppressor

DC specification: Approx. 60 V

AC specification: Approx. 1 V

#### 6. Leakage voltage

When the solenoid valve is operated using the controller, etc., the leakage voltage should be the product allowable leakage voltage or less. Particularly when using a resistor in parallel with a switching element and using a C-R element to protect the switching element, take note that leakage current will flow through the resistor, C-R element, etc., creating a possible danger that the valve may not turn off.



AC coil: 5 % or less of rated voltage

DC coil: 2 % or less of rated voltage



# JSX/JSX□ Series Specific Product Precautions 5

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>


## Electrical Connections

### ⚠ Caution

#### 1. Grommet

Lead wire: AWG20 Insulator O.D.: 2.6 mm

| Rated voltage | Lead wire colour |      |
|---------------|------------------|------|
|               | ①                | ②    |
| DC            | Black            | Red  |
| 100 VAC       | Blue             | Blue |
| 200 VAC       | Red              | Red  |
| Other AC      | Grey             | Grey |




\* There is no polarity.

#### 2. Conduit

Lead wire: AWG18 Insulator O.D.: 2.8 mm

| Rated voltage | Lead wire colour |      |              |
|---------------|------------------|------|--------------|
|               | ①                | ②    | ③            |
| DC            | Black            | Red  | Green/Yellow |
| 100 VAC       | Blue             | Blue | Green/Yellow |
| 200 VAC       | Red              | Red  | Green/Yellow |
| Other AC      | Grey             | Grey | Green/Yellow |



\* There is no polarity.

\* ③: Ground wire

#### 3. DIN terminal

##### Disassembly


- After loosening the binding head screw with flange, then if the housing is pulled in the direction of the arrow, the connector will be removed from the solenoid valve.
- Pull out the binding head screw with flange from the housing.
- There is a cutout on the bottom of the terminal block. Insert a small flat head screwdriver, etc., into this cutout, and remove the terminal block from the housing. (Refer to the figure to the right.)
- Remove the gland nut, and pull out the washer and the rubber seal.

##### Wiring

- Pass the cable through the gland nut, washer, and rubber seal in this order, and insert these parts into the housing.
- Loosen the binding head screw of the terminal block, then insert the core wire or the crimped terminal of the lead wire into the terminal, and securely fix it with the binding head screw. The binding head screw of the terminal block is M3.
  - \*1 Tighten the screw to a torque of between 0.5 and 0.6 N·m.
  - \*2 Cable O.D.:  $\varnothing 6$  to  $\varnothing 12$  mm
  - \*3 For an outside cable diameter of  $\varnothing 9$  to  $\varnothing 12$  mm, remove the internal parts of the rubber seal before use.

##### Assembly

- Pass the cable through the gland nut, washer, rubber seal, and the housing in this order, and connect to the terminal block. Then, set the terminal block inside the housing. (Push in the terminal block until it snaps into position.)
- Insert the rubber seal and the washer in this order into the cable entry of the housing, and then tighten the gland nut securely.
- Insert the gasket between the bottom part of the terminal block and the plug attached to the equipment, and then insert the binding head screw with flange from the top of the housing, and tighten it.
  - \*1 Tighten the screw to a torque of between 0.5 and 0.6 N·m.
  - \*2 The orientation of the connector can be changed in steps of  $90^\circ$  by changing the method of assembling the housing and the terminal block.




\*1 The position is fixed regardless of the electrical entry direction.

##### For the JSX10

##### Compatible cable

Cord O.D.:  $\varnothing 3.5$  to  $\varnothing 7$

(Reference)  $0.5 \text{ mm}^2$ , 2-core or 3-core, equivalent to JIS C 3306






# JSX/JSX□ Series Specific Product Precautions 6

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

## Electrical Connections

### ⚠ Caution

Internal connections are as shown below. Make connections to the power supply accordingly.




| Terminal no. | 1     | 2     |
|--------------|-------|-------|
| DIN terminal | + (-) | - (+) |

\* There is no polarity.

### DIN (EN 175301-803) Terminal


This DIN terminal corresponds to the Form C DIN connector with an 8 mm terminal pitch.



Size: 10

Applicable cable O.D.:  $\varnothing 3.5$  to  $\varnothing 7$

This DIN terminal corresponds to the Form A DIN connector with an 18 mm terminal pitch.



Size: 20, 30

Applicable cable O.D.:  $\varnothing 6$  to  $\varnothing 12$

### 4. M12 connector


- The IP67 (enclosure) rating of the valve can be obtained by using a cable with a female connector of IP67 specification. Please note that this product cannot be used in water.
- Do not use a tool to mount the connector as this may cause damage. Only tighten it by hand. (0.39 to 0.49 N·m)
- Avoid repeatedly bending or stretching the cable and applying heavy objects or force to it.
- Do not pull the connector or cable unnecessarily.
- Do not bend the cable at the root of the connector when installed.

### ■ Coding and pin arrangement of the M12 connector on the valve side

The shape (coding) and pin arrangement of the M12 connector are as follows.

DC specification: A-coded, 4-pin

AC specification: B-coded, 4-pin



\* The solenoid valve has no polarity for DC voltages.

When using the cable with a female connector, make sure that the coding is correct. When installing the cable, be sure to align the key on the cable side connector (female side) with the key on the valve side connector (male side).


Be careful not to squeeze it in the wrong direction as pin damage, etc., may result.

## Electrical Circuits

### ⚠ Caution


#### 1. DC circuit

##### ● Grommet




Without electrical option

##### ● Grommet, Conduit, DIN terminal




With surge voltage suppressor

##### ● DIN terminal



With light/surge voltage suppressor

##### ● M12 Connector




With surge voltage suppressor

#### 2. AC circuit


The standard product is equipped with a surge voltage suppressor.

##### Grommet, Conduit, DIN terminal, M12 connector



\*1 For M12 connector  
Without electrical option

##### DIN terminal



With light



# JSX/JSX□ Series

## Specific Product Precautions 7

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

### Maintenance

#### Warning

##### 1. Removal of product

- 1) Shut off the fluid supply and release the fluid pressure in the system.
- 2) Shut off the power supply.
- 3) Confirm that the valve temperature has dropped sufficiently before removing the product.

##### 2. Replace or clean filters (strainers) periodically.

- 1) Replace filters after one year of use, or earlier if the pressure drop reaches 0.1 MPa.
- 2) Clean strainers when the pressure drop reaches 0.1 MPa.

##### 3. Exhaust the drainage from air filters periodically.

If condensation in the drain bowl is not emptied on a regular basis, the bowl will overflow and allow the condensation to enter the compressed air lines. This causes the malfunction of pneumatic equipment. If the drain bowl is difficult to check and remove, the installation of a drain bowl with an auto drain option is recommended.

##### 4. Low frequency operation

Switch valves at least once every 30 days to prevent malfunction. Also, in order to use them under the optimum state, conduct a regular inspection biannually.

##### 5. Storage

In the case of long-term storage after use, thoroughly remove all moisture and store it in a location where the product is not exposed to sunlight and higher humidity to prevent rust and deterioration of rubber materials, etc.

##### 6. Perform a maintenance and inspection periodically.

Confirm that the product is mounted correctly by conducting suitable function and leakage tests periodically. If air leakage increases or equipment does not operate properly, stop operation.

### Return of Product

#### Warning

If the product to be returned is contaminated or is possibly contaminated with substances that are harmful to humans, for safety reasons, please contact SMC beforehand and then employ a specialist cleaning company to decontaminate the product. After the decontamination prescribed above has been carried out, submit a Product Return Request Sheet or the Detoxification/Decontamination Certificate to SMC and await SMC's approval and further instructions before attempting to return the item.

Please refer to the International Chemical Safety Cards (ICSC) for a list of harmful substances.

If you have any further questions, please don't hesitate to contact your SMC sales representative.

### JSXD Precautions

#### Warning

1. For pilot operated 2-port solenoid valves, when the valve is closed, sudden pressure resulting from the startup of the fluid supply source (pump, compressor, etc.) may cause the valve to open momentarily and leakage to occur, so please exercise caution.
2. If the product is used in the conditions in which rapid decrease in the inlet pressure of the valve and rapid increase in the outlet pressure of the valve are repeated, excessive stress will be applied to the diaphragm, which causes the diaphragm to be damaged and dropped, leading to the operation failure of the valve. Check the operating conditions before use.
3. Min. operating pressure differential  
Be aware that even if the pressure difference is above the min. operating pressure differential when the valve is closed, the pressure difference may fall below the min. operating pressure differential when the valve opens, depending on the capacity of the supply source (pumps, compressors, etc.) or the type of pipe restrictions (the piping is bent continuously due to elbow or tee, or narrow tube nozzle is installed in the end). If the product is used below the min. operating pressure, the operation becomes unstable, which might cause valve opening or closing failure, or oscillation, leading to failure due to insufficient pressure differential. Select an appropriate valve size with reference to the flow rate characteristics and flow rate characteristics table on pages 40 to 46.



# JSX/JSX□ Series Specific Product Precautions 8



Be sure to read this before handling the products. Refer to the back cover for safety instructions. For 2-port solenoid valve for fluid control precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

## Replacing the Solenoid Coils


### Warning

1. When replacing the solenoid coil, turn off the power supply.
2. Be careful for possible high temperature of the solenoid coil due to the fluid temperature and operating conditions.

### Caution




Insert a flat head screwdriver, etc., into the groove in the clip and slide it in the direction of ① to remove it.




Once the clip has been removed, the coil can be removed from above (in the direction of ②).


Insert the replacement coil into the body assembly, and then insert the clip by aligning it with the groove in the top of the body assembly.



Be sure to confirm the clip direction (back and front) as well as the insertion state.



OK



NG

Clip direction



OK



NG

Inserted condition

\* When inserting the coil, be sure to push it in until the groove in the body assembly is visible.

## Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “Caution,” “Warning” or “Danger.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)<sup>1)</sup>, and other safety regulations.

-  **Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.
-  **Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.
-  **Danger:** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

- 1) ISO 4414: Pneumatic fluid power – General rules relating to systems.  
ISO 4413: Hydraulic fluid power – General rules relating to systems.  
IEC 60204-1: Safety of machinery – Electrical equipment of machines.  
(Part 1: General requirements)  
ISO 10218-1: Manipulating industrial robots - Safety.  
etc.

## Warning

### 1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalogue information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

### 2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

### 3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

### 4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalogue.
3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

## Caution

### 1. The product is provided for use in manufacturing industries.

The product herein described is basically provided for peaceful use in manufacturing industries.

If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary. If anything is unclear, contact your nearest sales branch.

## Limited warranty and Disclaimer/Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”. Read and accept them before using the product.

### Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.<sup>2)</sup> Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided. This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalogue for the particular products.
- 2) Vacuum pads are excluded from this 1 year warranty.  
A vacuum pad is a consumable part, so it is warranted for a year after it is delivered. Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

### Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

## Caution

### SMC products are not intended for use as instruments for legal metrology.

Measurement instruments that SMC manufactures or sells have not been qualified by type approval tests relevant to the metrology (measurement) laws of each country.

Therefore, SMC products cannot be used for business or certification ordained by the metrology (measurement) laws of each country.

## Safety Instructions

Be sure to read “Handling Precautions for SMC Products” (M-E03-3) before using.

## Revision History

|                  |  |    |
|------------------|--|----|
| <b>Edition B</b> | - The JSXD and JSXM have been added.<br>- Brass and aluminium body materials have been added.<br>- An M12 connector electrical entry option has been added.<br>- Number of pages has been increased from 24 to 56. | ZV |
|------------------|--|----|

## SMC Corporation (Europe)

|                       |                   |                       |                        |
|-----------------------|-------------------|-----------------------|------------------------|
| <b>Austria</b>        | +43 (0)2262622800 | www.smc.at            | office@smc.at          |
| <b>Belgium</b>        | +32 (0)33551464   | www.smc.be            | info@smc.be            |
| <b>Bulgaria</b>       | +359 (0)2807670   | www.smc.bg            | office@smc.bg          |
| <b>Croatia</b>        | +385 (0)13707288  | www.smc.hr            | office@smc.hr          |
| <b>Czech Republic</b> | +420 541424611    | www.smc.cz            | office@smc.cz          |
| <b>Denmark</b>        | +45 70252900      | www.smc.dk.com        | smc@smcdk.com          |
| <b>Estonia</b>        | +372 6510370      | www.smc.pneumatics.ee | smc@info@smcee.ee      |
| <b>Finland</b>        | +358 207513513    | www.smc.fi            | smc@info@smc.fi        |
| <b>France</b>         | +33 (0)164761000  | www.smc-france.fr     | info@smc-france.fr     |
| <b>Germany</b>        | +49 (0)61034020   | www.smc.de            | info@smc.de            |
| <b>Greece</b>         | +30 210 2717265   | www.smc.hellas.gr     | sales@smchellas.gr     |
| <b>Hungary</b>        | +36 23513000      | www.smc.hu            | office@smc.hu          |
| <b>Ireland</b>        | +353 (0)14039000  | www.smc.automation.ie | sales@smcautomation.ie |
| <b>Italy</b>          | +39 03990691      | www.smc.italia.it     | mailbox@smcitalia.it   |
| <b>Latvia</b>         | +371 67817700     | www.smc.lv            | info@smc.lv            |

|                    |                     |                         |                             |
|--------------------|---------------------|-------------------------|-----------------------------|
| <b>Lithuania</b>   | +370 5 2308118      | www.smc.lt              | info@smc.lt                 |
| <b>Netherlands</b> | +31 (0)205318888    | www.smc.nl              | info@smc.nl                 |
| <b>Norway</b>      | +47 67129020        | www.smc-norge.no        | post@smc-norge.no           |
| <b>Poland</b>      | +48 222119600       | www.smc.pl              | office@smc.pl               |
| <b>Portugal</b>    | +351 214724500      | www.smc.eu              | apoioclientept@smc.smces.es |
| <b>Romania</b>     | +40 213205111       | www.smcromania.ro       | smcromania@smcromania.ro    |
| <b>Russia</b>      | +7 (812)3036600     | www.smc.eu              | sales@smcru.com             |
| <b>Slovakia</b>    | +421 (0)413213212   | www.smc.sk              | office@smc.sk               |
| <b>Slovenia</b>    | +386 (0)73885412    | www.smc.si              | office@smc.si               |
| <b>Spain</b>       | +34 945184100       | www.smc.eu              | post@smc.smces.es           |
| <b>Sweden</b>      | +46 (0)86031240     | www.smc.nu              | smc@smc.nu                  |
| <b>Switzerland</b> | +41 (0)523963131    | www.smc.ch              | info@smc.ch                 |
| <b>Turkey</b>      | +90 212 489 0 440   | www.smc.pnomatik.com.tr | info@smcpnomatik.com.tr     |
| <b>UK</b>          | +44 (0)845 121 5122 | www.smc.uk              | sales@smc.uk                |

**South Africa** +27 10 900 1233    www.smcza.co.za    zasales@smcza.co.za