

# 3-Colour Display Digital Flow Switch for Large Flow

Applicable fluid **Air, N<sub>2</sub>**



## IO-Link

The flow rate value and the device status can be figured out easily via the process data.



<b>Diagnostic contents</b>	Over current error, Rated/Accumulated flow error, Flow/Temperature sensor failure, Internal product malfunction
----------------------------	---

### How to Order

**PF3A 7 03 H - 10 - L Q - M**

- Type**

7	Integrated display
---	--------------------
- Rated flow range**

03	30 to 3000 l/min
06	60 to 6000 l/min
12	120 to 12000 l/min
- Large flow type**
- Thread type**

—	Rc
N	NPT
F*1	G

\*1 ISO 1179-1 compliant
- Port size**

Symbol	Port size	Rated flow range		
		03	06	12
10	1	●	—	—
14	1 1/2	—	●	—
20	2	—	—	●
- Calibration certificate\*9**

—	None
A*10	Yes

\*9 The certificate is in both English and Japanese.  
\*10 Made to order
- Unit specification**

—	Units selection function*7
M	SI unit only*8

\*7 This product is for overseas use only. (The SI unit type is provided for use in Japan in accordance with the New Measurement Act.)  
\*8 Fixed unit: Instantaneous flow: l/min  
Accumulated flow : L
- Options**

—	With lead wire and M12 connector (3 m)*5
N	Without lead wire and M12 connector
Q	Lead wire and M12-M12 connector (3 m)*6

\*5 Option is shipped together, but not assembled.  
\*6 The lead wire has an M12 (female) connector on one side and an M12 (male) connector on the other side.
- Output specification**

Symbol	OUT	FUNC*2	Applicable monitor unit model
L	IO-Link: Switch output (N/P)	—	—
L3	IO-Link: Switch output (N/P)	Analogue voltage output*3 ⇔ External input*4	PFG300 series
L4	IO-Link: Switch output (N/P)	Analogue current output ⇔ External input*4	PFG310 series

**Options/Part Nos.**  
When only optional parts are required, order with the part number listed below.

Part no.	Option	Note
ZS-37-A	Lead wire and M12 connector	Length: 3 m
ZS-49-A	Lead wire and M12-M12 connector	Male/female conversion Length: 3 m

\*2 Analogue output or external input can be selected by pressing the buttons.  
Analogue output is set as default setting.  
Output signal "L" cannot be used as the FUNC terminal is not connected.  
\*3 1 to 5 V or 0 to 10 V can be selected by pressing the button.  
The default setting is 1 to 5 V.  
\*4 The accumulated value, peak value, and bottom value can be reset.

## PF3A7□H-L Series

# PF3A7□H-L Series

For flow switch precautions and specific product precautions, refer to the Operation Manual on the SMC website.

## Specifications (Integrated Display)

Model		PF3A703H-L	PF3A706H-L	PF3A712H-L
Electrical	Power supply voltage	When used as a switch output device	24 VDC ±10 %	
		When used as an IO-Link device	18 to 30 VDC ±10 %	
Switch output	Output type		Select from NPN or PNP open collector output.	
	Output mode		Select from Hysteresis, Window comparator, Accumulated output, Accumulated pulse output, Error output, or Switch output OFF modes.	
	Max. applied voltage		30 V (NPN output)	
	Internal voltage drop (Residual voltage)		1.5 V or less (at load current of 80 mA)	
	Delay time*1		3.3 ms or less, variable from 0 to 60 s/0.01 s increments	
Analogue output	Response time*2		Linked to the set value of the digital filter	
Display	Display		LCD, 2-screen display (Main screen/Sub screen) Main screen: Red/Green, Sub screen: Orange Main screen/Sub screen: 9 digits (7 segments 7 digits, 11 segments 2 digits)	
	Digital filter*3		Select from 1 s, 2 s, or 5 s.	
Standards		CE marking (EMC Directive, RoHS Directive)		

\*1 The time from when the instantaneous flow reaches the set value to when the switch output operates can be set.

\*2 The time from when the flow is changed by a step input (when the flow rate changes from 0 to the maximum value of the rated flow range instantaneously) until the analogue output reaches 90 % of the rated flow rate.

\*3 The time for the digital filter can be set to the sensor input. The response time indicates when the set value is 90 % in relation to the step input.


## Communication Specifications (IO-Link mode)

IO-Link type	Device
IO-Link version	V 1.1
Communication speed	COM2 (38.4 kbps)
Configuration file	IODD file*1
Minimum cycle time	3.3 ms
Process data length	Input data: 4 bytes, Output data: 0 byte
On request data communication	Yes
Data storage function	Yes
Event function	Yes
Vendor ID	131 (0 x 0083)
Device ID*2	PF3A703H-□□-L□-□□ : 400 (0 x 0190)
	PF3A703H-□□-L3□-□□: 401 (0 x 0191)
	PF3A703H-□□-L4□-□□: 402 (0 x 0192)
	PF3A706H-□□-L□-□□ : 403 (0 x 0193)
	PF3A706H-□□-L3□-□□: 404 (0 x 0194)
	PF3A706H-□□-L4□-□□: 405 (0 x 0195)
	PF3A712H-□□-L□-□□ : 406 (0 x 0196)
	PF3A712H-□□-L3□-□□: 407 (0 x 0197)
	PF3A712H-□□-L4□-□□: 408 (0 x 0198)

\*1 The configuration file can be downloaded from the SMC website, <https://www.smcworld.com>

\*2 The device ID differs according to each product type (output specification).

Other specifications that are not listed are the same as those of the standard product. For details, refer to the **Web Catalogue**.



## SMC Corporation (Europe)

<b>Austria</b>	+43 (0)2262622800	www.smc.at	office@smc.at
<b>Belgium</b>	+32 (0)33551464	www.smc.be	info@smc.be
<b>Bulgaria</b>	+359 (0)2807670	www.smc.bg	office@smc.bg
<b>Croatia</b>	+385 (0)13707288	www.smc.hr	office@smc.hr
<b>Czech Republic</b>	+420 541424611	www.smc.cz	office@smc.cz
<b>Denmark</b>	+45 70252900	www.smc.dk.com	smc@smcdk.com
<b>Estonia</b>	+372 6510370	www.smc.pneumatics.ee	info@smcee.ee
<b>Finland</b>	+358 207513513	www.smc.fi	smc.fi@smc.fi
<b>France</b>	+33 (0)164761000	www.smc-france.fr	info@smc-france.fr
<b>Germany</b>	+49 (0)61034020	www.smc.de	info@smc.de
<b>Greece</b>	+30 210 2717265	www.smchellas.gr	sales@smchellas.gr
<b>Hungary</b>	+36 23513000	www.smc.hu	office@smc.hu
<b>Ireland</b>	+353 (0)14039000	www.smc.automation.ie	sales@smc.automation.ie
<b>Italy</b>	+39 03990691	www.smc.italy.it	mailbox@smc.italy.it
<b>Latvia</b>	+371 67817700	www.smc.lv	info@smc.lv

<b>Lithuania</b>	+370 5 2308118	www.smclt.lt	info@smclt.lt
<b>Netherlands</b>	+31 (0)205318888	www.smc.nl	info@smc.nl
<b>Norway</b>	+47 67129020	www.smc-norge.no	post@smc-norge.no
<b>Poland</b>	+48 222119600	www.smc.pl	office@smc.pl
<b>Portugal</b>	+351 214724500	www.smc.eu	apoioclientept@smc.smces.es
<b>Romania</b>	+40 213205111	www.smcromania.ro	smcromania@smcromania.ro
<b>Russia</b>	+7 8123036600	www.smc.eu	sales@smcru.com
<b>Slovakia</b>	+421 (0)413213212	www.smc.sk	office@smc.sk
<b>Slovenia</b>	+386 (0)73885412	www.smc.si	office@smc.si
<b>Spain</b>	+34 945184100	www.smc.eu	post@smc.smces.es
<b>Sweden</b>	+46 (0)86031200	www.smc.nu	smc@smc.nu
<b>Switzerland</b>	+41 (0)523963131	www.smc.ch	helpcenter@smc.ch
<b>Turkey</b>	+90 212 489 0 440	www.smc.pnomatik.com.tr	info@smc.pnomatik.com.tr
<b>UK</b>	+44 (0)845 121 5122	www.smc.uk	sales@smc.uk

**SMC Corporation** Akihabara UDX 15F, 4-14-1, Sotokanda, Chiyoda-ku, Tokyo 101-0021, JAPAN Phone: 03-5207-8249, Fax: 03-5298-5362